



HESTORE.HU

elektronikai alkatrész áruház

EN: This Datasheet is presented by the manufacturer.

Please visit our website for pricing and availability at www.hestore.hu.

High Sensitivity GPS Module

- Built-in SiRFstarIII chipsets receivers give unparalleled GPS performance and precision.
- Built-in WAAS/EGNOS Demodulator.
- 20 parallel satellite-tracking channels for fast acquisition and reacquisition.
- Low power consumption and ultra compact size-only 32x32x9mm.
- Allow the receiver to track up to 12-channel satellites.
- Built-in rechargeable battery for memory and RTC backup.
- Supports NMEA0183 v2.2 data protocol.
- Enhanced algorithms providing superior navigation performance in urban, canyon and foliage environments.
- Applications include Vehicular Navigation. Marine Navigation. Fleet management, AVL and Location-Based Services, Autopilot.

SPECIFICATIONS

Receiver :	Tracking up to 20 satellites L1, 1575.42 MHz, C/A code
Accuracy :	Position: 2DRMS approximately 5m, WAAS support Velocity: 0.1 m/s without SA imposed Time: 1! sec
Acquisition Time :	Cold Start: 42s (Average) Warm Start: 38s (Average) Hot Start: 1s (Minimum)
Sensitivity :	Acquisition: -148dBm Tracking: -159dBm
Dynamics :	Max Altitude: 18000m Max Velocity: 515m/s Max Acceleration: ! 4g
Navigation Update Rate :	Once per second
Serial Port :	TTL, MMCX
Baud Rate :	4800 bps (Optional 9600,19300,38400 bps)
Output Message :	NMEA0283 V2.2 GGA, GSV, GSA, RMC (optional VTG, GLL)
Datum :	WGS 84
Power Supply :	DC 3.3~5V
Power Consumption :	Typical 80mA @5V
LED Indicator :	Power On/Off Navigation
Operating Temperature :	-40"~ +85" C
Storage Temperature :	-40 " ~ +100" C
Humidity :	5%~95%
Antenna Type :	Built-in patch antenna

