
EN: This Datasheet/Document is presented by the manufacturer.

Please visit our website for pricing and availability at www.hestore.hu.

2SD965

TRANSISTOR (NPN)

SOT-89



1. BASE
2. COLLECTOR
3. EMITTER

FEATURES

- Low Collector-Emitter Saturation Voltage
- Large Collector Power Dissipation and Current
- Mini Power Type Package

MARKING : D965

MAXIMUM RATINGS (T_a=25℃ unless otherwise noted)


Symbol	Parameter	Value	Unit
V_{CBO}	Collector-Base Voltage	42	V
V_{CEO}	Collector-Emitter Voltage	22	V
V_{EBO}	Emitter-Base Voltage	7.5	V
I_{CM}	Collector Current	5	A
P_C	Collector Power Dissipation	750	mW
$R_{\theta JA}$	Thermal Resistance From Junction To Ambient	167	℃/W
T_j	Junction Temperature	150	℃
T_{stg}	Storage Temperature	-55~+150	℃


ELECTRICAL CHARACTERISTICS (T_a=25℃ unless otherwise specified)

Parameter	Symbol	Test conditions	Min	Typ	Max	Unit
Collector-base breakdown voltage	$V_{(BR)CBO}$	I_C=100μA,I_E=0	40			V
Collector-emitter breakdown voltage	$V_{(BR)CEO}$	I_C=1mA,I_B=0	20			V
Emitter-base breakdown voltage	$V_{(BR)EBO}$	I_E=10μA,I_C=0	7			V
Collector cut-off current	I_{CBO}	V_{CB}=10V,I_E=0			0.1	μA
Emitter cut-off current	I_{EBO}	V_{EB}=7V,I_C=0			0.1	μA
DC current gain	$h_{FE(1)}$	V_{CE}=2V, I_C=1mA		200		
	$h_{FE(2)}$	V_{CE}=2V, I_C=500mA	340		1000	
	$h_{FE(3)}$	V_{CE}=2V, I_C=2A	150			
Collector-emitter saturation voltage	$V_{CE(sat)}$	I_C=3A,I_B=0.1A			1	V
Transition frequency	f_T	VCE=6V,IC=50mA，f=200MHz		150		MHz
Collector output capacitance	C_{ob}	V_{CB}=20V, I_E=0, f=1MHz			50	pF


CLASSIFICATION OF $h_{FE(2)}$

RANK	R	S
RANGE	340 -600	560 -1000






SOT-89 Package Outline Dimensions



Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min	Max	Min	Max
A	1.400	1.600	0.055	0.063
b	0.320	0.520	0.013	0.020
b1	0.400	0.580	0.016	0.023
c	0.350	0.440	0.014	0.017
D	4.400	4.600	0.173	0.181
D1	1.550 REF.		0.061 REF.	
E	2.300	2.600	0.091	0.102
E1	3.940	4.250	0.155	0.167
e	1.500 TYP.		0.060 TYP.	
e1	3.000 TYP.		0.118 TYP.	
L	0.900	1.200	0.035	0.047

SOT-89 Suggested Pad Layout



Note:
1.Controlling dimension:in millimeters.
2.General tolerance:±0.05mm.
3.The pad layout is for reference purposes only.

NOTICE

we reserve the right to make modifications,enhancements, improvements, corrections or other changes without further notice to any product herein. we does not assume any liability arising out of the application or use of any product described herein.