

EN: This Datasheet is presented by the manufacturer.


Please visit our website for pricing and availability at www.hestore.hu.

KEMET Part Number: C4ASPBW4120A3JJ

(4ASPBW4120A3JJ)



Film, Metallized Polypropylene, Power, KEMET, C4AS, 1.2 uF, 5%, 1,200 V, 70C, Lead Spacing = 37.5mm



Dimensions	
L	42.5mm NOM
Н	37mm NOM
Т	28mm NOM
S	37.5mm +/-0.4mm
LL	6mm -2mm

Packaging Specifications		
Packaging:	Bulk	
Packaging Quantity:	36	

General Information		
Dielectric:	Metallized Polypropylene	
Style:	Radial	
Supplier:	KEMET	
Series:	C4AS	
RoHS:	Yes	
Lead:	4 Wire Leads	

Specifications		
Capacitance:	1.2 uF	
Capacitance Tolerance:	5%	
Voltage DC:	1200 VDC	
Voltage AC:	630 VAC	
Temperature Range:	-40/+85C	
Rated Temperature:	70C	
Dissipation Factor:	0.05%	
Max dVdt:	965 V	
Resistance:	2.9 mOhms (100kHz)	
Current:	28 Amps (100kHz 70C), 1158 Amps (Peak)	

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.

