
EN: This Datasheet/Document is presented by the manufacturer.

Please visit our website for pricing and availability at www.hestore.hu.

General Purpose Transistor

multicomp PRO





Pin Configuration:
1. Emitter
2. Base
3. Collector

Description:

General purpose NPN silicon planar epitaxial transistors, best suited for use in driver stages of audio amplifiers, low noise input stages of tape recorders. Hi-Fi amplifiers, signal processing circuits of television receivers.

Absolute Maximum Ratings

Parameter	Symbol	Value	Units
Collector-Emitter Voltage	V_{CEO}	45	V
Collector-Emitter Voltage	V_{CES}	50	
Emitter-Base Voltage	V_{EBO}	6	
Collector Current Continuous	I_C	100	mA
Power Dissipation at T_a = 25°C Derate Above 25°C	P_D	350 2.8	mW mW/°C
Total Device Dissipation at T_c = 25°C Derate Above 25°C		1 8	W mW/°C
Operating and Storage Junction Temperature Range	T_j, T_{stg}	-55 to + 150	°C

Thermal Resistance

Junction to Ambient	$R_{th\ (j\text{-}a)}$	375	ºC/W
Junction to Case	$R_{th\ (j\text{-}c)}$	125	

Electrical Characteristics (T_a = 25°C unless otherwise specified)


Parameter	Symbol	Test Condition	Min.	Typ.	Max.	Units
Collector Emitter Voltage	V_{CEO}	I_C = 2mA, I_B = 0	45	-	-	V
Emitter Base Voltage	V_{EBO}	I_E = 100µA, I_C = 0	6	-	-	
Collector Cut off Current	I_{CES}	V_{CE} = 50V, V_{BE} = 0 V_{CE} = 50V, V_{BE} = 0, T_a = 125°C	-	-	15 4	nA µA
DC Current Gain	h_{FE}	I_C = 2mA, V_{CE} = 50V	200	290	460	-
Collector Emitter Saturation Voltage	$V_{CE\ (sat)}$	I_C = 10mA, I_B = 0.5mA I_C = 100mA, I_B = 5mA*	-	0.07 0.2	0.2 0.6	V
Base Emitter Saturation Voltage	$V_{BE\ (sat)}$	I_C = 10mA, I_B = 0.5mA I_C = 100mA, I_B = 0.5mA*	-	0.6	0.83 1.05	
Base Emitter On Voltage	$V_{BE\ (on)}$	I_C = 100µA, V_{CE} = 5V I_C = 2mA, V_{CE} = 5V I_C = 100mA, V_{CE} = 5V*	0.55	0.5 0.62 0.83	0.7	

Dynamic Characteristics

Transition Frequency	f_T	I_C = 0.5mA, V_{CE} = 3V f = 100MHz I_C = 10mA, V_{CE} = 5V f = 100MHz	- 150	100 200	-	MHz
Collector Output Capacitance	C_{ob}	V_{CB} = 10V, I_E = 0 f = 1MHz	-	-	4.5	pF
Emitter Input Capacitance	C_{ib}	V_{EB} = 0.5V, I_E = 0 f = 1MHz	-	8		
Noise Figure	NF	V_{CE} = 5V, I_C = 2mA Rs = 2kW, f = 1kHz F = 200Hz	-	2	10	dB

*Pulse Condition: Pulse Width 300µs, Duty Cycle 2%.

General Purpose Transistor



Dimensions	Min.	Max.
A	4.32	5.33
B	4.45	5.2
C	3.18	4.19
D	0.41	0.55
E	0.35	0.5
F	5°	
G	1.14	1.4
H	1.14	1.53
K	12.7	-
L	1.982	2.082

Dimensions : Millimetres

Pin Configuration:

1. Emitter
2. Base
3. Collector

Part Number Table

Description	Part Number
Transistor, NPN, TO-92	BC237B

Important Notice : This data sheet and its contents (the "Information") belong to the members of the AVNET group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp Pro is the registered trademark of Premier Farnell Limited 2019.