



**EN:** This Datasheet/Document is presented by the manufacturer.

Please visit our website for pricing and availability at [www.hestore.hu](http://www.hestore.hu).

**Aufbau:**

32 mA – 2 A: Glasrohr, durchsichtig

2,5 A – 16 A: Glasrohr, mit Löschmittel

**Kontaktkappen:**

Messing, vernickelt

**Lötbarkeit:** gemäß EN 60068-2-20**Verpackungsmöglichkeiten:**

100 St. = 10 x 10er Faltschachteln

500 St. = Industrieverpackung (lose geschüttet in Faltkarton)

Als Baugruppe mit 2 Aufsteckkappen in beliebiger Form und Länge, fertig montiert

**Construction:**

32 mA – 2 A: Glasstube, transparent

2,5 A – 16 A: Glasstube, with extinguishing agent

**Contact caps:**

Brass, nickel plated

**Solderability:** by EN 60068-2-20**Packing options:**

100 pcs. = 10 boxes of 10 pieces

500 pcs. = Industrial box (loose in carton)

As assembly with two pigtails in various forms and lengths, finally mounted

**Bemessungswerte / Ratings**

| Art.-<br>No. | Strom<br>Current | Spannung<br>Voltage | Ausschaltvermögen<br>Breaking capacity | Spannungsfall<br>Voltage drop<br>max [mV] | Schmelzintegral<br>Melting integral<br>[A <sup>2</sup> s] |
|--------------|------------------|---------------------|----------------------------------------|-------------------------------------------|-----------------------------------------------------------|
| 632.302      | 32 mA            | 250 V               | 35 A                                   | 14.000                                    | auf Anfrage                                               |
| 632.303      | 40 mA            | 250 V               | 35 A                                   | 4.000                                     | 0,0090                                                    |
| 632.304      | 50 mA            | 250 V               | 35 A                                   | 3.500                                     | auf Anfrage /                                             |
| 632.305      | 63 mA            | 250 V               | 35 A                                   | 2.000                                     | on request                                                |
| 632.306      | 80 mA            | 250 V               | 35 A                                   | 2.000                                     | 0,0323                                                    |
| 632.307      | 100 mA           | 250 V               | 35 A                                   | 2.000                                     | 0,0787                                                    |
| 632.308      | 125 mA           | 250 V               | 35 A                                   | 1.000                                     | auf Anfrage                                               |
| 632.309      | 160 mA           | 250 V               | 35 A                                   | 750                                       | 0,0225                                                    |
| 632.310      | 200 mA           | 250 V               | 35 A                                   | 750                                       | 0,1046                                                    |
| 632.311      | 250 mA           | 250 V               | 35 A                                   | 650                                       | 0,0250                                                    |
| 632.312      | 315 mA           | 250 V               | 35 A                                   | 650                                       | 0,28                                                      |
| 632.313      | 400 mA           | 250 V               | 35 A                                   | 1.700                                     | 0,12                                                      |
| 632.314      | 500 mA           | 250 V               | 35 A                                   | 1.600                                     | 0,45                                                      |
| 632.315      | 630 mA           | 250 V               | 35 A                                   | 180                                       | 2,09                                                      |
| 632.316      | 800 mA           | 250 V               | 35 A                                   | 180                                       | 5,77                                                      |
| 632.317      | 1 A              | 250 V               | 35 A                                   | 180                                       | 5,90                                                      |
| 632.318      | 1,25 A           | 250 V               | 35 A                                   | 180                                       | 11,96                                                     |
| 632.319      | 1,6 A            | 250 V               | 35 A                                   | 180                                       | 6,35                                                      |
| 632.320      | 2 A              | 250 V               | 35 A                                   | 180                                       | 58,68                                                     |
| 632.321      | 2,5 A            | 250 V               | 1.000 A                                | 300                                       | 12,01                                                     |
| 632.322      | 3,15 A           | 250 V               | 1.000 A                                | 300                                       | 20,64                                                     |
| 632.323      | 4 A              | 250 V               | 1.000 A                                | 300                                       | 30,88                                                     |
| 632.324      | 5 A              | 250 V               | 1.000 A                                | 300                                       | 60,75                                                     |
| 632.325      | 6,3 A            | 250 V               | 1.000 A                                | 300                                       | 83,72                                                     |
| 632.326      | 8 A              | 250 V               | 1.000 A                                | 200                                       | 145,92                                                    |
| 632.327      | 10 A             | 250 V               | 1.000 A                                | 200                                       | 230,00                                                    |
| 632.328      | 12,5 A           | 250 V               | 1.000 A                                | 200                                       | 434,37                                                    |
| 632.330      | 16 A             | 250 V               | 1.000 A                                | 180                                       | 908,80                                                    |

**Schmelzzeit-Grenzwert / Pre-arcing time limits**

| Bemessungsstrom<br>Rated current | 1,15 I <sub>rat</sub><br>min.. | 2,0 I <sub>rat</sub><br>max. | 2,75 I <sub>rat</sub><br>min max. | 4 I <sub>rat</sub><br>min max. | 10 I <sub>rat</sub><br>max. |
|----------------------------------|--------------------------------|------------------------------|-----------------------------------|--------------------------------|-----------------------------|
| 32 mA – 2 A                      | 1 h                            | 10 min.                      | 150 ms 5 s                        | 60 ms 1 s                      | 200 ms                      |
| 2,5 A – 10 A                     | 1 h                            | 30 min.                      | 300 ms 5 s                        | 80 ms 2 s                      | 300 ms                      |