




EN: This Datasheet/Document is presented by the manufacturer.

Please visit our website for pricing and availability at www.hestore.hu.

Carbon Film Resistor

SRPASSIVES



Specifications

POWER PATING	MAXIMUN WORKING VOLTAGE	MAXIMUN OVERLOAD VOLTAGE	DIMENSIONS(mm)				RESISTANCE RANGE
			L	D	H	d±0.02	
1/6W, 1/8W	200V	400V	3.2±0.2	1.8±0.2	28±2.0	0.43	STANDARD 1 Ω~10M Ω
1/4WS	250V	500V	3.2±0.2	1.8±0.2	28±2.0	0.43	
1/4W	250V	500V	6.0±0.5	2.3±0.5	28±2.0	0.50	
1/2WS	350V	700V	6.0±0.5	2.3±0.5	28±2.0	0.50	
1/2W	350V	700V	9.0±0.5	3.2±0.5	26±2.0	0.60	
1WS	500V	1000V	9.0±0.5	3.2±0.5	26±2.0	0.60	
1W	500V	1000V	11.0±1.0	3.7±0.5	35±2.0	0.70	
1W	500V	1000V	11.0±1.0	4.2±0.5	25±2.0	0.70	
2WS	500V	1000V	11.0±1.0	4.2±0.5	35±3.0	0.70	
2W	500V	1000V	15.0±1.0	5.0±0.5	33±3.0	0.75	
3W	500V	1000V	17.0±1.0	6.0±0.5	38±3.0	0.75	

Electrical Specifications

Test Items		Condition			Spec
Short Time Overload		2.5 times of RCWV for 5 secs.			±(2%+0.05 Ω)
Load life		70℃ at rated power 1.5hrs on;0.5 hr off for 1000hrs			±(5%+0.05 Ω)
Dielectric Withstanding Voltage		Max Overload Voltage 1 Minute			±(0.5%+0.05 Ω)
Temp. Cycling		-30℃ / +85℃ for 5 cycles			±(1%+0.05 Ω)
Insulation Resistance		D.C. 500V			1000MΩ
Moisture-proof Load Life		40℃ 95% RH 1.5hrs on / 0.5hr off cycle for 1000 hrs.			±(5%+0.05 Ω)
Soldering Heat Resistance		350℃ for 3.5 secs.			±(2%+0.05 Ω)
ppm / ℃ Temp. Coeff.	T.C.	±450	-150~-700	-150~-1000	-150~-1300
	TYPE				
	1/6W ~ 1/8W	<47K Ω	51KΩ~100KΩ	110KΩ~330KΩ	Over 360kΩ
	1/4W & OVER	<100KΩ	110KΩ~1MΩ	1.1MΩ~2.2MΩ	Over 2.4MΩ

*RCWV" Rated Continuous Working Voltage

