EN: This Datasheet/Document is presented by the manufacturer.

Please visit our website for pricing and availability at www.hestore.hu.



Features

- Virtually infinite electrical circuit isolation
- Sealed for board wash
- Metal or plastic shaft options
- RoHS compliant*

Model 96 – 5/8 ˝ Square Sealed Single-Turn Panel Control

Initial Electrical Characteristics[1]	Conductive Plastic Element	Cermet Element
Standard Resistance Range		
Linear Tapers (A, B, E, & H)	(B & E) 1 K ohms to 1 megohm	(A & H) 100 ohms to 1 megohm
Audio Tapers (C, D, F, G, S, & T)	(D,G,S, & T) 1 K ohms to 1 megohm	(C & F) 1 K ohms to 1 megohm
Total Resistance Tolerance	10 % or 20 %	5% or 10%
Independent Linearity	±5 %	±5 %
Absolute Minimum Resistance	2 ohms maximum	2 ohms maximum
Effective Electrical Angle	(Linear tapers) 240 ° ± 5 °	(Linear tapers) 240 ° ± 6 °
	(Audio tapers) 225 ° ± 5 °	(Audio tapers) 225 ° ± 6 °
Contact Resistance Variation	±1 %	±1 % or 3 ohms (whichever is greater)
Dielectric Withstanding Voltage (MIL-STD-202, Method 301)		
Sea Level	1,500 VAC minimum	1,500 VAC minimum
70,000 Feet	500 VAC minimum	500 VAC minimum
Insulation Resistance (500 VDC)	1,000 megohms minimum	1,000 megohms minimum
Power Rating (Voltage Limited By Power Dissipation or 350 VAC, Whichever Is Less)		
+70 °C Single Section Assembly	(Linear tapers) 1 watt	(Linear tapers) 2 watts
	(Audio tapers) 0.5 watt	(Audio tapers) 1 watt
+125 °C	0 watt	0 watt
Theoretical Resolution	Essentially infinite	Essentially infinite

Environmental Characteristics[1]		
Operating Temperature Range	-40 °C to +125 °C	-40 °C to +125 °C
Storage Temperature Range	-55 °C to +125 °C	-55 °C to +125 °C
Temperature Coefficient Over Storage Temperature Range	±1,000 ppm/°C	±150 ppm/°C
Vibration (Single Section)	15 G	15 G
Total Resistance Shift	±2 % maximum	±2 % maximum
Voltage Ratio Shift	±5 % maximum	±5 % maximum
Shock (Single Section)	30 G	30 G
Total Resistance Shift	±2 % maximum	±2 % maximum
Voltage Ratio Shift	±5 % maximum	±5 % maximum
Load Life	1,000 hours	1,000 hours
Total Resistance Shift	±10 % maximum	±5 % maximum
Rotational Life (No Load)	100,000 cycles	100,000 cycles
Total Resistance Shift	(Linear tapers) 10 ohms or ±15 % TRS max. (whichever is greater)	(All tapers) ±5 % TRS max.
	(Audio tapers) ±20 % maximum	
Contact Resistance Variation @ 50,000 cycles	(Linear tapers) ±2 %	±2 %
	(Audio tapers) ±3 %	±3 %
Moisture Resistance (MIL-STD-202, Method 103, Condition B)		
Total Resistance Shift	(Linear tapers) ±10 % TRS maximum	(All tapers) ±5 % TRS maximum
	(Audio tapers) ±20 % TRS maximum	
Insulation Resistance (500 VDC)	100 megohms minimum	100 megohms minimum
IP Rating	IP 65	IP 65

WARNING
Cancer and Reproductive Harm
www.P65Warnings.ca.gov

*RoHS Directive 2015/863, Mar 31, 2015 and Annex.
Specifications are subject to change without notice. Users should verify actual device performance in their specific applications. The products described herein and this document are subject to specific legal disclaimers as set forth on the last page of this document, and at www.bourns.com/docs/legal/disclaimer.pdf.

Model 96 – 5/8 ″ Square Sealed Single-Turn Panel Control

BOURNS®

Mechanical Characteristics[1]

Stop Strength (1/4 ″ D shaft) ..... 45.19 N-cm (4 lb.-in.)
(1/8 ″ D shaft) ..... 33.89 N-cm (3 lb.-in.)
Mechanical Angle ..... 300 ° ±5 °
Torque
Starting ..... 0.3 max. above average running torque
Running Torque
Single or Dual Section (A & R Bushings) ..... 0.21 to 1.06 N-cm (0.3 to 1.5 oz.-in.)
Single or Dual Section (C & U Bushings) ..... 0.14 to 1.06 N-cm (0.2 to 1.5 oz.-in.)
Mounting ..... 1.7-2.0 N-m (15-18 lb.-in.) maximum
Variation ..... 0.35 N-cm (0.5 oz.-in.) maximum in 45 ° shaft travel
Weight (Single Section, Metal Bushing) ..... 12.7 grams nominal
Terminals ..... Printed circuit terminals, J-Hooks or solder lugs
Soldering Condition ..... Recommended hand soldering using Sn95/Ag5 no clean solder, 0.025 ″ wire diameter. Maximum temperature 399 °C (750 °F) for 3 seconds. Immersion wash is not recommended.
Marking ..... Manufacturer's trademark, date code, resistance, manufacturer's part number
Hardware ..... One lockwasher and one mounting nut is shipped with each potentiometer (Bushing A: H-37-2 & H-38-2; Bushing C: H-37-1 & H-38-1; Bushing R: H-37-4 & H-38-9; Bushing U: H-37-3 & H-38-8)

NOTE: Performance specifications do not apply to units subjected to printed circuit board immersion cleaning processes.

[1] Electrical specifications tested at 200 RPM, at room ambient: +25 °C nominal.

Product Dimensions

Model 96 PC Pin Terminals, In-Line



Shaft Flat Orientation



Specifications are subject to change without notice.
Users should verify actual device performance in their specific applications.
The products described herein and this document are subject to specific legal disclaimers as set forth on the last page of this document, and at www.bourns.com/docs/legal/disclaimer.pdf.

Product Dimensions

Plastic Shaft Styles

SHAFT TYPE "B" (USES BUSHING A)



STD. LENGTHS:			
12.70 (.500)	15.88 (.625)	19.05 (.750)	22.23 (.875)

SHAFT TYPE "C" (USES BUSHING A)



STD. LENGTHS:	
19.05 (.750)	22.23 (.875)

SHAFT TYPE "D" (USES BUSHING C)



STD. LENGTHS:		
12.70 (.500)	15.88 (.625)	19.05 (.750)

SHAFT TYPE "R" (USES BUSHING R)



STD. LENGTHS:	
16.0 (.630)	22.0 (.866)

SHAFT TYPE "T" (USES BUSHING U)



STD. LENGTHS:	
16.0 (.630)	22.0 (.866)

SHAFT TYPE "W" (USES BUSHING A)



STD. LENGTHS:
25.40 (1.00)

Metal Shaft Styles

SHAFT TYPE "A" (USES BUSHING A)



STD. LENGTHS:				
12.70 (.500)	15.88 (.625)	19.05 (.750)	22.23 (.875)	25.4 (1.000)

SHAFT TYPE "E" (USES BUSHING C)



STD. LENGTHS:		
12.0 (.500)	16.0 (.625)	19.0 (.750)

SHAFT TYPE "G" (USES BUSHING A)



STD. LENGTHS:			
12.70 (.500)	15.88 (.625)	19.05 (.750)	22.23 (.875)

SHAFT TYPE "H" (USES BUSHING A)



STD. LENGTHS:	
19.05 (.750)	22.23 (.875)

FLAT LENGTH "F":	
7.95 (.313)	11.13 (.438)

SHAFT TYPE "J" (USES BUSHING R)



STD. LENGTHS:	
16.0 (.630)	22.0 (.866)

SHAFT TYPE "S" (USES BUSHING R)



STD. LENGTHS:	
16.0 (.630)	22.0 (.866)

FLAT LENGTH "F":	
6.99 (.275)	12.98 (.511)

SHAFT TYPE "V" (USES BUSHING U)



STD. LENGTHS:	
16.0 (.630)	22.0 (.866)

TOLERANCES EXCEPT AS SHOWN: .XX = ± .02 (.050)
.XXX = ± .005 (.127)
.XXXX = ± .0005 (.0127)

DIMENSIONS: MM / (INCHES)

Specifications are subject to change without notice.
Users should verify actual device performance in their specific applications.
The products described herein and this document are subject to specific legal disclaimers as set forth on the last page of this document, and at www.bourns.com/docs/legal/disclaimer.pdf.

Model 96 – 5/8 ″ Square Sealed Single-Turn Panel Control

BOURNS®

Suggested Panel Layout



BUSHING	DIM A
A	9.91 (.39)
C	6.73 (.265)
R	10.5 (.413)
U	7.5 (.295)

DIMENSIONS: MM (INCHES)

Date Code Description



Hardware

LOCKWASHER H-37-1



LOCKWASHER H-37-2



LOCKWASHER H-37-3



LOCKWASHER H-37-4



NUT H-38-1



NUT H-38-2



NUT H-38-8



NUT H-38-9



DIMENSIONS: MM (INCHES)

Specifications are subject to change without notice.
Users should verify actual device performance in their specific applications.
The products described herein and this document are subject to specific legal disclaimers as set forth on the last page of this document, and at www.bourns.com/docs/legal/disclaimer.pdf.

How to Order Model 96 Panel Controls

BOURNS®

96	A	1	A	-	A	28	-	A	15	L

MODEL	
96	**Single-Turn, In-Line PC Pins, Sealed**

BUSHING	
A	**Metal Plain 3/8 ” (9.53 mm) D x 3/8 ” (9.53 mm) L**
C	Metal Plain 1/4 ” (6.35 mm) D x 1/4 ” (6.35 mm) L
R	**Metal Plain 10 mm D x 9 mm L**
U	Metal Plain 7 mm D x 9 mm L

# SECTIONS	
1	**Single**

ANTI-ROTATION LUG	
A	**Single .305 ” (7.8 mm) R, 90 °CW**
D	**No Lug**

SHAFT TYPE		AVAILABLE ONLY IN LENGTHS (CODE)	AVAILABLE ONLY IN BUSHINGS (CODE)
B	**Plastic Single Slotted 1/4 " (6.35 mm) D**	16, 20, 24, 28	**A**
C	**Plastic Single Flatted 1/4" (6.35 mm) D**	24, 28	**A**
D	Plastic Single Plain 1/8" (3.18 mm) D	16, 20, 24	C
R	**Plastic Single Slotted 6 mm D**	Metric 16,22	R
T	**Plastic Single Slotted 4 mm D**	Metric 16, 22	U
W	Plastic Single Knurled 1/4" (6.35 mm) D	32	**A**
A	**Metal Single Plain 1/4" (6.35 mm) D**	16, 20, 24	**A**
E	**Metal Single Slotted 1/8" (3.18 mm) D**	16, 20, 24	**C**
G	**Metal Single Slotted 1/4" (6.35 mm) D**	16, 20, 24, 28	**A**
H	**Metal Single Flatted 1/4" (6.35 mm) D**	24, 28	**A**
J	**Metal Single Slotted 6 mm D**	Metric16, 22	R
S	**Metal Single Flatted 6 mm D**	Metric 16, 22	R
V	**Metal Single Slotted 4 mm D**	Metric 16, 22	U

SHAFT LENGTH (FMS) Code	Description	AVAILABLE ONLY IN BUSHING Code
16	1/2 ”L	A, C
20	5/8 ”L	A, C
24	**3/4 ”L**	A, C
28	**7/8 ”L**	**A**
32	1 ”L	A
METRIC		
16	16 mmL	R, U
22	**22 mmL**	R, U

RoHS IDENTIFIER	
L	**Compliant**

ELEMENT TAPER TYPE/TOLERANCE		RESISTANCE CODE VALUE IN OHMS	
(A)	**Linear Cermet ±10 %**	(05) - 100	(30) - 15 K
(H)	Linear Cermet ±5 %	(28) - 150	(16) - 20 K
		(06) - 200	(17) - 25 K
		(07) - 250	**(18) - 50 K**
		(08) - 500	**(20) - 100 K**
		(10) - 1 K	(21) - 200 K
		(11) - 2 K	(22) - 250 K
		(12) - 2.5 K	(23) - 500 K
		(13) - 5 K	(25) - 1 M
		(15) - 10 K	
(B)	**Linear C-P ±20 %**	**(10) - 1 K**	**(18) - 50 K**
(E)	Linear C-P ±10 %	(12) - 2.5 K	**(20) - 100 K**
		(13) - 5 K	(22) - 250 K
		(15) - 10 K	(23) - 500 K
		(16) - 20 K	(25) - 1 M
		(17) - 25 K	
(C)	CW Audio Cermet ±10 %	(10) - 1 K	(18) - 50 K
(D)	CW Audio C-P ±20 %	(12) - 2.5 K	(20) - 100 K
(F)	CCW Audio Cermet ±10 %	(13) - 5 K	(22) - 250 K
(G)	CCW Audio C-P ±20 %	(15) - 10 K	(23) - 500 K
(S)	CW Audio C-P ±10 %	(17) - 25 K	(25) - 1 M
(T)	CCW Audio C-P ± 10 %		

Boldface features are Bourns standard options. All others are available with higher minimum order quantities.

BOURNS®

Asia-Pacific: Tel: +886-2 2562-4117 • Email: asiacus@bourns.com
EMEA: Tel: +36 88 885 877 • Email: eurocus@bourns.com
The Americas: Tel: +1-951 781-5500 • Email: americus@bourns.com
www.bourns.com

REV. 10/20

Specifications are subject to change without notice.
Users should verify actual device performance in their specific applications.
The products described herein and this document are subject to specific legal disclaimers as set forth on the last page of this document, and at www.bourns.com/docs/legal/disclaimer.pdf.

Legal Disclaimer Notice

BOURNS®

This legal disclaimer applies to purchasers and users of Bourns® products manufactured by or on behalf of Bourns, Inc. and its affiliates (collectively, "Bourns").

Unless otherwise expressly indicated in writing, Bourns® products and data sheets relating thereto are subject to change without notice. Users should check for and obtain the latest relevant information and verify that such information is current and complete before placing orders for Bourns® products.

The characteristics and parameters of a Bourns® product set forth in its data sheet are based on laboratory conditions, and statements regarding the suitability of products for certain types of applications are based on Bourns' knowledge of typical requirements in generic applications. The characteristics and parameters of a Bourns® product in a user application may vary from the data sheet characteristics and parameters due to (i) the combination of the Bourns® product with other components in the user's application, or (ii) the environment of the user application itself. The characteristics and parameters of a Bourns® product also can and do vary in different applications and actual performance may vary over time. Users should always verify the actual performance of the Bourns® product in their specific devices and applications, and make their own independent judgments regarding the amount of additional test margin to design into their device or application to compensate for differences between laboratory and real world conditions.

Unless Bourns has explicitly designated an individual Bourns® product as meeting the requirements of a particular industry standard (e.g., ISO/TS 16949) or a particular qualification (e.g., UL listed or recognized), Bourns is not responsible for any failure of an individual Bourns® product to meet the requirements of such industry standard or particular qualification. Users of Bourns® products are responsible for ensuring compliance with safety-related requirements and standards applicable to their devices or applications.

Bourns® products are not recommended, authorized or intended for use in nuclear, lifesaving, life-critical or life-sustaining applications, nor in any other applications where failure or malfunction may result in personal injury, death, or severe property or environmental damage. Unless expressly and specifically approved in writing by two authorized Bourns representatives on a case-by-case basis, use of any Bourns® products in such unauthorized applications might not be safe and thus is at the user's sole risk. Life-critical applications include devices identified by the U.S. Food and Drug Administration as Class III devices and generally equivalent classifications outside of the United States.

Bourns expressly identifies those Bourns® standard products that are suitable for use in automotive applications on such products' data sheets in the section entitled "Applications." Unless expressly and specifically approved in writing by two authorized Bourns representatives on a case-by-case basis, use of any other Bourns® standard products in an automotive application might not be safe and thus is not recommended, authorized or intended and is at the user's sole risk. If Bourns expressly identifies a sub-category of automotive application in the data sheet for its standard products (such as infotainment or lighting), such identification means that Bourns has reviewed its standard product and has determined that if such Bourns® standard product is considered for potential use in automotive applications, it should only be used in such sub-category of automotive applications. Any reference to Bourns® standard product in the data sheet as compliant with the AEC-Q standard or "automotive grade" does not by itself mean that Bourns has approved such product for use in an automotive application.

Bourns® standard products are not tested to comply with United States Federal Aviation Administration standards generally or any other generally equivalent governmental organization standard applicable to products designed or manufactured for use in aircraft or space applications. Bourns expressly identifies Bourns® standard products that are suitable for use in aircraft or space applications on such products' data sheets in the section entitled "Applications." Unless expressly and specifically approved in writing by two authorized Bourns representatives on a case-by-case basis, use of any other Bourns® standard product in an aircraft or space application might not be safe and thus is not recommended, authorized or intended and is at the user's sole risk.

The use and level of testing applicable to Bourns® custom products shall be negotiated on a case-by-case basis by Bourns and the user for which such Bourns® custom products are specially designed. Absent a written agreement between Bourns and the user regarding the use and level of such testing, the above provisions applicable to Bourns® standard products shall also apply to such Bourns® custom products.

Users shall not sell, transfer, export or re-export any Bourns® products or technology for use in activities which involve the design, development, production, use or stockpiling of nuclear, chemical or biological weapons or missiles, nor shall they use Bourns® products or technology in any facility which engages in activities relating to such devices. The foregoing restrictions apply to all uses and applications that violate national or international prohibitions, including embargos or international regulations. Further, Bourns® products and Bourns technology and technical data may not under any circumstance be exported or re-exported to countries subject to international sanctions or embargoes. Bourns® products may not, without prior authorization from Bourns and/or the U.S. Government, be resold, transferred, or re-exported to any party not eligible to receive U.S. commodities, software, and technical data.

To the maximum extent permitted by applicable law, Bourns disclaims (i) any and all liability for special, punitive, consequential, incidental or indirect damages or lost revenues or lost profits, and (ii) any and all implied warranties, including implied warranties of fitness for particular purpose, non-infringement and merchantability.

For your convenience, copies of this Legal Disclaimer Notice with German, Spanish, Japanese, Traditional Chinese and Simplified Chinese bilingual versions are available at:

Web Page: http://www.bourns.com/legal/disclaimers-terms-and-policies

PDF: http://www.bourns.com/docs/Legal/disclaimer.pdf

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Bourns:

96A1A-B16-A10 96A1D-C28-E12 96A1A-B28-A15 96A1A-C28-A15 96A1A-C28-A13 96A1A-B28-A13 96A1A-B28-A20 96R1A-R16-B15 96U1D-T12-B15 96R1A-R22-A13 96R1A-R22-A12 96R1A-R22-A17 96R1A-R22-A10 96D1D-C28-H15 96R1A-R19-A13 96R1A-R19-A15 96A1D-C28-H10 96A1D-B24-A22 96R1A-R16-A15 96A1D-B20-E25 96A1A-C28-H10 96A1A-B24-A15 96A1A-C24-A15 96A1A-B24-A13 96A1A-B24-E10 96A1A-B24-B15 96A1A-B24-B15L 96A1D-C28-H10L 96A1A-B28-A13L 96A1A-B28-A15L 96A1A-B28-B18L 96R1A-R16-A15L 96R1A-R16-B15L 96R1A-R22-A10L 96R1A-R22-A13L 96R1A-R22-B15L 96R1D-R22-B15L 96A1D-B24-C15 96R1A-R22-B15 96R1A-R22-B12 96D1D-B16-H15 96A1A-C24-H25 96A1A-C24-H11 96A1A-B24-H10 96U1D-T12-A18 96C1D-D16-B15 96A1D-C28-A20 96A1D-C24-D15 96A1A-B24-D13 96R1A-R16-H15 96A1A-B24-D20 96A1A-B24-D10 96R1A-R22-A22 96R1A-R22-A20 96A1A-C24-C25 96R1D-R22-B15 96C1C-D16-E16 96C1C-D16-E18 96A1A-B20-B15 96A1A-B28-B20 96A1A-B28-B22 96A1A-B28-B12 96A1A-B28-B15 96A1A-B28-B13 96D1A-W32-D15 96A1A-B28-B16 96A1A-B28-B18 96A1D-G28-E13L 96A1D-G28-E17L 96A1D-G28-E22L 96A1D-G28-S15L 96A1D-G28-S23L 96A1D-G28-S25L 96A1D-A24-D13L 96A1A-B28-B20L 96A1A-B28-B22L 96A1A-B28-A10L 96A1D-G28-A15L 96A1D-G24-B20L 96A1A-C24-EAO/253L 96A1A-B28-A20L 96A1A-H24-B15L 96C1D-E24-B15L