



HESTORE.HU

elektronikai alkatrész áruház

EN: This Datasheet is presented by the manufacturer.

Please visit our website for pricing and availability at www.hestore.hu.

MAXIMUM RATINGS

(Ta=25°C)

Item	Symbol	Rating	Unit
Supply voltage	V _{cc}	17	V
Low level output current	I _{OL}	30	mA
Output transistor power dissipation	P _o	200	mW
Operating temp.	T _{opr.}	-25 ~ +85	°C
Storage temp.	T _{stg.}	-40 ~ +100	°C
Soldering temp.*1	T _{sol.}	260	°C

*1. For MAX. 5 seconds at the position of 2 mm from the resin edge.

ELECTRO-OPTICAL CHARACTERISTICS

 (V_{cc}=5V, Ta=25°C)

Item	Symbol	Conditions	Min.	Typ.	Max.	Unit.	
Supply voltage	V _{cc}		4.5		17	V	
High level supply current	I _{ccH}	E _v =0lx		3	6	mA	
Low level supply current	I _{ccL}	E _v =100lx		3	6	mA	
High level output voltage	V _{OH}	E _v =100lx, E _s =10KΩ, V _{OH} =5V	4.5			V	
Low level output voltage	V _{OL}	E _v =100lx, I _s =16mA			0.4	V	
L→H Threshold illuminance	E _{vHL}		10	25		lx	
H→L Threshold illuminance	E _{vHL}			30	80	lx	
Hysteresis	E _{vHL} /E _{vLH}	R _s =280Ω	0.5	0.8	0.95	—	
Peak wavelength	λ _P			900		nm	
Switching speed	L→H propagation time	t _{PH}		3	9	μsec.	
	H→L propagation time	t _{PL}		2	6	μsec.	
	Rise time	t _r	E _v =100lx, R _s =280Ω		0.1	0.5	μsec.
	Fall time	t _f			0.05	0.5	μsec.

