



EN: This Datasheet/Document is presented by the manufacturer.

Please visit our website for pricing and availability at www.hestore.hu.

ULTRASONIC SENSOR

Customer	
Customer P/O	
Customer Spec. No.	
Bestar Model Name	BPU-1640IOAH12
Product No.	100902
Issue No.	BS/TEP01.201A
Issue Date	03/10/06

Approval:

- 1.Applications
- 2.Features
- 3.Technical terms
- 4.Drawing
- 5.Beam Pattern
- 6.Test Circuit
- 7.Reliability Test

Prepared	Chec.	Appr.	Revision		
			No.	Date	Contents
			0		
			1		
			2		
			3		

Reference:

超声波探头GS认证中的C12-5-2标准



BESTAR ELECTRONICS INDUSTRY CO.,LTD
 Site B,TianAn Industry,New District,ChangZhou ,P.R.China
 Tel:86-519-5103228
 Fax:86-519-5131010
 Http:www.be-star.com
 E-Mail:bestarco@pub.cz.jsinfo.net

BPU-1640IOAH12

1.Applications

Burglar alarms、 Range finders、 Automatic doors、 Remote control.

2.Features

- 2.1) Open struct and Dual use
- 2.2) Compact and light weight.
- 2.3) High sensitivity and sound pressure.
- 2.4) Less power consumption.
- 2.5) High reliability

3.Technical terms

No.	Item	Specification
1.	Construction	Open Struct
2.	Using Method	Dual Use
3.	Center Frequency	40kHz
4.	Transmitting Sound Pressure Level	min115dB (30cm/10Vrms Sine Wave)
5.	Receive Sensitive	min-74dB/V/ μ bar
6.	-6dB Directivity	50deg
7.	Sensitivity Distance	min.13m
8.	Capacitance	2000pF $\pm$ 20% at1KHz
9.	Operating Tem.Range	-30 to 85 $^{\circ}$ C
10.	Allowable Input Voltage	120 Vp-p(40KHz)
11.	Housing Material	Aluminum

DIS.

DATE

Page:1 of 5

BPU-1640IOAH12

CHEC.

DATE

3rd angle
projection

Ultrasonic Sensor

APPR.

DATE



BESTAR ELECTRONICS INDUSTRY CO.,LTD


TianAn Industry Park 4/F,Site B ChangZhou New District

E-Mail:bestarco@ pub.cz.jsinfo.net Http:www.be-star.com

DRG NO
BS/TEP01.201A

BPU-1640IOAH12

4. Drawing





This print and information therein are proprietary to Bestar Electronics Industry Co., Ltd. and shall not be used in whole or in part without its written content 100900

DIS.		DATE		Page:2 of 5	BPU-1640IOAH12
CHEC.		DATE		3rd angle projection	Ultrasonic Sensor
APPR.		DATE			
 BESTAR ELECTRONICS INDUSTRY CO.,LTD TianAn Industry Park 4/F,Site B ChangZhou New District E-Mail:bestarco@ pub.cz.jsinfo.net Http:www.be-star.com					DRG NO BS/TEP01.201A

Bestar
Acoustic

BPU-1640IOAH12


5. Beam Pattern




DIS.		DATE		Page:3 of 5	BPU-1640IOAH12
CHEC.		DATE		3rd angle projection	Ultrasonic Sensor
APPR.		DATE			DRG NO BS/TEP01.201A
BESTAR ELECTRONICS INDUSTRY CO.,LTD TianAn Industry Park 4/F,Site B ChangZhou New District E-Mail:bestarco@ pub.cz.jsinfo.net Http:www.be-star.com					



BPU-1640IOAH12



6.Test circuit



Rl: 3.9K Ω

Rc=1k Ω

T.G. :Target

F.G. :Function Generator

O.S. :Oscilloscope

DIS.		DATE		Page:4 of 5	BPU-1640IOAH12
CHEC.		DATE		3rd angle projection	Ultrasonic Sensor
APPR.		DATE			DRG NO BS/TEP01.201A
Bestar Acoustic BESTAR ELECTRONICS INDUSTRY CO.,LTD TianAn Industry Park 4/F,Site B ChangZhou New District E-Mail:bestarco@ pub.cz.jsinfo.net Http:www.be-star.com					

BPU-1640IOAH12

7. Reliability Test

7.1 High temp.life test

Temperature +85° C
Duration 200hrs

7.2 Low temp.life test

Temperature -40° C
Duration 200hrs

7.3 Heat Cycle Test

Temperature +85± 3° C 1hour
-40± 3° C 1hour
Cycles 100cycles

7.4 Humidity Test

Temperature +65° C
Relative Humidity 90~95%
Duration 200hrs

Tests above should be measured after leaving normal temperature for 24hrs.

7.5 Vibration Test

Vibration Frequency 10~200Hz
Sweep Period 15min
Acceleration 43.12m/s²
Direction 3(x.y&z)
Time 96hours/direction

*7.6 Life test in normal temperature(25° C reference)

Power supply 10V (40KHz ,square wave)
Duration 4hours

7.7 Shock test

Acceleration sine 980 m/s²
Direction 3directions
Shock time 3 time/directions

7.8 Drop test

Height 1m
(Dropped to 20mm thick hardwood board without packing.)
Times 10times

Notice:

The variation of the S.P.L at 40KHz is within 3dB compared with initial figures at 25° C after above test condition
after 7.6 test conditions, repeat test 20 times or more, the product must be have request distance response .

DIS.		DATE		Page:5 of 5	BPU-1640IOAH12
CHEC.		DATE		3rd angle projection	Ultrasonic Sensor
APPR.		DATE			DRG NO BS/TEP01.201A
 BESTAR ELECTRONICS INDUSTRY CO.,LTD TianAn Industry Park 4/F,Site B ChangZhou New District E-Mail:bestarco@ pub.cz.jsinfo.net Http:www.be-star.com					