






EN: This Datasheet/Document is presented by the manufacturer.

Please visit our website for pricing and availability at www.hestore.hu.



TOLERANCE	
XX.	± 0.5
X.	± 0.2
.XX	± 0.2

SPECIFICATIONS:

CONTACT RATING : 6 AMPS @ 120 V AC or 28 V DC.

3AMPS @250 V AC or 0.4 AMPS @ 20V AC or DC

ELECTRICAL LIFE : 30,000 make-and-break cycles at full load.

CONTACT RESISTANCE : 10 mΩ max. initial @ 2-4 V DC.

100 mA, for both silver and gold plated contacts.

INSULATION RESISTANCE : 1,000 MΩ min.

DIELECTRIC STRENGTH : 1,000 V RMS @ sea level.

OPERATING TEMPERATURE : -30 °C to 130 °C

MATERIALS:

CASE : Diallyl phthalate (DAP)(UL-94V-0).

ACTUATOR : Nylon.



BUSHING : Brass, nickel plated.

HOUSING : Stainless steel.

TERMINAL/CONTACT : Brass, with silver or gold plated.

or gold over silver

SWITCH SUPPORT : Brass, tin plated.



P.C. MOUNTING

REVISION	DESCRIPTION	REVISED BY	TOLERANCES		X	XX	ANGLE $\frac{1}{2}^\circ$		UNIT	mm	PART NAME	SL19 SPEC DRAWING	DWG NO
			DRAWN BY	Alice	DESIGNED BY	Eric	SCALE				SL19 SPEC DRAWING	WS0234A	
			CHECKED BY		APPROVED BY		DATE	2006.01.25	PART NO	SL19-123			
	2006.01.25 換新圖框, 重新出圖	吳美玉											