



HESTORE.HU

elektronikai alkatrész áruház

EN: This Datasheet is presented by the manufacturer.

Please visit our website for pricing and availability at www.hestore.hu.

3DP-PLA-01-MTBK

Filament, matte PLA, black, 1.75 mm, 1 kg

VERSATILE & EASY TO USE

- PLA (polylactide) is a biodegradable thermoplastic polyester, which is easy to print for variety 3D printers.
- It has no odor, a lower melting point and good flowability, no need to post-treatment
- The material is composed of PLA and ester
- Matte surface



Features

- High precision roundness enables higher printing quality
- No bubbles, vivid colors
- Can be applied to a variety of 3D printers

Packaging

Q'ty in crtn, pcs	8
Crtn volume, CUM	0.033
Crtn weight, kgs	10.94
Individual package size LxWxH:	208x208x63 mm
Carton size LxWxH:	310x450x235 mm
Country of origin	CN
Barcode	8716309127165
Customs code	3916909000

Specifications

Material: PLA, 1.75 mm diameter
Weight: 1 kg/spool (2.2 lbs)
Length: approx. 340 m
Density at 21.5 °C: 1.21 g/cm³
Melt Flow Index at 10min, 2.16kg: 6...8
Melt Point: 190 220 °C
Heat-Deflection-Temperature at 0.455 MPa: 50 °C
Yield Strength at 5mm/min: > 30 MPa
Impact Strength: 5 KJ/m²
Tensile Strength: 20 %
Diameter: 1.75 ± 0.05 mm

System requirements

A 3D printer with 1.75 mm extruder of temperature around 200 °, suitable for PLA filament

Certificates

