

HESTORE.HU
elektronikai alkatrész áruház

EN: This Datasheet is presented by the manufacturer.

Please visit our website for pricing and availability at www.hestore.hu.


Material
Insulator: LCP+30% G.F., UL 94V-0 Rated Color : Black Contact: Phosphor Bronze , JIS C5191R-H , 0.25t
Plating
Contact Area: Gold plating over 1.2μm(50u")Nickel underplating. See Note Soldering Zone: 3.08μm(120u") min. Sn/Pb, 90/10, or 100%TIN over 1.2μm(50u") min. Ni underplate overall.
NOTES: This soldering pad is optional and shall be grounding. Inspection Dimension: ■ Critical





CARD DETECTION	
WITHOUT CARD	CARD INSERTED
①—④ ③ GND	①—④ ③ GND

WRITE PROTECT SWITCH	
WRITE PROTECTION LOCK	WRITE PROTECTION UNLOCK
②—④ ③ GND	②—④ ③ GND



RECOMMENDED P.C.B. LAYOUT

UNLESS OTHERWISE SPECIFIED TOLERANCE	
ANG.	±5'
0.	±
.0	±0.25
.00	±0.20

ATTEND TECHNOLOGY INC.
www.attend.com.tw

SCALE: AS SHOWED	UNIT: mm	DRAWN NAME: SD Socket	
DRAWN willis	2006/11/28	Push-Push Type,W/Card Lock Function	
CHECKED	/ /		
APPROVED	/ /	PRODUCT NO. 104G-TAA0-R	
SIZE A4	REV.	FILE NAME: 104G-TAA0-R	

REV.	DESCRIPTION	DATE