
EN: This Datasheet/Document is presented by the manufacturer.

Please visit our website for pricing and availability at www.hestore.hu.

RXEF Series
Radial Leaded



Description

Littelfuse PolySwitch radial-leaded devices represent the most comprehensive and complete set of PPTC products available in the industry today. RXEF series offers low hold currents (down to 50mA) and high voltage rating
(up to 72V).

Features & Benefits

- Resettable and single-use overcurrent devices
- Wide range of form factor and termination methods
- Devices compatible with high-volume electronics assembly
- RoHS compliant, Lead-Free and Halogen-Free
- UL Recognized to UL 1434
- CSA Approved to CSA TIL No. CA-3A
- TUV Approved to EN 60730-1
- CQC Approved to GB 8898, GB/T 7153, GB 14536.1

Applications

- Satellite video receivers
- Industrial controls
- Transformers
- Computer motherboards
- Modems
- USB hubs, ports and peripherals
- IEEE 1394 ports
- CD-ROMs
- Game machines
- Battery packs
- Phones
- Fax machines
- Analog and digital line cards
- Printers

Additional Information

Resources | Accessories | Samples

Agency Approvals

Agency	Agency File/Certificate Number
	E74889
	78165
	16001159722
	72161785

Electrical Characteristics

Part Number	Ordering Part Number	I_H	I_T	V_{MAX}		I_{MAX}		$P_{D\ Typ}$	Max Time-to-trip		R_{MIN}	R_{MAX}	R_{1MAX}	Lead Size (mm^2/AWG)
		(A)	(A)	(V_{DC})	($V_{AC\ RMS}$)	(DC_{ADC})	(AC_{ARMS})	(W)	(A)	(s)	(Ω)	(Ω)	(Ω)	
RXEF – 60V														
RXEF005	RF2577-000	0.05	0.10	60	–	40	–	0.22	0.25	5.0	7.3	11.10	20.00	0.128/26
RXEF010	RF2579-000	0.10	0.20	60	–	40	–	0.38	0.50	4.0	2.5	4.50	7.50	0.205/24
RXEF017	RF2563-000	0.17	0.34	60	–	40	–	0.48	0.85	3.0	3.3	5.21	8.00	0.205/24

Notes:

I_H : Hold current: maximum current device will pass without interruption in 20°C still air.

I_T : Trip current: minimum current that will switch the device from low resistance to high resistance in 20°C still air.

V_{MAX} : Maximum continuous voltage device can withstand without damage at rated current.

I_{MAX} : Maximum fault current device can withstand without damage at rated voltage.

P_D : Power dissipated from device when in the tripped state in 20°C still air.

R_{MIN} : Minimum resistance of device as supplied at 20°C unless otherwise specified.

R_{MAX} : Maximum resistance of device as supplied at 20°C unless otherwise specified.

R_{1MAX}: Maximum resistance of device when measured one hour post reflow (surface-mount device) or one hour post trip (radial-leaded device) at 20°C unless otherwise specified.

* Electrical characteristics determined at 25°C.

© 2022 Littelfuse, Inc.
Specifications are subject to change without notice.
Revised: GD. 09/21/22

RXEF Series
Radial Leaded

Electrical Characteristics (Cont'd)

Part Number	Ordering Part Number	I_H	I_T	V_{MAX}		I_{MAX}		$P_{D\ Typ}$	Max Time-to-trip		R_{MIN}	R_{MAX}	R_{1MAX}	Lead Size (mm^2/AWG)
		(A)	(A)	(V_{DC})	($V_{AC\ RMS}$)	(DC_{ADC})	(AC_{ARMS})	(W)	(A)	(s)	(Ω)	(Ω)	(Ω)	
RXEF – 72V														
RXEF020	RF2564-000	0.20	0.40	72	72	40	40	0.41	1.00	2.2	1.83	2.75	4.40	0.205/24
RXEF025	RF2628-000	0.25	0.50	72	72	40	40	0.45	1.25	2.5	1.25	1.95	3.00	0.205/24
RXEF030	RF2565-000	0.30	0.60	72	72	40	40	0.49	1.50	3.0	0.88	1.33	2.10	0.205/24
RXEF040	RF2566-000	0.40	0.80	72	72	40	40	0.56	2.00	3.8	0.55	0.86	1.29	0.205/24
RXEF050	RF2567-000	0.50	1.00	72	72	40	40	0.77	2.50	4.0	0.50	0.77	1.17	0.205/24
RXEF065	RF2568-000	0.65	1.30	72	72	40	40	0.88	3.25	5.3	0.31	0.48	0.72	0.205/24
RXEF075	RF2569-000	0.75	1.50	72	72	40	40	0.92	3.75	6.3	0.25	0.40	0.60	0.205/24
RXEF090	RF2571-000	0.90	1.80	72	72	40	40	0.99	4.50	7.2	0.20	0.31	0.47	0.205/24
RXEF110	RF2623-000	1.10	2.20	72	72	40	40	1.50	5.50	8.2	0.15	0.25	0.38	0.520/20
RXEF135	RF2640-000	1.35	2.70	72	72	40	40	1.70	6.75	9.6	0.12	0.19	0.30	0.520/20
RXEF160	RF2637-000	1.60	3.20	72	72	40	40	1.90	8.00	11.4	0.09	0.14	0.22	0.520/20
RXEF185	RF2635-000	1.85	3.70	72	72	40	40	2.10	9.25	12.6	0.08	0.12	0.19	0.520/20
RXEF250	RF2649-000	2.50	5.00	72	72	40	40	2.50	12.50	15.6	0.05	0.08	0.13	0.520/20
RXEF300	RF2650-000	3.00	6.00	72	72	40	40	2.80	15.00	19.8	0.04	0.06	0.10	0.520/20
RXEF375	RF2647-000	3.75	7.50	72	72	40	40	3.20	18.75	24.0	0.03	0.05	0.08	0.520/20

Notes:

I_H : Hold current: maximum current device will pass without interruption in 20°C still air.

I_T : Trip current: minimum current that will switch the device from low resistance to high resistance in 20°C still air.

V_{MAX} : Maximum continuous voltage device can withstand without damage at rated current.

I_{MAX} : Maximum fault current device can withstand without damage at rated voltage.

P_D : Power dissipated from device when in the tripped state in 20°C still air.

R_{MIN} : Minimum resistance of device as supplied at 20°C unless otherwise specified.

R_{MAX} : Maximum resistance of device as supplied at 20°C unless otherwise specified.


R_{1MAX}: Maximum resistance of device when measured one hour post reflow (surface-mount device) or one hour post trip (radial-leaded device) at 20°C unless otherwise specified.

* Electrical characteristics determined at 25°C.

Typical Time-to-Trip Curves at 20°C

RXEF

A	=	RXEF005	J	=	RXEF075
B	=	RXEF010	K	=	RXEF090
C	=	RXEF017	L	=	RXEF110
D	=	RXEF020	M	=	RXEF135
E	=	RXEF025	N	=	RXEF160
F	=	RXEF030	O	=	RXEF185
G	=	RXEF040	P	=	RXEF250
H	=	RXEF050	Q	=	RXEF300
I	=	RXEF065	R	=	RXEF375




© 2022 Littelfuse, Inc.
Specifications are subject to change without notice.
Revised: GD. 09/21/22

RXEF Series
Radial Leaded

Temperature Rerating

Maximum Ambient Temperature										
	-40°C	-20°C	0°C	20°C	25°C	40°C	50°C	60°C	70°C	85°C
Hold Current (A)										
RXEF – 60V										
RXEF005	0.078	0.068	0.06	0.05	0.048	0.04	0.035	0.032	0.027	0.02
RXEF010	0.160	0.140	0.11	0.10	0.096	0.08	0.072	0.067	0.050	0.04
RXEF017	0.260	0.230	0.21	0.17	0.160	0.14	0.120	0.110	0.090	0.07
RXEF – 72V										
RXEF020	0.31	0.27	0.24	0.20	0.19	0.16	0.14	0.13	0.11	0.08
RXEF025	0.39	0.34	0.30	0.25	0.24	0.20	0.18	0.16	0.14	0.10
RXEF030	0.47	0.41	0.36	0.30	0.29	0.24	0.22	0.20	0.16	0.12
RXEF040	0.62	0.54	0.48	0.40	0.38	0.32	0.29	0.25	0.22	0.16
RXEF050	0.78	0.68	0.60	0.50	0.48	0.41	0.36	0.32	0.27	0.20
RXEF065	1.01	0.88	0.77	0.65	0.62	0.53	0.47	0.41	0.35	0.26
RXEF075	1.16	1.02	0.89	0.75	0.72	0.61	0.54	0.47	0.41	0.30
RXEF090	1.40	1.22	1.07	0.90	0.86	0.73	0.65	0.57	0.49	0.36
RXEF110	1.71	1.50	1.31	1.10	1.06	0.89	0.79	0.69	0.59	0.44
RXEF135	2.09	1.84	1.61	1.35	1.30	1.09	0.97	0.85	0.73	0.54
RXEF160	2.48	2.18	1.90	1.60	1.54	1.30	1.15	1.01	0.86	0.64
RXEF185	2.87	2.52	2.20	1.85	1.78	1.50	1.33	1.17	1.00	0.74
RXEF250	3.88	3.40	2.98	2.50	2.40	2.03	1.80	1.58	1.35	1.00
RXEF300	4.65	4.08	3.57	3.00	2.88	2.43	2.16	1.89	1.62	1.20
RXEF375	5.81	5.10	4.46	3.75	3.60	3.04	2.70	2.36	2.03	1.50

Temperature Rerating Curve



© 2022 Littelfuse, Inc.
Specifications are subject to change without notice.
Revised: GD. 09/21/22

RXEF Series
Radial Leaded

Physical Specifications

Lead Material	RXEF005: Tin-plated Nickel-copper Alloy, 0.128mm^2 (26AWG), ø0.40mm (0.016in) RXEF010: Tin-plated Nickel-copper Alloy, 0.205mm^2 (24AWG), ø0.51mm (0.020in) RXEF017 to 040: Tin-plated Copper-clad Steel, 0.205mm^2 (24AWG), ø0.51mm (0.020in) RXEF050 to 090 : Tin-plated Copper, 0.205mm^2 (24AWG), ø0.51mm (0.020in) RXEF110 to 375: Tin-plated Copper, 0.52mm^2 (20AWG), ø0.81mm (0.032in)
Soldering Characteristics	Solderability per ANSI/J-STD-002 Category 3 RXEF005, RXEF010 Meet ANSI/J-STD-002 Category 1
Solder Heat Withstand	RXEF005- RXEF025: per IEC-STD 68-2-20, Test Tb, Method 1a, Condition a; Can Withstand 5s at 260°C ±5°C All Other Sizes: per IEC-STD 68-2-20, Test Tb, Method 1a, Condition b; Can Withstand 10s at 260°C ±5°C
Insulating Material	Cured, Flame-retardant Epoxy Polymer; Meets UL 94V-0
Operation Temperature	-40°C~85°C

Note: Devices are not designed to be placed through a reflow process.

Environmental Specifications

Test	Conditions	Resistance Change
Passive Aging	-40°C, 1000 hrs 85°C, 1000 hrs	±5% ±5%
Humidity Aging	85°C, 85% R.H., 1000 hrs	±10%
Thermal Shock	85°C to -40°C 10 times	±10%
Solvent Resistance	MIL-STD-202, Method 215F	No change

Moisture Resistance Level	Level 1, J-STD-020
Storage Conditions	40°C max, 70% RH max; devices should remain in original sealed bags prior to use. Devices may not meet specified values if these storage conditions are exceeded.

© 2022 Littelfuse, Inc.
Specifications are subject to change without notice.
Revised: GD. 09/21/22

RXEF Series
Radial Leaded

Dimension Figures




Figure 1




Figure 2




Figure 3




Figure 4




Figure 5

Dimensions and Weights

Part Number	Dimensions in Millimeters (Inches)												Figure	Device Mass (g) (Only for Reference)
	A		B		C		D		E		H	J		
	Min	Max	Min	Max	Min	Max	Min	Max	Min	Max	Typ	Typ		
RXEF – 60V														
RXEF005	—	8.0 (0.32)	—	8.3 (0.33)	4.3 (0.17)	5.8 (0.23)	7.6 (0.30)	—	—	3.0 (0.12)	1.07 (0.042)	1.0 (0.04)	1,4,5	0.069
RXEF010	—	7.4 (0.29)	—	11.6 (0.46)	4.3 (0.17)	5.8 (0.23)	7.6 (0.30)	—	—	3.0 (0.12)	1.07 (0.042)	1.0 (0.04)	2,4,5	0.128
RXEF017	—	7.4 (0.29)	—	12.7 (0.50)	4.3 (0.17)	5.8 (0.23)	7.6 (0.30)	—	—	3.0 (0.12)	1.68 (0.066)	1.7 (0.07)	2,4,5	0.174
RXEF – 72V														
RXEF020	—	7.4 (0.29)	—	11.7 (0.46)	4.3 (0.17)	5.8 (0.23)	7.6 (0.30)	—	—	3.0 (0.12)	1.17 (0.046)	1.0 (0.04)	2,4,5	0.119
RXEF025	—	7.4 (0.29)	—	12.7 (0.50)	4.3 (0.17)	5.8 (0.23)	7.6 (0.30)	—	—	3.0 (0.12)	1.17 (0.046)	1.0 (0.04)	2,4,5	0.130
RXEF030	—	7.4 (0.29)	—	12.7 (0.50)	4.3 (0.17)	5.8 (0.23)	7.6 (0.30)	—	—	3.0 (0.12)	1.17 (0.046)	1.0 (0.04)	2,4,5	0.143
RXEF040	—	7.6 (0.30)	—	13.5 (0.53)	4.3 (0.17)	5.8 (0.23)	7.6 (0.30)	—	—	3.0 (0.12)	1.17 (0.046)	1.2 (0.05)	2,4,5	0.202
RXEF050	—	7.9 (0.31)	—	13.7 (0.54)	4.3 (0.17)	5.8 (0.23)	7.6 (0.30)	—	—	3.0 (0.12)	1.17 (0.046)	1.2 (0.05)	2,4,5	0.210
RXEF065	—	9.4 (0.37)	—	14.5 (0.57)	4.3 (0.17)	5.8 (0.23)	7.6 (0.30)	—	—	3.0 (0.12)	1.17 (0.046)	1.5 (0.06)	2,4,5	0.277
RXEF075	—	10.2 (0.40)	—	15.2 (0.60)	4.3 (0.17)	5.8 (0.23)	7.6 (0.30)	—	—	3.0 (0.12)	1.17 (0.046)	1.5 (0.06)	2,4,5	0.310
RXEF090	—	11.2 (0.44)	—	15.8 (0.62)	4.3 (0.17)	5.8 (0.23)	7.6 (0.30)	—	—	3.0 (0.12)	1.17 (0.046)	1.5 (0.06)	2,4,5	0.365

© 2022 Littelfuse, Inc.
Specifications are subject to change without notice.

RXEF Series
Radial Leaded

Dimension Figures




Figure 1




Figure 2




Figure 3




Figure 4




Figure 5

Dimensions and Weights (Cont'd)

Part Number	Dimensions in Millimeters (Inches)												Figure	Device Mass (g) (Only for Reference)
	A		B		C		D		E		H	J		
	Min	Max	Min	Max	Min	Max	Min	Max	Min	Max	Typ	Typ		
RXEF – 72V														
RXEF110	—	12.8 (0.50)	—	17.5 (0.69)	4.3 (0.17)	5.8 (0.23)	7.6 (0.30)	—	—	3.0 (0.12)	1.37 (0.054)	1.2 (0.05)	3,4,5	0.546
RXEF135	—	14.5 (0.57)	—	19.1 (0.75)	4.3 (0.17)	5.8 (0.23)	7.6 (0.30)	—	—	3.0 (0.12)	1.37 (0.054)	1.2 (0.05)	3,4,5	0.653
RXEF160	—	16.3 (0.64)	—	20.8 (0.82)	4.3 (0.17)	5.8 (0.23)	7.6 (0.30)	—	—	3.0 (0.12)	1.37 (0.054)	1.5 (0.06)	3,4,5	0.684
RXEF185	—	17.5 (0.69)	—	22.4 (0.88)	4.3 (0.17)	5.8 (0.23)	7.6 (0.30)	—	—	3.0 (0.12)	1.37 (0.054)	1.5 (0.06)	3,4,5	0.808
RXEF250	—	20.8 (0.82)	—	25.4 (1.00)	9.4 (0.37)	10.9 (0.43)	7.6 (0.30)	—	—	3.0 (0.12)	1.37 (0.054)	1.7 (0.07)	3,4,5	1.139
RXEF300	—	23.9 (0.94)	—	28.6 (1.13)	9.4 (0.37)	10.9 (0.43)	7.6 (0.30)	—	—	3.0 (0.12)	1.37 (0.054)	1.7 (0.07)	3,4,5	1.379
RXEF375	—	27.2 (1.07)	—	31.8 (1.25)	9.4 (0.37)	10.9 (0.43)	7.6 (0.30)	—	—	3.0 (0.12)	1.37 (0.054)	1.7 (0.07)	3,4,5	1.708

© 2022 Littelfuse, Inc.
Specifications are subject to change without notice.
Revised: GD. 09/21/22

RXEF Series
Radial Leaded

Packaging and Marking Information

Part Number	Bag Quantity	Tape and Reel Quantity	Ammo Pack Quantity	Standard Package Quantity	Part Marking	Agency Recognition
RXEF – 60V						
RXEF005	500	—	—	10,000	—	UL, CSA, TÜV, CQC
RXEF005-2	—	3,000	—	15,000	—	UL, CSA, TÜV, CQC
RXEF005-AP	—	—	2,000	10,000	—	UL, CSA, TÜV, CQC
RXEF010	500	—	—	10,000	X10	UL, CSA, TÜV, CQC
RXEF010-2	—	3,000	—	15,000	X10	UL, CSA, TÜV, CQC
RXEF010-AP	—	—	2,000	10,000	X10	UL, CSA, TÜV, CQC
RXEF017	500	—	—	10,000	X17	UL, CSA, TÜV, CQC
RXEF017-2	—	2,500	—	12,500	X17	UL, CSA, TÜV, CQC
RXEF017-AP	—	—	2,000	10,000	X17	UL, CSA, TÜV, CQC
RXEF – 72V						
RXEF020	500	—	—	10,000	X20	UL, CSA, TÜV, CQC
RXEF020-2	—	3,000	—	15,000	X20	UL, CSA, TÜV, CQC
RXEF020-AP	—	—	2,000	10,000	X20	UL, CSA, TÜV, CQC
RXEF025	500	—	—	10,000	X25	UL, CSA, TÜV, CQC
RXEF025-2	—	3,000	—	15,000	X25	UL, CSA, TÜV, CQC
RXEF025-AP	—	—	2,000	10,000	X25	UL, CSA, TÜV, CQC
RXEF030	500	—	—	10,000	X30	UL, CSA, TÜV, CQC
RXEF030-2	—	3,000	—	15,000	X30	UL, CSA, TÜV, CQC
RXEF030-AP	—	—	2,000	10,000	X30	UL, CSA, TÜV, CQC
RXEF040	500	—	—	10,000	X40	UL, CSA, TÜV, CQC
RXEF040-2	—	3,000	—	15,000	X40	UL, CSA, TÜV, CQC
RXEF040-AP	—	—	2,000	10,000	X40	UL, CSA, TÜV, CQC
RXEF050	500	—	—	10,000	X50	UL, CSA, TÜV, CQC
RXEF050-2	—	3,000	—	15,000	X50	UL, CSA, TÜV, CQC
RXEF050-AP	—	—	2,000	10,000	X50	UL, CSA, TÜV, CQC
RXEF065	500	—	—	10,000	X65	UL, CSA, TÜV, CQC
RXEF065-2	—	3,000	—	15,000	X65	UL, CSA, TÜV, CQC
RXEF065-AP	—	—	2,000	10,000	X65	UL, CSA, TÜV, CQC
RXEF075	500	—	—	10,000	X75	UL, CSA, TÜV, CQC
RXEF075-2	—	3,000	—	15,000	X75	UL, CSA, TÜV, CQC
RXEF075-AP	—	—	2,000	10,000	X75	UL, CSA, TÜV, CQC
RXEF090	500	—	—	10,000	X90	UL, CSA, TÜV, CQC
RXEF090-2	—	3,000	—	15,000	X90	UL, CSA, TÜV, CQC
RXEF090-AP	—	—	2,000	10,000	X90	UL, CSA, TÜV, CQC
RXEF110	500	—	—	10,000	X110	UL, CSA, TÜV, CQC
RXEF110-2	—	1,500	—	7,500	X110	UL, CSA, TÜV, CQC
RXEF110-AP	—	—	1,000	5,000	X110	UL, CSA, TÜV, CQC


© 2022 Littelfuse, Inc.
Specifications are subject to change without notice.
Revised: GD. 09/21/22

RXEF Series
Radial Leaded

Packaging and Marking Information (Cont'd)

Part Number	Bag Quantity	Tape and Reel Quantity	Ammo Pack Quantity	Standard Package Quantity	Part Marking	Agency Recognition
RXEF – 72V						
RXEF135	500	—	—	10,000	X135	UL, CSA, TÜV, CQC
RXEF135-2	—	1,500	—	7,500	X135	UL, CSA, TÜV, CQC
RXEF135-AP	—	—	1,000	5,000	X135	UL, CSA, TÜV, CQC
RXEF160	500	—	—	10,000	X160	UL, CSA, TÜV, CQC
RXEF160-2	—	1,500	—	7,500	X160	UL, CSA, TÜV, CQC
RXEF160-AP	—	—	1,000	5,000	X160	UL, CSA, TÜV, CQC
RXEF185	500	—	—	10,000	X185	UL, CSA, TÜV, CQC
RXEF185-2	—	1,500	—	7,500	X185	UL, CSA, TÜV, CQC
RXEF185-AP	—	—	1,000	5,000	X185	UL, CSA, TÜV, CQC
RXEF250	250	—	—	5,000	X250	UL, CSA, TÜV, CQC
RXEF250-2	—	1,000	—	5,000	X250	UL, CSA, TÜV, CQC
RXEF250-AP	—	—	1,000	5,000	X250	UL, CSA, TÜV, CQC
RXEF300	250	—	—	5,000	X300	UL, CSA, TÜV, CQC
RXEF300-2	—	1,000	—	5,000	X300	UL, CSA, TÜV, CQC
RXEF300-AP	—	—	1,000	5,000	X300	UL, CSA, TÜV, CQC
RXEF375	250	—	—	5,000	X375	UL, CSA, TÜV, CQC

Part Ordering Number System



Note: Kinked parts are recommended to control the height of the part on the PCB in non-auto PCB applications.

© 2022 Littelfuse, Inc.
Specifications are subject to change without notice.
Revised: GD. 09/21/22

RXEF Series
Radial Leaded

Tape and Reel Specifications

RXEF devices are available in tape and reel packaging per EIA468-B/IEC60286-2 standards. See Figures 1 and 2 for details.

Description	EIA Mark	Dimension (mm)	Tolerance
Carrier Tape Width	W	18	-0.5/+1.0
Hold-Down Tape Width	W_4	11	Minimum
Top Distance between Tape Edges	W_6	3	Maximum
Sprocket Hole Position	W_5	9	-0.5/+0.75
Sprocket Hole Diameter	D_0	4	± 0.2
Abscissa to Plane (Straight Lead) (RXEF110 To RXEF300)	H	18.5	± 2.5
Abscissa to Plane (Kinked Lead) (RXEF010 To RXEF090)	H_0	16.0	± 0.5
Abscissa to Top (RXEF010 To RXEF090)	H_1	32.2	Maximum
Abscissa to Top* (RXEF110 To RXEF300)	H_1	47.5	Maximum
Overall Width with Lead Protrusion (RXEF010 To RXEF090)	C_1	43.2	Maximum
Overall Width with Lead Protrusion* (RXEF110 To RXEF300)	C_1	58	Maximum
Overall Width without Lead Protrusion (RXEF010 To RXEF090)	C_2	42.5	Maximum
Overall Width without Lead Protrusion* (RXEF110 To RXEF300)	C_2	57.0	Maximum
Lead Protrusion	L_1	1.0	Maximum
Protrusion of Cut-Out	L	11.0	Maximum
Protrusion beyond Hold-down Tape	I_2	Not Specified	—
Sprocket Hole Pitch	P_0	12.7	± 0.3
Device Pitch (RXEF010 To RXEF090)	—	12.7	± 0.3
Device Pitch (RXEF110 To RXEF300)	—	25.4	± 0.61
Pitch Tolerance	—	20 Consecutive	± 1
Tape Thickness	T	0.9	Maximum
Overall Tape and Lead Thickness (RXEF010 To RXEF090)	T_1	1.5	Maximum
Overall Tape and Lead Thickness (RXEF110 To RXEF300)	T_1	2.3	Maximum
Splice Sprocket Hole Alignment	—	0	± 0.3
Body Lateral Deviation	Dh	0	± 1.0
Body Tape Plane Deviation	Dp	0	± 1.3
Ordinate to Adjacent Component Lead (RXEF010 To RXEF185)	P_1	3.81	± 0.7
Ordinate to Adjacent Component Lead (RXEF250 To RXEF300)	P_1	7.62	± 0.7
Lead Spacing* (RXEF010 To RXEF185)	F	5.05	± 0.75
Lead Spacing* (RXEF250 To RXEF300)	F	10.15	± 0.75
Reel Width (RXEF010 To RXEF090)	W_2	56.0	Maximum
Reel Width* (RXEF110 To RXEF300)	W_2	63.5	Maximum
Reel Diameter	A	370.0	Maximum
Space between Flanges* (RXEF010 To RXEF090)	W_1	48.0	Maximum
Space between Flanges* (RXEF110 To RXEF300)	W_1	55.0	Maximum
Arbor Hold Diameter	C	26.0	± 12.0
Core Diameter*	N	91.0	Maximum
Box	—	64/372/362	Maximum
Consecutive Missing Places	—	None	—
Empty Places per Reel	—	0.1%	Maximum

*Differs from EIA specification.

© 2022 Littelfuse, Inc.
Specifications are subject to change without notice.
Revised: GD. 09/21/22

RXEF Series
Radial Leaded

Tape and Reel Diagrams




Figure 1




Figure 2

Warning

- Users should independently evaluate the suitability of and test each product selected for their own application.
- Operation beyond the maximum ratings or improper use may result in device damage and possible electrical arcing and flame.
- These devices are intended for protection against damage caused by occasional overcurrent or overtemperature fault conditions and should not be used when repeated fault conditions or prolonged trip events are anticipated.
- Contamination of the PPTC material with certain silicone-based oils or some aggressive solvents can adversely impact the performance of the devices.
- Device performance can be impacted negatively if devices are handled in a manner inconsistent with recommended electronic, thermal, and mechanical procedures for electronic components.
- PPTC devices are not recommended for installation in applications where the device is constrained such that its PTC properties are inhibited, for example in rigid potting materials or in rigid housings, which lack adequate clearance to accommodate device expansion.
- Operation in circuits with a large inductance can generate a circuit voltage (Ldi/dt) above the rated voltage of the device.

Disclaimer Notice - Information furnished is believed to be accurate and reliable. However, users should independently evaluate the suitability of and test each product selected for their own applications. Littelfuse products are not designed for, and may not be used in, all applications. Read complete Disclaimer Notice at www.littelfuse.com/disclaimer-electronics.

© 2022 Littelfuse, Inc.
Specifications are subject to change without notice.
Revised: GD. 09/21/22