



**HESTORE.HU**

elektronikai alkatrész áruház

**EN:** This Datasheet is presented by the manufacturer.

Please visit our website for pricing and availability at [www.hestore.hu](http://www.hestore.hu).



# W311MI

## AX300 Wi-Fi 6 Wireless Nano USB Adapter

### Products Description

With a mini and portable exterior, the 286 Mbps Wi-Fi 6 driver-free adapter W311MI fits securely into your computer and has no effect on the usage of neighboring ports. It contains an internal driver, which completes installation automatically once plugged into your computer without tedious installation steps. Therefore, you do not need to manually install the driver with a CD-ROM or a file downloaded from the internet. It is compatible with many operating systems concluding Windows 11, Windows 10, Windows 7, and Linux, to meet the requirements of various desktop and laptop users for wireless internet connections.

## Main Features



### Upgrade to WiFi 6 For Better Experience

Support the Next-Gen Wi-Fi 6 technology, with a transmission rate of 286Mbps, allowing you to enjoy faster transmission and lower latency, refreshing your surfing experience.



### Auto-install, Plug And Play

W311MI completes installation automatically once plugged into your computer without tedious installation steps.



### Compatible with Various Operating Systems

Compatible with Windows 11, Windows 10, Windows 7, Linux and UOS, to meet the requirements of various desktop and laptop users for wireless internet connections.

# Technical Specifications

## Hardware features

Interfaces	USB2.0
Antenna Type	Internal Antenna
Button	-
LED Indicator	-
Dimension	21mm × 15mm × 7.7mm

## Wireless features

Wireless Standard	IEEE802.11ax/b/g/n
Frequency	2.4GHz
Data Rate	2.4GHz: 286Mbps
Transmission Power	<20dBm (EIRP)、 <0.1W(EIRP)
Wireless Modes	Station Mode , Soft AP
Wireless Security	WPA-PSK/WPA2-PSK

## Other Features

Certification	CE FCC UKCA RoH
Package Contents	1 * W311MI Wireless Adapters 1 * Quick Insatalltaion Guide
Environment	Operating Temperature : 0°C ~ 45°C ; Storage Temperature : -40°C ~ 70°C . Operating Humility:10% ~ 90%RH Non-condensing Storage Humility:3% ~ 90%RH Non-condensing
System Requirements	Windows 7/10/11、 Linux (V3.2 above) 、 UOS
Related Products	TX2 Pro TX12 Pro

## **SHENZHEN TENDA TECHNOLOGY CO.,LTD.**

Tenda Technology Bldg.Int'l E-City,  
#1001 Zhong Shan Yuan Rd.,Nanshan District,Shenzhen China.

E-mail:support@tenda.com.cn

Tel:+86-755-2765 7098

Fax:+86-755-2765 7178

PC:518055

