




EN: This Datasheet/Document is presented by the manufacturer.

Please visit our website for pricing and availability at www.hestore.hu.

Adapter D-Sub 9 pin male with nuts to D-Sub 25 pin female with screws

Description

This narrow adapter by Delock can, for example, connect devices such as printers, modems and computers with serial RS-232 D-Sub 9 or D-Sub 25 interfaces.



Item no. 66982

EAN: 4043619669820

Country of origin: Taiwan,
Republic of China

Package: Zip poly bag

Technical details

- Connectors:
 - 1 x D-Sub 9 pin male with nuts
 - 1 x D-Sub 25 pin female with screws
- Pin assignment: 1 – 8, 2 – 3, 3 – 2, 4 – 20, 5 – 7, 6 – 6, 7 – 4, 8 – 5, 9 – 22, shielded
- Contacts: gold plated brass
- Screw type: #4-40 UNC
- Dimensions (LxWxH): ca. 53 x 18 x 13 mm

System requirements

- A free D-Sub 9 pin interface
- A free D-Sub 25 pin interface

Package content

- Adapter D-Sub 9 pin to D-Sub 25 pin

Images

DB 9 Pin	Name	DB 25 Pin
1	DCD	8
2	RXD	3
3	TXD	2
4	DTR	20
5	GND	7
6	DSR	6
7	RTS	4
8	CTS	5
9	RI	22

Interface

Connector 1:	1 x Serial D-Sub 9 male with nuts
Connector 2:	1 x Serial D-Sub 25 female with screws

Technical characteristics

Signal transmission:	TxD, RxD, RTS, CTS, DTR, DSR, DCD, RI, GND
----------------------	--

Physical characteristics

Pin finishing:	gold-plated
Screw type:	#4-40 UNC
Material:	metal / plastic
Length:	53 mm
Width:	18 mm
Height:	13 mm
Colour:	orange silver

Manufacturer information

Street	Beeskowdamm 13/15
Postal code	14167
City	Berlin
Country	Deutschland
E-Mail	info@delock.de
Website	www.delock.de