



EN: This Datasheet/Document is presented by the manufacturer.

Please visit our website for pricing and availability at www.hestore.hu.



Installation contactors

Installation contactors

Installation contactors are electromagnetic switching devices for switching of all kind of electric loads. They have one position of rest, capable of making, carrying and breaking currents under normal circuit conditions including operating overload conditions.



Installation contactors are the most flexible switching devices for use in all types of applications. In electronic system provide reliable, safe and efficient management of electrical equipment.

For universal switching

- All kind of motors
- Electric heating
- Lights and lighting
- Electrical and electronic equipment

Advanced operation

- Remote control
- Manual control

Other benefits

- Silent hum-free AC/DC version with overvoltage protection
- Available also standard AC version
- Fast switching
- Wide application
- Mounting on 35 mm rail
- Sealing terminal covers
- Control voltages up to 400 V



Installation contactors	page 2
Installation contactors with manual control	page 6
Installation contactors with manual momentary control.....	page 9
UL/CSA installation contactors	page 11
Accessories	page 14
Installation switches and installation momentary switches	page 16

Ordering data	page 5, 8, 10, 13
Technical characteristics	page 18
Dimensions	page 38

Installation Contactors

up to 32 A

AC-1 acc. to IEC/EN 60947-4-1 (2-pole, 1 module)






AC

Type	Rated current I _e	Control voltage at 50/60 Hz	Wiring diagram	Ordering No.	Weight (g)	Packaging (pcs)
IKA20-20	20 A	230 V		30.046.005	130	6
IKA20-20	20 A	24 V		30.046.021	130	
IKA225-20	25 A	230 V		30.046.714	130	
IKA225-20	25 A	24 V		30.046.711	130	
IKA232-20	32 A	230 V		30.046.833	130	
IKA232-20	32 A	24 V		30.046.834	130	
IKA20-11	20 A	230 V		30.046.009	130	6
IKA20-11	20 A	24 V		30.046.022	130	
IKA225-11	25 A	230 V		30.046.715	130	
IKA225-11	25 A	24 V		30.046.712	130	
IKA232-11	32 A	230 V		30.046.835	130	
IKA232-11	32 A	24 V		30.046.836	130	
IKA20-10	20 A	230 V		30.046.457	125	6
IKA20-10	20 A	24 V		30.046.837	125	
IKA225-10	25 A	230 V		30.046.713	125	
IKA225-10	25 A	24 V		30.046.710	125	
IKA232-10	32 A	230 V		30.046.838	125	
IKA232-10	32 A	24 V		30.046.839	125	
IKA20-01	20 A	230 V		30.046.716	125	6
IKA20-01	20 A	24 V		30.046.840	125	
IKA225-01	25 A	230 V		30.046.841	125	
IKA225-01	25 A	24 V		30.046.842	125	
IKA232-01	32 A	230 V		30.046.843	125	
IKA232-01	32 A	24 V		30.046.844	125	
IKA20-02	20 A	230 V		30.046.010	130	6
IKA20-02	20 A	24 V		30.046.023	130	
IKA225-02	25 A	230 V		30.046.845	130	
IKA225-02	25 A	24 V		30.046.846	130	
IKA232-02	32 A	230 V		30.046.847	130	
IKA232-02	32 A	24 V		30.046.848	130	



AC-1 acc. to IEC/EN 60947-4-1 (4-pole, 2 modules)

AC






Type	Rated current I _e	Control voltage at 50/60 Hz	Wiring diagram	Ordering No.	Weight (g)	Packaging (pcs)
IKA25-40	25 A	230 V		30.046.007	230	3
IKA25-40	25 A	24 V		30.046.027	230	
IKA432-40	32 A	230 V		30.046.849	230	
IKA432-40	32 A	24 V		30.046.850	230	
IKA25-31	25 A	230 V		30.046.013	230	3
IKA25-31	25 A	24 V		30.046.028	230	
IKA432-31	32 A	230 V		30.046.851	230	
IKA432-31	32 A	24 V		30.046.852	230	
IKA25-30	25 A	230 V		30.046.282	225	3
IKA25-30	25 A	24 V		30.046.853	225	
IKA432-30	32 A	230 V		30.046.854	225	
IKA432-30	32 A	24 V		30.046.855	225	
IKA25-22	25 A	230 V		30.046.014	230	3
IKA25-22	25 A	24 V		30.046.029	230	
IKA432-22	32 A	230 V		30.046.856	230	
IKA432-22	32 A	24 V		30.046.857	230	
IKA25-04	25 A	230 V		30.046.015	230	3
IKA25-04	25 A	24 V		30.046.030	230	
IKA432-04	32 A	230 V		30.046.858	230	
IKA432-04	32 A	24 V		30.046.859	230	



Other control voltages are on request - define type and voltage

AC-1 acc. to IEC/EN 60947-4-1 (4-pole, 3 modules)



63 A
AC

Type	Rated current I_e	Control voltage at 50/60 Hz	Wiring diagram	Ordering No.	Weight (g)	Packaging (pcs)
IKA40-40	40 A	230 V		30.045.518	350	5
IKA40-40	40 A	24 V		30.045.595	350	
IKA63-40	63 A	230 V		30.045.522	350	
IKA63-40	63 A	24 V		30.045.711	350	
IKA40-31	40 A	230 V		30.045.597	350	5
IKA40-31	40 A	24 V		30.045.598	350	
IKA63-31	63 A	230 V		30.045.533	350	
IKA63-31	63 A	24 V		30.045.599	350	
IKA40-30	40 A	230 V		30.045.517	340	5
IKA40-30	40 A	24 V		30.045.600	340	
IKA63-30	63 A	230 V		30.045.521	340	
IKA63-30	63 A	24 V		30.045.601	340	
IKA40-22	40 A	230 V		30.045.519	350	5
IKA40-22	40 A	24 V		30.045.602	350	
IKA63-22	63 A	230 V		30.045.523	350	
IKA63-22	63 A	24 V		30.045.603	350	
IKA40-04	40 A	230 V		30.045.511	350	5
IKA40-04	40 A	24 V		30.045.604	350	
IKA63-04	63 A	230 V		30.045.605	350	
IKA63-04	63 A	24 V		30.045.606	350	



AC-1 acc. to IEC/EN 60947-4-1 (4-pole, 2 modules)

20 A
AC




Type	Rated current I_e	Control voltage at 50/60 Hz	Wiring diagram	Ordering No.	Weight (g)	Packaging (pcs)
IK21-10	20 A	220-240 V		30.041.246	170	10
IK21-10	20 A	24 V		30.041.289	170	
IK21-01	20 A	220-240 V		30.041.245	170	10
IK21-01	20 A	24 V		30.041.249	170	

SLIM CASE



AC-1 acc. to IEC/EN 60947-4-1 (2-pole, 1 module)

32 A
AC/DC

Type	Rated current I_e	Control voltage at 50/60 Hz	Wiring diagram	Ordering No.	Weight (g)	Packaging (pcs)
IKD20-20	20 A	230 V AC		30.046.006	130	6
IKD20-20	20 A	220 V DC		30.046.024	130	
IKD20-20	20 A	24 V AC/DC		30.046.024	130	
IKD20-20	20 A	24 V AC/DC		30.046.024	130	
IKD225-20	25 A	230 V AC		30.046.860	130	6
IKD225-20	25 A	220 V DC		30.046.861	130	
IKD225-20	25 A	24 V AC/DC		30.046.862	130	
IKD225-20	25 A	24 V AC/DC		30.046.863	130	
IKD232-20	32 A	230 V AC		30.046.011	130	6
IKD232-20	32 A	220 V DC		30.046.025	130	
IKD232-20	32 A	24 V AC/DC		30.046.025	130	
IKD232-20	32 A	24 V AC/DC		30.046.025	130	
IKD20-11	20 A	230 V AC		30.046.864	130	6
IKD20-11	20 A	220 V DC		30.046.865	130	
IKD20-11	20 A	24 V AC/DC		30.046.866	130	
IKD20-11	20 A	24 V AC/DC		30.046.867	130	

HUM-FREE



Other control voltages are on request - define type and voltage

Installation Contactors

up to 32 A

AC-1 acc. to IEC/EN 60947-4-1 (2-pole, 1 module)




HUM-FREE

Type	Rated current I_n	Control voltage at 50/60 Hz	Wiring diagram	Ordering No.	Weight (g)	Packaging (pcs)
IKD20-10	20 A	230 V AC		30.046.868	125	6
		220 V DC				
IKD20-10	20 A	24 V AC/DC		30.046.590	125	
IKD225-10	25 A	230 V AC		30.046.869	125	
		220 V DC				
IKD225-10	25 A	24 V AC/DC		30.046.870	125	
IKD232-10	32 A	230 V AC		30.046.871	125	6
		220 V DC				
IKD232-10	32 A	24 V AC/DC		30.046.872	125	
IKD20-01	20 A	230 V AC		30.046.873	125	6
		220 V DC				
IKD20-01	20 A	24 V AC/DC		30.046.874	125	
IKD225-01	25 A	230 V AC		30.046.875	125	
		220 V DC				
IKD225-01	25 A	24 V AC/DC		30.046.876	125	
IKD232-01	32 A	230 V AC		30.046.877	125	6
		220 V DC				
IKD232-01	32 A	24 V AC/DC		30.046.878	125	
IKD20-02	20 A	230 V AC		30.046.012	130	6
		220 V DC				
IKD20-02	20 A	24 V AC/DC		30.046.026	130	
IKD225-02	25 A	230 V AC		30.046.879	130	
		220 V DC				
IKD225-02	25 A	24 V AC/DC		30.046.880	130	
IKD232-02	32 A	230 V AC		30.046.881	130	6
		220 V DC				
IKD232-02	32 A	24 V AC/DC		30.046.882	130	



AC-1 acc. to IEC/EN 60947-4-1 (4-pole, 2 modules)

HUM-FREE

Type	Rated current I_n	Control voltage at 50/60 Hz	Wiring diagram	Ordering No.	Weight (g)	Packaging (pcs)
IKD25-40	25 A	230 V AC		30.046.008	250	3
		220 V DC				
IKD25-40	25 A	24 V AC/DC		30.046.031	250	
IKD432-40	32 A	230 V AC		30.046.883	250	
		220 V DC				
IKD432-40	32 A	24 V AC/DC		30.046.884	250	
IKD25-31	25 A	230 V AC		30.046.016	250	3
		220 V DC				
IKD25-31	25 A	24 V AC/DC		30.046.032	250	
IKD432-31	32 A	230 V AC		30.046.885	250	
		220 V DC				
IKD432-31	32 A	24 V AC/DC		30.046.886	250	
IKD25-30	25 A	230 V AC		30.046.887	245	3
		220 V DC				
IKD25-30	25 A	24 V AC/DC		30.046.888	245	
IKD432-30	32 A	230 V AC		30.046.889	245	
		220 V DC				
IKD432-30	32 A	24 V AC/DC		30.046.890	245	





Other control voltages are on request - define type and voltage

AC-1 acc. to IEC/EN 60947-4-1 (4-pole, 2 modules)

32 A

AC/DC

HUM-FREE

Type	Rated current I _e	Control voltage at 50/60 Hz	Wiring diagram	Ordering No.	Weight (g)	Packaging (pcs)
IKD25-22	25 A	230 V AC		30.046.017	250	3
		220 V DC		30.046.033	250	
IKD25-22	25 A	24 V AC/DC		30.046.891	250	
IKD432-22	32 A	230 V AC		30.046.892	250	
IKD432-22	32 A	220 V DC		30.046.018	250	3
IKD25-04	25 A	230 V AC		30.046.034	250	
IKD25-04	25 A	24 V AC/DC		30.046.893	250	
IKD432-04	32 A	230 V AC		30.046.894	250	
IKD432-04	32 A	220 V DC				
IKD25-04	25 A	230 V AC				
IKD25-04	25 A	24 V AC/DC				
IKD432-04	32 A	230 V AC				








AC-1 acc. to IEC/EN 60947-4-1 (4-pole, 3 modules)

63 A

AC/DC

HUM-FREE

Type	Rated current I _e	Control voltage at 50/60 Hz	Wiring diagram	Ordering No.	Weight (g)	Packaging (pcs)
IK40-40	40 A	230 V AC		30.045.010	420	5
		220 V DC		30.045.022	420	
IK40-40	40 A	24 V AC/DC		30.045.011	420	
IK63-40	63 A	230 V AC		30.045.187	420	
IK63-40	63 A	220 V DC		30.045.086	420	5
IK40-31	40 A	230 V AC		30.045.485	420	
IK40-31	40 A	24 V AC/DC		30.045.087	420	
IK63-31	63 A	230 V AC		30.045.234	420	
IK63-31	63 A	220 V DC		30.045.268	410	5
IK40-30	40 A	230 V AC		30.045.607	410	
IK40-30	40 A	24 V AC/DC		30.045.608	410	
IK63-30	63 A	230 V AC		30.045.609	410	
IK63-30	63 A	220 V DC		30.045.150	420	5
IK40-22	40 A	230 V AC		30.045.172	420	
IK40-22	40 A	24 V AC/DC		30.045.235	420	
IK63-22	63 A	230 V AC		30.045.233	420	
IK63-22	63 A	220 V DC		30.045.145	420	5
IK40-04	40 A	230 V AC		30.045.232	420	
IK40-04	40 A	24 V AC/DC		30.045.610	420	
IK63-04	50 A	230 V AC		30.045.611	420	
IK63-04	50 A	220 V DC				
IK40-04	40 A	230 V AC				
IK40-04	40 A	24 V AC/DC				
IK63-04	50 A	230 V AC				



Other control voltages are on request - define type and voltage

Ordering data

IKA63 - 40 / 12 V

Control voltage

Version of contacts

Basic type

Installation Contactors with Manual Control

up to 32 A



IKA*-R and IKD*-R are upgraded version of basic types of contactors. Besides basic functions they enable manual control with a handle.

Description of the handle position:

- **A:** the contactor functions as an installation contactor without manual control
- **O:** permanently switched off control voltage
- **I:** at manual shifting the handle from position **A** to **I** causes the contactor to close; when control voltage is applied, the handle is automatically set to position **A**.

Contactor with manual control enable:

- switching depending on tariff (selection of the most convenient tariff)
- switching when control voltage is not applied

AC-1 acc. to IEC/EN 60947-4-1 (2-pole, 1 module)

AC




Type	Rated current I_n	Control voltage at 50/60 Hz	Wiring diagram	Ordering No.	Weight (g)	Packaging (pcs)
IKA20-20-R	20 A	230 V		30.046.265	130	6
IKA20-20-R	20 A	24 V		30.046.268	130	
IKA225-20-R	25 A	230 V		30.046.895	130	
IKA225-20-R	25 A	24 V		30.046.896	130	
IKA232-20-R	32 A	230 V		30.046.897	130	
IKA232-20-R	32 A	24 V		30.046.898	130	
IKA20-11-R	20 A	230 V		30.046.266	130	6
IKA20-11-R	20 A	24 V		30.046.269	130	
IKA225-11-R	25 A	230 V		30.046.899	130	
IKA225-11-R	25 A	24 V		30.046.900	130	
IKA232-11-R	32 A	230 V		30.046.901	130	
IKA232-11-R	32 A	24 V		30.046.902	130	
IKA20-10-R	20 A	230 V		30.046.496	125	6
IKA20-10-R	20 A	24 V		30.046.903	125	
IKA225-10-R	25 A	230 V		30.046.904	125	
IKA225-10-R	25 A	24 V		30.046.905	125	
IKA232-10-R	32 A	230 V		30.046.906	125	
IKA232-10-R	32 A	24 V		30.046.907	125	
IKA20-01-R	20 A	230 V		30.046.908	125	6
IKA20-01-R	20 A	24 V		30.046.909	125	
IKA225-01-R	25 A	230 V		30.046.910	125	
IKA225-01-R	25 A	24 V		30.046.911	125	
IKA232-01-R	32 A	230 V		30.046.912	125	
IKA232-01-R	32 A	24 V		30.046.913	125	
IKA20-02-R	20 A	230 V		30.046.267	130	6
IKA20-02-R	20 A	24 V		30.046.270	130	
IKA225-02-R	25 A	230 V		30.046.914	130	
IKA225-02-R	25 A	24 V		30.046.915	130	
IKA232-02-R	32 A	230 V		30.046.916	130	
IKA232-02-R	32 A	24 V		30.046.917	130	



Other control voltages are on request - define type and voltage

AC-1 acc. to IEC/EN 60947-4-1 (4-pole, 2 module)

AC

Type	Rated current I _e	Control voltage at 50/60 Hz	Wiring diagram	Ordering No.	Weight (g)	Packaging (pcs)
IKA25-40-R	25 A	230 V		30.046.271	230	3
IKA25-40-R	25 A	24 V		30.046.275	230	
IKA432-40-R	32 A	230 V		30.046.918	230	
IKA432-40-R	32 A	24 V		30.046.919	230	
IKA25-31-R	25 A	230 V		30.046.272	230	3
IKA25-31-R	25 A	24 V		30.046.276	230	
IKA432-31-R	32 A	230 V		30.046.920	230	
IKA432-31-R	32 A	24 V		30.046.921	230	
IKA25-30-R	25 A	230 V		30.046.922	225	3
IKA25-30-R	25 A	24 V		30.046.923	225	
IKA432-30-R	32 A	230 V		30.046.924	225	
IKA432-30-R	32 A	24 V		30.046.925	225	
IKA25-22-R	25 A	230 V		30.046.273	230	3
IKA25-22-R	25 A	24 V		30.046.277	230	
IKA432-22-R	32 A	230 V		30.046.926	230	
IKA432-22-R	32 A	24 V		30.046.927	230	
IKA25-04-R	25 A	230 V		30.046.274	230	3
IKA25-04-R	25 A	24 V		30.046.278	230	
IKA432-04-R	32 A	230 V		30.046.928	230	
IKA432-04-R	32 A	24 V		30.046.929	230	



AC-1 acc. to IEC/EN 60947-4-1 (2-pole, 1 module)

AC/DC

HUM-FREE

Type	Rated current I _e	Control voltage at 50/60 Hz	Wiring diagram	Ordering No.	Weight (g)	Packaging (pcs)
IKD20-20-R	20 A	230 V AC		30.046.381	130	6
IKD20-20-R	20 A	220 V DC		30.046.506	130	
IKD20-20-R	20 A	24 V AC/DC		30.046.930	130	
IKD225-20-R	25 A	230 V AC		30.046.930	130	
IKD225-20-R	25 A	220 V DC		30.046.931	130	
IKD225-20-R	25 A	24 V AC/DC		30.046.932	130	
IKD232-20-R	32 A	230 V AC		30.046.932	130	6
IKD232-20-R	32 A	220 V DC		30.046.933	130	
IKD232-20-R	32 A	24 V AC/DC		30.046.933	130	
IKD20-11-R	20 A	230 V AC		30.046.507	130	
IKD20-11-R	20 A	220 V DC		30.046.508	130	
IKD20-11-R	20 A	24 V AC/DC		30.046.508	130	
IKD225-11-R	25 A	230 V AC		30.046.934	130	6
IKD225-11-R	25 A	220 V DC		30.046.935	130	
IKD225-11-R	25 A	24 V AC/DC		30.046.935	130	
IKD232-11-R	32 A	230 V AC		30.046.936	130	
IKD232-11-R	32 A	220 V DC		30.046.936	130	
IKD232-11-R	32 A	24 V AC/DC		30.046.937	130	
IKD20-10-R	20 A	230 V AC		30.046.938	125	6
IKD20-10-R	20 A	220 V DC		30.046.939	125	
IKD20-10-R	20 A	24 V AC/DC		30.046.939	125	
IKD225-10-R	25 A	230 V AC		30.046.940	125	
IKD225-10-R	25 A	220 V DC		30.046.941	125	
IKD225-10-R	25 A	24 V AC/DC		30.046.941	125	
IKD232-10-R	32 A	230 V AC		30.046.942	125	6
IKD232-10-R	32 A	220 V DC		30.046.942	125	
IKD232-10-R	32 A	24 V AC/DC		30.046.943	125	6



Other control voltages are on request - define type and voltage

Installation Contactors with Manual Control up to 32 A

AC-1 acc. to IEC/EN 60947-4-1 (2-pole, 1 module)









HUM-FREE

Type	Rated current I_n	Control voltage at 50/60 Hz	Wiring diagram	Ordering No.	Weight (g)	Packaging (pcs)
IKD20-01-R	20 A	230 V AC		30.046.944	125	6
		220 V DC				
IKD20-01-R	20 A	24 V AC/DC		30.046.945	125	
IKD225-01-R	25 A	230 V AC		30.046.946	125	
		220 V DC				
IKD225-01-R	25 A	24 V AC/DC		30.046.947	125	
IKD232-01-R	32 A	230 V AC		30.046.948	125	6
		220 V DC				
IKD232-01-R	32 A	24 V AC/DC		30.046.949	125	
IKD20-02-R	20 A	230 V AC		30.046.950	130	6
		220 V DC				
IKD20-02-R	20 A	24 V AC/DC		30.046.951	130	
IKD225-02-R	25 A	230 V AC		30.046.952	130	
		220 V DC				
IKD225-02-R	25 A	24 V AC/DC		30.046.953	130	
IKD232-02-R	32 A	230 V AC		30.046.954	130	6
IKD232-02-R	32 A	220 V DC		30.046.955	130	



AC-1 acc. to IEC/EN 60947-4-1 (4-pole, 2 modules)

HUM-FREE

Type	Rated current I_n	Control voltage at 50/60 Hz	Wiring diagram	Ordering No.	Weight (g)	Packaging (pcs)
IKD25-40-R	25 A	230 V AC		30.046.509	250	3
		220 V DC				
IKD25-40-R	25 A	24 V AC/DC		30.046.510	250	
IKD432-40-R	32 A	230 V AC		30.046.956	250	
IKD432-40-R	32 A	220 V DC		30.046.957	250	3
IKD25-31-R	25 A	230 V AC		30.046.958	250	
		220 V DC				
IKD25-31-R	25 A	24 V AC/DC		30.046.959	250	
IKD432-31-R	32 A	230 V AC		30.046.960	250	3
		220 V DC				
IKD432-31-R	32 A	24 V AC/DC		30.046.961	250	
IKD25-30-R	25 A	230 V AC		30.046.962	245	3
		220 V DC				
IKD25-30-R	25 A	24 V AC/DC		30.046.963	245	
IKD432-30-R	32 A	230 V AC		30.046.964	245	
IKD432-30-R	32 A	220 V DC		30.046.965	245	3
IKD25-22-R	25 A	230 V AC		30.046.966	250	
		220 V DC				
IKD25-22-R	25 A	24 V AC/DC		30.046.967	250	
IKD432-22-R	32 A	230 V AC		30.046.968	250	3
		220 V DC				
IKD432-22-R	32 A	24 V AC/DC		30.046.969	250	
IKD25-04-R	25 A	230 V AC		30.046.970	250	3
		220 V DC				
IKD25-04-R	25 A	24 V AC/DC		30.046.971	250	
IKD432-04-R	32 A	230 V AC		30.046.972	250	
IKD432-04-R	32 A	220 V DC		30.046.973	250	3
IKD432-04-R	32 A	24 V AC/DC				



Other control voltages are on request - define type and voltage

Ordering data

IKA20 - 20 - R / 12 V

Control voltage
Manual control
Version of contacts
Basic type



IKA*-T and IKD*-T are upgraded version of basic types of contactors. Besides basic functions they enable manual control with a handle.

Description of the handle position:

- **A:** the contactor functions as an installation contactor
- **O:** permanently switched off control voltage
- **I:** momentary switch-on depending of manual activation






AC-1 acc. to IEC/EN 60947-4-1 (2-pole, 1 module)

Type	Rated current I _e	Control voltage at 50/60 Hz	Wiring diagram	Ordering No.	Weight (g)	Packaging (pcs)
IKA20-20-T	20 A	230 V		30.046.974	130	6
IKA225-20-T	25 A	230 V		30.046.975	130	
IKA232-20-T	32 A	230 V		30.046.976	130	
IKA20-11-T	20 A	230 V		30.046.977	130	6
IKA225-11-T	25 A	230 V		30.046.978	130	
IKA232-11-T	32 A	230 V		30.046.979	130	
IKA20-10-T	20 A	230 V		30.046.980	125	6
IKA225-10-T	25 A	230 V		30.046.981	125	
IKA232-10-T	32 A	230 V		30.046.982	125	
IKA20-01-T	20 A	230 V		30.046.983	125	6
IKA225-01-T	25 A	230 V		30.046.984	125	
IKA232-01-T	32 A	230 V		30.046.985	125	
IKA20-02-T	20 A	230 V		30.046.986	130	6
IKA225-02-T	25 A	230 V		30.046.987	130	
IKA232-02-T	32 A	230 V		30.046.988	130	

AC



AC-1 acc. to IEC/EN 60947-4-1 (4-pole, 2 modules)

Type	Rated current I _e	Control voltage at 50/60 Hz	Wiring diagram	Ordering No.	Weight (g)	Packaging (pcs)
IKA25-40-T	25 A	230 V		30.046.989	230	3
IKA432-40-T	32 A	230 V		30.046.990	230	
IKA25-31-T	25 A	230 V		30.046.991	230	3
IKA432-31-T	32 A	230 V		30.046.992	230	
IKA25-30-T	25 A	230 V		30.046.993	225	3
IKA432-30-T	32 A	230 V		30.046.994	225	
IKA25-22-T	25 A	230 V		30.046.995	230	3
IKA432-22-T	32 A	230 V		30.046.996	230	
IKA25-04-T	25 A	230 V		30.046.997	230	3
IKA432-04-T	32 A	230 V		30.046.998	230	

AC



Other control voltages are on request - define type and voltage

Installation Contactors with Manual Momentary Control up to 32 A

AC-1 acc. to IEC/EN 60947-4-1 (2-pole, 1 module)






HUM-FREE

Type	Rated current I_n	Control voltage at 50 Hz	Wiring diagram	Ordering No.	Weight (g)	Packaging (pcs)
IKD20-20-T	20 A	230 V AC		30.046.999	130	6
		220 V DC				
IKD225-20-T	25 A	230 V AC		30.047.000	130	
		220 V DC				
IKD232-20-T	32 A	230 V AC		30.047.001	130	
		220 V DC				
IKD20-11-T	20 A	230 V AC		30.047.002	130	6
		220 V DC				
IKD225-11-T	25 A	230 V AC		30.047.003	130	
		220 V DC				
IKD232-11-T	32 A	230 V AC		30.047.004	130	
		220 V DC				
IKD20-10-T	20 A	230 V AC		30.047.005	125	6
		220 V DC				
IKD225-10-T	25 A	230 V AC		30.047.006	125	
		220 V DC				
IKD232-10-T	32 A	230 V AC		30.047.007	125	
		220 V DC				
IKD20-01-T	20 A	230 V AC		30.047.008	125	6
		220 V DC				
IKD225-01-T	25 A	230 V AC		30.047.009	125	
		220 V DC				
IKD232-01-T	32 A	230 V AC		30.047.010	125	
		220 V DC				
IKD20-02-T	20 A	230 V AC		30.047.011	130	6
		220 V DC				
IKD225-02-T	25 A	230 V AC		30.047.012	130	
		220 V DC				
IKD232-02-T	32 A	230 V AC		30.047.013	130	
		220 V DC				



AC-1 acc. to IEC/EN 60947-4-1 (4-pole, 2 modules)

HUM-FREE

Type	Rated current I_n	Control voltage at 50/60 Hz	Wiring diagram	Ordering No.	Weight (g)	Packaging (pcs)
IKD25-40-T	25 A	230 V AC		30.047.014	250	3
		220 V DC				
IKD432-40-T	32 A	230 V AC		30.047.015	250	
		220 V DC				
IKD25-31-T	25 A	230 V AC		30.047.016	250	3
		220 V DC				
IKD432-31-T	32 A	230 V AC		30.047.017	250	
		220 V DC				
IKD25-30-T	25 A	230 V AC		30.047.018	245	3
		220 V DC				
IKD432-30-T	32 A	230 V AC		30.047.019	245	
		220 V DC				
IKD25-22-T	25 A	230 V AC		30.047.020	250	3
		220 V DC				
IKD432-22-T	32 A	230 V AC		30.047.021	250	
		220 V DC				
IKD25-04-T	25 A	230 V AC		30.047.022	250	3
		220 V DC				
IKD432-04-T	32 A	230 V AC		30.047.023	250	
		220 V DC				



Other control voltages are on request - define type and voltage

Ordering data

IKA20 - 20 - T / 12 V

Control voltage
Manual momentary control
Version of contacts
Basic type



Special designed installation contactors for markets who required UL and CSA approval.



General Use acc. to UL 60947-4-1 (2-pole, 1 module)






20 A
AC

Type	Rated current I _e	Control voltage at 50/60 Hz	Wiring diagram	Ordering No.	Weight (g)	Packaging (pcs)
IKA220-20	20 A	230 V		30.046.825	130	6
IKA220-20		120 V		30.047.024	130	
IKA220-20		24 V		30.047.025	130	
IKA220-11	20 A	230 V		30.047.289	130	6
IKA220-11		120 V		30.047.026	130	
IKA220-11		24 V		30.047.027	130	
IKA220-10	20 A	230 V		30.047.290	130	6
IKA220-10		120 V		30.047.028	125	
IKA220-10		24 V		30.047.029	125	
IKA220-01	20 A	230 V		30.047.291	130	6
IKA220-01		120 V		30.047.030	125	
IKA220-01		24 V		30.047.031	125	
IKA220-02	20 A	230 V		30.047.291	130	6
IKA220-02		120 V		30.047.032	130	
IKA220-02		24 V		30.047.033	130	



General Use acc. to UL 60947-4-1 (4-pole, 2 modules)

25 A
AC

Type	Rated current I _e	Control voltage at 50/60 Hz	Wiring diagram	Ordering No.	Weight (g)	Packaging (pcs)
IKA425-40	25 A	230 V		30.046.827	230	3
IKA425-40		120 V		30.047.034	230	
IKA425-40		24 V		30.047.035	230	
IKA425-31	25 A	230 V		30.047.293	230	3
IKA425-31		120 V		30.047.036	230	
IKA425-31		24 V		30.047.037	230	
IKA425-30	25 A	230 V		30.047.294	225	3
IKA425-30		120 V		30.047.038	225	
IKA425-30		24 V		30.047.039	225	
IKA425-22	25 A	230 V		30.047.295	230	3
IKA425-22		120 V		30.047.040	230	
IKA425-22		24 V		30.047.041	230	
IKA425-04	25 A	230 V		30.047.296	230	3
IKA425-04		120 V		30.047.042	230	
IKA425-04		24 V		30.047.043	230	



Other control voltages are on request - define type and voltage






UL/CSA Installation Contactors

from 20 A up to 63 A

General Use acc. to UL 60947-4-1 (4-pole, 3 modules)

63 A

AC

Type	Rated current I_n	Control voltage at 50/60 Hz	Wiring diagram	Ordering No.	Weight (g)	Packaging (pcs)
IKA440-40	40 A	230 V		30.045.700	350	5
IKA440-40	40 A	120 V		30.045.612	350	
IKA440-40	40 A	24 V		30.045.613	350	
IKA463-40	63 A	230 V		30.045.592	350	
IKA463-40	63 A	120 V		30.045.614	350	
IKA463-40	63 A	24 V		30.045.615	350	
IKA440-31	40 A	230 V		30.045.701	350	5
IKA440-31	40 A	120 V		30.045.616	350	
IKA463-31	40 A	24 V		30.045.617	350	
IKA463-31	63 A	230 V		30.045.702	350	
IKA463-31	63 A	120 V		30.045.618	350	
IKA463-31	63 A	24 V		30.045.619	350	
IKA440-30	40 A	230 V		30.045.703	340	5
IKA440-30	40 A	120 V		30.045.620	340	
IKA463-30	40 A	24 V		30.045.621	340	
IKA463-30	63 A	230 V		30.045.704	340	
IKA463-30	63 A	120 V		30.045.622	340	
IKA463-30	63 A	24 V		30.045.623	340	
IKA440-22	40 A	230 V		30.045.705	350	5
IKA440-22	40 A	120 V		30.045.624	350	
IKA463-22	40 A	24 V		30.045.625	350	
IKA463-22	63 A	230 V		30.045.706	350	
IKA463-22	63 A	120 V		30.045.626	350	
IKA463-22	63 A	24 V		30.045.627	350	
IKA440-04	40 A	230 V		30.045.707	350	5
IKA440-04	40 A	120 V		30.045.628	350	
IKA463-04	40 A	24 V		30.045.629	350	
IKA463-04	63 A	230 V		30.045.708	350	
IKA463-04	63 A	120 V		30.045.630	350	
IKA463-04	63 A	24 V		30.045.631	350	



General Use acc. to UL 60947-4-1 (2-pole, 1 module)

20 A

AC/DC

HUM-FREE

Type	Rated current I_n	Control voltage at 50/60 Hz	Wiring diagram	Ordering No.	Weight (g)	Packaging (pcs)
IKD220-20	20 A	230 V AC		30.046.826	130	6
IKD220-20	20 A	220 V DC		30.047.044	130	
IKD220-20	20 A	110 V DC		30.047.045	130	
IKD220-11	20 A	230 V AC		30.047.297	130	6
IKD220-11	20 A	220 V DC		30.047.046	130	
IKD220-11	20 A	110 V DC		30.047.047	130	
IKD220-10	20 A	230 V AC		30.047.298	125	6
IKD220-10	20 A	220 V DC		30.047.048	125	
IKD220-10	20 A	110 V DC		30.047.049	125	
IKD220-01	20 A	230 V AC		30.047.299	125	6
IKD220-01	20 A	220 V DC		30.047.050	125	
IKD220-01	20 A	110 V DC		30.047.051	125	
IKD220-02	20 A	230 V AC		30.047.300	130	6
IKD220-02	20 A	220 V DC		30.047.052	130	
IKD220-02	20 A	110 V DC		30.047.053	130	








Other control voltages are on request - define type and voltage

General Use acc. to UL 60947-4-1 (4-pole, 2 modules)

25 A
AC/DC

HUM-FREE







Type	Rated current I _e	Control voltage at 50/60 Hz	Wiring diagram	Ordering No.	Weight (g)	Packaging (pcs)
IKD425-40	25 A	230 V AC		30.046.828	250	6
		220 V DC				
IKD425-40	25 A	120 V AC		30.047.054	250	
		110 V DC				
IKD425-40	25 A	24 V AC/DC		30.047.055	250	
IKD425-31	25 A	230 V AC		30.047.301	250	6
		220 V DC				
IKD425-31	25 A	120 V AC		30.047.056	250	
		110 V DC				
IKD425-31	25 A	24 V AC/DC		30.047.057	250	
IKD425-30	25 A	230 V AC		30.047.302	245	6
		220 V DC				
IKD425-30	25 A	120 V AC		30.047.058	245	
		110 V DC				
IKD425-30	25 A	24 V AC/DC		30.047.059	245	
IKD425-22	25 A	230 V AC		30.047.303	250	6
		220 V DC				
IKD425-22	25 A	120 V AC		30.047.060	250	
		110 V DC				
IKD425-22	25 A	24 V AC/DC		30.047.061	250	
IKD425-04	25 A	120 V AC		30.047.062	250	6
		110 V DC				
IKD425-04	25 A	120 V AC		30.047.062	250	
		110 V DC				
IKD425-04	25 A	24 V AC/DC		30.047.063	250	



General Use acc. to UL 60947-4-1 (4-pole, 3 modules)

63 A
AC/DC

HUM-FREE

Type	Rated current I _e	Control voltage at 50/60 Hz	Wiring diagram	Ordering No.	Weight (g)	Packaging (pcs)
IKD440-40	40 A	230 V AC		30.045.709	420	5
		220 V DC				
IKD440-40	40 A	120 V AC		30.045.632	420	
		110 V DC				
IKD440-40	40 A	24 V AC/DC		30.045.633	420	
IKD463-40	63 A	230 V AC		30.045.593	420	5
		220 V DC				
IKD463-40	63 A	120 V AC		30.045.634	420	
		110 V DC				
IKD463-40	63 A	24 V AC/DC		30.045.635	420	
IKD440-31	40 A	230 V AC		30.045.710	420	5
		220 V DC				
IKD440-31	40 A	120 V AC		30.045.636	420	
		110 V DC				
IKD440-31	40 A	24 V AC/DC		30.045.637	420	
IKD463-31	63 A	230 V AC		30.045.711	420	5
		220 V DC				
IKD463-31	63 A	120 V AC		30.045.638	420	
		110 V DC				
IKD463-31	63 A	24 V AC/DC		30.045.639	420	
IKD440-30	40 A	230 V AC		30.045.712	410	5
		220 V DC				
IKD440-30	40 A	120 V AC		30.045.640	410	
		110 V DC				
IKD440-30	40 A	24 V AC/DC		30.045.641	410	
IKD463-30	63 A	230 V AC		30.045.713	410	5
		220 V DC				
IKD463-30	63 A	120 V AC		30.045.642	410	
		110 V DC				
IKD463-30	63 A	24 V AC/DC		30.045.643	410	



Other control voltages are on request - define type and voltage

UL/CSA Installation Contactors

from 20 A up to 63 A



General Use acc. to UL 60947-4-1 (4-pole, 3 modules)

63 A
AC/DC

HUM-FREE

Type	Rated current I _e	Control voltage at 50/60 Hz	Wiring diagram	Ordering No.	Weight (g)	Packaging (pcs)
IKD440-22	40 A	230 V AC		30.045.714	420	5
		220 V DC				
IKD440-22	40 A	120 V AC		30.045.644	420	
		110 V DC				
IKD440-22	40 A	24 V AC/DC		30.045.645	420	
IKD463-22	63 A	230 V AC		30.045.715	420	
		220 V DC				5
		120 V AC				
IKD463-22	63 A	120 V AC		30.045.646	420	
		110 V DC				
IKD463-22	63 A	24 V AC/DC		30.045.647	420	
IKD440-04	40 A	230 V AC		30.045.594	420	
		220 V DC				
IKD440-04	40 A	120 V AC		30.045.648	420	
		110 V DC				
IKD440-04	40 A	24 V AC/DC		30.045.649	420	



Other control voltages are on request - define type and voltage

Ordering data

IKA440 - 40 / 12 V

Control voltage
Version of contacts
Basic type

Installation Contactors

Accessories

Sealing cover for 2-pole, 1 module

Type	Ordering No.	Weight (g)	Packaging (pcs)
IK20-PP	37.425.061	1	2




Sealing cover for 4-pole, 2 modules

Type	Ordering No.	Weight (g)	Packaging (pcs)
IK25-PP	37.425.062	2	2



Sealing cover for 4-pole, 3 modules

Type	Ordering No.	Weight (g)	Packaging (pcs)
IK40/63-PP	37.423.463	3	2



Ventilation modul

Type	Ordering No.	Weight (g)	Packaging (pcs)
IKV	37.425.296	13	1



Auxiliary switch

AC-15 acc. to IEC/EN 60947-5-1 (2-pole, ½ module)

Type	Rated current I _e	Wiring diagram					Ordering No.	Weight (g)	Packaging (pcs)
		-20	-11	-01	-10	-02			
IKN20	6 A						38.046.002	30	1
IKN11	6 A	33 43	31 43	31	33	31 41	38.046.004	30	
IKN10	6 A	33 43	31 43	31	33	31 41	38.046.036	25	
IKN01	6 A	34 44	32 44	32	34	32 42	38.046.037	30	
IKN02	6 A						38.046.003	30	



Auxiliary switch

Ratings acc. to UL 508 (2-pole, ½ module)


Type	Rating code	Wiring diagram			Ordering No.	Weight (g)	Packaging (pcs)
		-20	-11	-02			
IKN20UL	C300, Q300	33 43	31 43	31 41	38.046.050	30	1
IKN11UL	C300, Q300	33 43	31 43	31 41	38.046.049	30	
IKN02UL	C300, Q300	34 44	32 44	32 42	38.046.051	30	



4-phase busbars for installation contactors up to 32 A

- insulated

Type	Module width	Length (mm)	Ordering No.	Weight (g)	Packaging (pcs)
L/32-8P	4	66	38.046.061	60	10
L/32-12P	6	98	38.046.062	86	
L/32-16P	8	138	38.046.063	114	
L/32-20P	10	173	38.046.064	141	
L/32-24P	12	208	38.046.065	169	



Single pin terminals for installation contactors up to 32 A

- insulated

Type	Pin length	Cross-section rigid/flexible (mm²)	Screw	Ordering No.	Weight (g)	Packaging (pcs)
S/32-1P	13.5/32 (total)	6-25/4-16	PZ2	38.046.066	12	25

Double pin terminals for installation contactors 40-63 A

- insulated terminals for parallel connection

Type	Pin length	Cross-section rigid/flexible (mm²)	Screw	Ordering No.	Weight (g)	Packaging (pcs)
S/63-2P	15	6-50/4-35	PZ2	38.046.067	22	25

Installation Switches and Installation Momentary Switches




IKS-R installation switches are designed for manual switching of loads with a handle in the same look as the installation contactors.

AC-21 acc. to IEC/EN 60947-3 (2-pole, 1 module)

Type	Rated current I_n	Wiring diagram	Ordering No.	Weight (g)	Packaging (pcs)
IKS220-20-R	20 A		30.047.064	55	6
IKS225-20-R	25 A		30.047.065	55	
IKS232-20-R	32 A		30.047.066	55	
IKS220-11-R	20 A		30.047.067	55	6
IKS225-11-R	25 A		30.047.068	55	
IKS232-11-R	32 A		30.047.069	55	



AC-21 acc. to IEC/EN 60947-3 (4-pole, 2 modules)

Type	Rated current I_n	Wiring diagram	Ordering No.	Weight (g)	Packaging (pcs)
IKS420-40-R	20 A		30.047.070	105	3
IKS425-40-R	25 A		30.047.071	105	
IKS432-40-R	32 A		30.047.072	105	
IKS420-31-R	20 A		30.047.073	105	3
IKS425-31-R	25 A		30.047.074	105	
IKS432-31-R	32 A		30.047.075	105	
IKS420-22-R	20 A		30.047.076	105	3
IKS425-22-R	25 A		30.047.077	105	
IKS432-22-R	32 A		30.047.078	105	






IKS-T installation momentary switches are designed for manual momentary switching of loads with a handle in the same look as the installation contactors.

AC-21 acc. to IEC/EN 60947-3 (2-pole, 1 module)

Type	Rated current I_n	Wiring diagram	Ordering No.	Weight (g)	Packaging (pcs)
IKS220-20-T	20 A		30.047.079	55	6
IKS225-20-T	25 A		30.047.080	55	
IKS232-20-T	32 A		30.047.081	55	
IKS220-11-T	20 A		30.047.082	55	6
IKS225-11-T	25 A		30.047.083	55	
IKS232-11-T	32 A		30.047.084	55	



AC-21 acc. to IEC/EN 60947-3 (4-pole, 2 modules)

Type	Rated current I_n	Wiring diagram	Ordering No.	Weight (g)	Packaging (pcs)
IKS420-40-T	20 A		30.047.085	105	3
IKS425-40-T	25 A		30.047.086	105	
IKS432-40-T	32 A		30.047.087	105	
IKS420-31-T	20 A		30.047.088	105	3
IKS425-31-T	25 A		30.047.089	105	
IKS432-31-T	32 A		30.047.090	105	
IKS420-22-T	20 A		30.047.091	105	3
IKS425-22-T	25 A		30.047.092	105	
IKS432-22-T	32 A		30.047.093	105	





Technical characteristics

Dimensions

Installation Contactors

up to 25 A



TECHNICAL DATA

GENERAL	Type	Symbol	Unit	IK21	IKA20 IKA20-R IKA20-T ¹⁾	IKD20 IKD20-R IKD20-T ¹⁾	IKA225 IKA225-R IKA225-T ¹⁾	IKD225 IKD225-R IKD225-T ¹⁾	
	Standards			IEC/EN 61095, IEC/EN 60947-4-1, IEC/EN 60947-5-1					
	Approvals			CE, EAC	CE, CB, NF, EAC		CE		
	Module width			2	1				
	Number of poles			4	2				
	Degree of protection			IP20 (IP40 when installed in installation box - distribution board)					
	Pollution degree			3					
	Climatic conditions			95 % relative humidity					
	Ambient temperature (open)		°C	-15 ... +55 ⁴⁾					
	Storage temperature		°C	-30...+80					
	Maximum altitude U _i and U _e is reduced for 1.2 % and I _e for 0.4 % for every additional 100 m		m	2000					
	Number of contactors or switches side-by-side: ≤40 °C (40 ... 55) °C			no limitation	max. 3 max. 2				
	Noise level (operation)		dB	30	30	20	30	20	
	Vibration resistance according to IEC/EN 60068-2-6	a	g	switched off: 2 (Z and X axis) / switched on: 3 (Z axis) and 1 (X axis)					
	Shock resistance according to IEC/EN 6068-2-27	a	g	switched off: 10 (Z and X axis) / switched on: 15 (Z axis) and 2 (X axis)					
	MAIN CIRCUIT	Maximum operating frequency with no load		op. c./h	3.000				
		Mechanical endurance		op. c.	3.000.000		10.000.000	3.000.000	10.000.000
Weight			g	170	130	130	130	130	
Contact reliability				≥17 V; ≥50 mA					
Minimum distance of open contacts			mm	3.6					
Power dissipation per pole			W	2.0	1.7	1.7	2.0	2.0	
Overload current withstand capability: 10 s			A	40	72				
Maximum back-up fuse for short-circuit protection gL and gG: coordination type 1 coordination type 2		I _v	A				25	25	
Rated insulation voltage		U _i	V	415	440				
Rated impulse withstand voltage		U _{imp}	kV	4					
Rated operational voltage		U _e	V	400	400 ^{2) 3)}				
Rated frequency		f	Hz	50/60					
Thermal current		I _{th}	A	20		25			
Rated operational current for AC-1, AC-7a and AC-21		I _e	A	20		25			
Operational power for AC-1, AC-7a and AC-21: single-phase 230 V three-phase 230 V three-phase 400 V		P _e	kW		4	5.4			
Maximum operating frequency for AC-1, AC-7a and AC-21			op. c./h	600					
Electrical endurance for AC-1, AC-7a and AC-21			op. c.	200.000					
Rated operational current for AC-2		I _e	A	10	12		14		
Operational power for AC-2: single-phase 230 V three-phase 230 V three-phase 400 V		P _e	kW	1.5 2.5 4.5	1.8		2.0		
Maximum operating frequency for AC-2			op. c./h	120					
Electrical endurance for AC-2			op. c.	100.000					
Rated operational current for AC-22		I _e	A	20		25			
Operational power for AC-22: single-phase 230 V three-phase 230 V three-phase 400 V		P _e	kW	3.7		4.6			
Maximum operating frequency for AC-22			op. c./h	300					
Electrical endurance for AC-22			op. c.	50.000					
Rated operational current for AC-3, AC-7b and AC-23		I _e	A	5	NO: 9 / NC: 6				
Operational power for AC-3, AC-7b and AC-23: single-phase 230 V three-phase 230 V three-phase 400 V	P _e	kW	0.37 1.1 2.2	NO: 1.3 / NC: 0.75					
Maximum operating frequency for AC-3, AC-7b and AC-23		op. c./h	600						
Electrical endurance for AC-3, AC-7b and AC-23		op. c.	300.000						

¹⁾ Available approvals only CE

²⁾ Rated operational voltage between two line (phase) conductors

³⁾ Rated operational voltage for versions of contacts -10 and -01 is 230 V

⁴⁾ Ambient temperature (open) -25...+55 °C for version with 2NO and 4NO contacts

TECHNICAL DATA

MAIN CIRCUIT	Type	Symbol	Unit	IK21	IKA20 IKA20-R IKA20-T	IKD20 IKD20-R IKD20-T	IKA225 IKA225-R IKA225-T	IKD225 IKD225-R IKD225-T
	Rated operational current for AC-5a (at 230 V)	I _e	A	8.8			11.2	
	Maximum operating frequency for AC-5a		op. c./h	600				
	Electrical endurance for AC-5a		op. c.	100.000				
	Rated operational current for AC-5b (at 230 V)	I _e	A	8.8			9.7	
	Maximum operating frequency for AC-5b		op. c./h	600				
	Electrical endurance for AC-5b		op. c.	100.000				
	Rated operational current for AC-6a (at 230 V)	I _e	A	4			4.8	
	Maximum operating frequency for AC-6a		op. c./h	600				
	Electrical endurance for AC-6a		op. c.	100.000				
	Switching of capacitors AC-6b and AC-7c (at 230 V)	C	µF	30			36	
	Maximum operating frequency for AC-6b and AC-7c		op. c./h	600				
	Electrical endurance for AC-6b and AC-7c		op. c.	100.000				
	Rated operational current for DC-1 (L/R ≤ 1 ms): 1 pole ... 24 V DC/48 V DC/60 V DC/110 V DC/ 220 V DC 2 poles in series ... 24 V DC/48 V DC/60 V DC/110 V DC/ 220 V DC 3 poles in series ... 24 V DC/48 V DC/60 V DC/110 V DC/ 220 V DC 4 poles in series ... 24 V DC/48 V DC/60 V DC/110 V DC/ 220 V DC	I _e	A	20/12/6/2/0,5 20/15/10/4/1.5 20/20/20/6/2.5 20/20/20/6/3.5	20/15/10/6/0,6 20/18/15/10/6		25/20/15/6/0,6 25/25/20/10/6	
	Maximum operating frequency for DC-1		op. c./h	300				
	Electrical endurance for DC-1		op. c.	100.000				
	Rated operational current for DC-3 (L/R ≤ 2 ms): 1 pole ... 24 V DC/48 V DC/60 V DC/110 V DC/ 220 V DC 2 poles in series ... 24 V DC/48 V DC/60 V DC/110 V DC/ 220 V DC 3 poles in series ... 24 V DC/48 V DC/60 V DC/110 V DC/ 220 V DC 4 poles in series ... 24 V DC/48 V DC/60 V DC/110 V DC/ 220 V DC	I _e	A	10/5/2/1/0.1 20/10/8/4/0.4 20/20/15/6/2.5 20/20/15/6/3.5		15/8/4/1.3/0.2 25/16/12/5.5/0.6		
	Maximum operating frequency for DC-3		op. c./h	300				
	Electrical endurance for DC-3		op. c.	100.000				
	Rated operational current for DC-5 (L/R ≤ 7.5 ms): 1 pole ... 24 V DC/48 V DC/60 V DC/110 V DC/ 220 V DC 2 poles in series ... 24 V DC/48 V DC/60 V DC/110 V DC/ 220 V DC 3 poles in series ... 24 V DC/48 V DC/60 V DC/110 V DC/ 220 V DC 4 poles in series ... 24 V DC/48 V DC/60 V DC/110 V DC/ 220 V DC	I _e	A	10/4/1/0.3/0.06 20/8/6/2/0.2 20/20/15/5/1.5 20/20/15/5/3		15/5/3/0.5/0.1 25/15/10/4/0.4		
	Maximum operating frequency for DC-5		op. c./h	300				
	Electrical endurance for DC-5		op. c.	100.000				
	Terminal capacity: rigid (solid and stranded) flexible	S	mm ²	1 ... 2.5 1 ... 2.5	1 ... 10 1 ... 6			
	Length of removed wire insulation		mm	9				
Screw			M3.5					
Screw head			PZ2	PZ1				
Tightening torque		Nm	1.2					
Contact reliability			≥17 V; ≥50 mA					
Minimum distance of open contacts		mm	3.6					
Power dissipation per pole		W	2	1.7	1.7	2	2	
Overload current withstand capability: 10 s		A	40	72				
Maximum back-up fuse for short-circuit protection gL and gG: coordination type 1 coordination type 2	I _v	A				25	25	
			20	20	20			
Rated insulation voltage	U _i	V	415	440				
Rated impulse withstand voltage	U _{imp}	kV	4					
Rated operational voltage	U _e	V	230/400					
Rated frequency	f	Hz	50/60					
Thermal current	I _{th}	A	20			25		
Rated operational current for AC-15: single-phase 230 V single-phase 400 V	I _e	A	6 4					
Maximum operating frequency for AC-15		op. c./h	1200	600				
Electrical endurance for AC-15		op. c.	200.000	300.000				
Rated operational current for DC-13: 1 pole ... 24 V DC/48 V DC/60 V DC/110 V DC/ 220 V DC 2 poles in series ... 24 V DC/48 V DC/60 V DC/110 V DC/ 220 V DC 3 poles in series ... 24 V DC/48 V DC/60 V DC/110 V DC/ 220 V DC 4 poles in series ... 24 V DC/48 V DC/60 V DC/110 V DC/ 220 V DC	I _e	A	6/4/1/0.3/0.05 6/6/4/1/0.1 6/6/6/3/1 6/6/6/4/2					

AUXILIARY CIRCUIT	Rated operational current for AC-15: single-phase 230 V single-phase 400 V	I _e	A	6 4				
	Maximum operating frequency for AC-15		op. c./h	1200	600			
	Electrical endurance for AC-15		op. c.	200.000	300.000			
	Rated operational current for DC-13: 1 pole ... 24 V DC/48 V DC/60 V DC/110 V DC/ 220 V DC 2 poles in series ... 24 V DC/48 V DC/60 V DC/110 V DC/ 220 V DC 3 poles in series ... 24 V DC/48 V DC/60 V DC/110 V DC/ 220 V DC 4 poles in series ... 24 V DC/48 V DC/60 V DC/110 V DC/ 220 V DC	I _e	A	6/4/1/0.3/0.05 6/6/4/1/0.1 6/6/6/3/1 6/6/6/4/2				

Installation Contactors

up to 25 A



TECHNICAL DATA

AUXILIARY CIRCUIT	Type	Symbol	Unit	IK21	IKA20 IKA20-R IKA20-T	IKD20 IKD20-R IKD20-T	IKA225 IKA225-R IKA225-T	IKD225 IKD225-R IKD225-T	
	Maximum operating frequency for DC-13		op. c./h	300					
	Electrical endurance for DC-13		op. c.	200.000					
	Terminal capacity: rigid (solid and stranded) flexible	S	mm ²	1 ... 2.5 1 ... 2.5	1 ... 10 1 ... 6				
	Length of removed wire insulation		mm	9					
	Screw			M3.5					
	Screw head		mm	PZ2	PZ1				
	Tightening torque			1.2					
COIL	Range of control voltage for switch-on	U _c	%	85 ... 110					
	Range of control voltage for drop out	U _c	%	AC: 75 ... 20 / DC: 75 ... 10 (where is applicable)					
	Kind of voltage			AC		AC/DC	AC	AC/DC	
	Standard control voltages	U _c	V	12, 24, 48, 120, 230, 400	12, 24, 48, 120, 230				
	Frequency of AC control voltage	f	Hz	50/60		40 ... 500	50/60	40 ... 500	
	Control mode			remote control with U _c / manual control only for types with -R and -T					
	Impulse duration of control voltage: minimum maximum			permanent permanent					
	Minimum duration between two impulses of control voltage		ms	AC: 150 / DC: 500 (where is applicable)					
	Surge immunity withstand voltage 1.2/50 μs acc. to standard IEC/EN 61000-4-5		kV	2					
	Coil consumption: switch-on operation		VA/W	30/25 5/1.5	12/10 2.8/1.2	2.1/2.1 2.1/2.1	12/10 2.8/1.2	2.1/2.1 2.1/2.1	
	Delays: make brake		ms	7 ... 20 10 ... 20	15 ... 25 10 ... 30	15 ... 45 20 ... 50	15 ... 25 10 ... 30	15 ... 45 20 ... 50	
	Terminal capacity: rigid (solid and stranded) flexible		mm ²	1 ... 2.5 1 ... 2.5					
	Length of removed wire insulation		mm	9	7				
	Screw			M3.5	M3				
	Screw head			PZ2	PZ1				
	Tightening torque		Nm	1.2	0.6				
	SAFETY	MTTF - Mean time to failure MTTF = 1/λ = B10/(0.1 n _{op})		h	AC-1: 5.000 AC-3: 7.500				
		MTTF _d - Mean time to failure dangerous MTTF _d = 1/λ _d = B10 _d /(0.1 n _{op})		h	AC-1: 6.666 AC-3: 10.000				
		B10 - Number of operating cycles until 10 % of devices fail		op. c.	AC-1: 150.000 AC-3: 225.000				
B10 _d - Number of operating cycles until 10 % of device dangerous B10 _d = B10/ratio of dangerous failures			op. c.	AC-1: 200.000 AC-3: 300.000					
λ - Failure rate λ = (0.1 n _{op})/B10			1/h	AC-1: 0.0002 AC-3: 0.000133					
λ _d - Failure rate dangerous λ _d = (0.1 n _{op})/B10 _d			1/h	AC-1: 0.00015 AC-3: 0.0001					
Ratio of dangerous failures			%	75					
n _{op} - Operating cycles (operating cycles/h)			op. c./h	300					

TECHNICAL DATA

	Type	Symbol	Unit	IKA232 IKA232-R IKA232-T	IKD232 IKD232-R IKD232-T	IKA25 IKA25-R IKA25-T ¹⁾	IKD25 IKD25-R IKD25-T ¹⁾	IKA432 IKA432-R IKA432-T ¹⁾	IKD432 IKD432-R IKD432-T ¹⁾
GENERAL	Standards			IEC/EN 61095, IEC/EN 60947-4-1, IEC/EN 60947-5-1					
	Approvals			CE, EAC		CE, CB, NF, EAC		CE	
	Module width			1		2			
	Number of poles			2		4			
	Degree of protection			IP20 (IP40 when installed in installation box - distribution board)					
	Pollution degree			3					
	Climatic conditions			95 % relative humidity					
	Ambient temperature (open)		°C	-15 ... +55 ⁴⁾					
	Storage temperature		°C	-30...+80					
	Maximum altitude U _i and U _e is reduced for 1.2 % and I _e for 0.4 % for every additional 100 m		m	2000					
	Number of contactors or switches side-by-side: ≤40 °C (40 ... 55) °C			max. 3 max. 2					
	Noise level (operation)		dB	30	20	30	20	30	20
	Vibration resistance according to IEC/EN 60068-2-6	a	g	switched off: 2 (Z and X axis) / switched on: 3 (Z axis) and 1 (X axis)					
	Shock resistance according to IEC/EN 6068-2-27	a	g	switched off: 10 (Z and X axis) / switched on: 15 (Z axis) and 2 (X axis)					
	Maximum operating frequency with no load		op. c./h	3.000					
	Mechanical endurance		op. c.	3.000.000	10.000.000	3.000.000	10.000.000	3.000.000	10.000.000
	Weight		g	130	130	230	250	230	250
MAIN CIRCUIT	Contact reliability			≥17 V; ≥50 mA					
	Minimum distance of open contacts		mm	3,6					
	Power dissipation per pole		W	2.5	2.5	2.2	2.2	2.5	2.5
	Overload current withstand capability: 10 s		A	72		68			
	Maximum back-up fuse for short-circuit protection gL and gG: coordination type 1 coordination type 2	I _v	A	32	32	25	25	32	32
	Rated insulation voltage	U _i	V	440					
	Rated impulse withstand voltage	U _{imp}	kV	4					
	Rated operational voltage	U _e	V	400 ²⁽³⁾		400			
	Rated frequency	f	Hz	50/60					
	Thermal current	I _{th}	A	32		25		32	
	Rated operational current for AC-1, AC-7a and AC-21	I _e	A	32		25		32	
	Operational power for AC-1, AC-7a and AC-21: single-phase 230 V three-phase 230 V three-phase 400 V	P _e	kW	7		5,4		7	
						9		12	
						16		21	
	Maximum operating frequency for AC-1, AC-7a and AC-21		op. c./h	600					
	Electrical endurance for AC-1, AC-7a and AC-21		op. c.	NO: 150.000 / NC: 100.000		200.000		150.000	
	Rated operational current for AC-2	I _e	A	16		14		16	
	Operational power for AC-2: single-phase 230 V three-phase 230 V three-phase 400 V	P _e	kW	2,4		2		2,4	
						3,6		4,1	
						6		7,2	
	Maximum operating frequency for AC-2		op. c./h	120					
	Electrical endurance for AC-2		op. c.	100.000					
	Rated operational current for AC-22	I _e	A	32		25		32	
	Operational power for AC-22: single-phase 230 V three-phase 230 V three-phase 400 V	P _e	kW	5,9		4,6		5,9	
						8		10,2	
						13,8		17,7	
	Maximum operating frequency for AC-22		op. c./h	300					
	Electrical endurance for AC-22		op. c.	50.000					
	Rated operational current for AC-3, AC-7b and AC-23	I _e	A	NO: 9 / NC: 6		8,5			
	Operational power for AC-3, AC-7b and AC-23: single-phase 230 V three-phase 230 V three-phase 400 V	P _e	kW	NO: 1,3 / NC: 0,75		1,3			
						2,2			
						4			
	Maximum operating frequency for AC-3, AC-7b and AC-23		op. c./h	600					
Electrical endurance for AC-3, AC-7b and AC-23		op. c.	300.000		500.000				

¹⁾ Available approvals only CE

²⁾ Rated operational voltage between two line (phase) conductors

³⁾ Rated operational voltage for versions of contacts -10 and -01 is 230 V

⁴⁾ Ambient temperature (open) -25...+55 °C for version with 2NO and 4NO contacts

Installation Contactors

up to 32 A



TECHNICAL DATA

Type	Symbol	Unit	IKA232	IKD232	IKA25	IKD25	IKA432	IKD432
			IKA232-R IKA232-T	IKD232-R IKD232-T	IKA25-R IKA25-T	IKD25-R IKD25-T	IKA432-R IKA432-T	IKD432-R IKD432-T
Rated operational current for AC-5a (at 230 V)	I _e	A	13		11.2		13	
Maximum operating frequency for AC-5a		op. c./h	600					
Electrical endurance for AC-5a		op. c.	100.000					
Rated operational current for AC-5b (at 230 V)	I _e	A	11		9.7		11	
Maximum operating frequency for AC-5b		op. c./h	600					
Electrical endurance for AC-5b		op. c.	100.000					
Rated operational current for AC-6a (at 230 V)	I _e	A	6		2.8		6	
Maximum operating frequency for AC-6a		op. c./h	600					
Electrical endurance for AC-6a		op. c.	100.000					
Switching of capacitors AC-6b and AC-7c (at 230 V)	C	µF	40		36		40	
Maximum operating frequency for AC-6b and AC-7c		op. c./h	600					
Electrical endurance for AC-6b and AC-7c		op. c.	100.000					
Rated operational current for DC-1 (L/R ≤ 1 ms): 1 pole ... 24 V DC/48 V DC/60 V DC/110 V DC/ 220 V DC 2 poles in series ... 24 V DC/48 V DC/60 V DC/110 V DC/ 220 V DC 3 poles in series ... 24 V DC/48 V DC/60 V DC/110 V DC/ 220 V DC 4 poles in series ... 24 V DC/48 V DC/60 V DC/110 V DC/ 220 V DC	I _e	A	32/25/15/6/0.6		25/20/15/6/0.6		32/25/15/6/0.6	
			32/32/20/10/6		25/25/20/10/6		32/32/20/10/6	
					25/25/25/20/15		32/32/32/20/15	
					25/25/25/20/15		32/32/32/20/15	
Maximum operating frequency for DC-1		op. c./h	300					
Electrical endurance for DC-1		op. c.	100.000					
Rated operational current for DC-3 (L/R ≤ 2 ms): 1 pole ... 24 V DC/48 V DC/60 V DC/110 V DC/ 220 V DC 2 poles in series ... 24 V DC/48 V DC/60 V DC/110 V DC/ 220 V DC 3 poles in series ... 24 V DC/48 V DC/60 V DC/110 V DC/ 220 V DC 4 poles in series ... 24 V DC/48 V DC/60 V DC/110 V DC/ 220 V DC	I _e	A	20/10/4/1.3/0.2		15/8/4/1.3/0.2		20/10/4/1.3/0.2	
			32/18/12/5.5/0.6		25/16/12/5.5/0.6		32/18/12/5.5/0.6	
					25/25/25/15/3		32/32/25/15/3	
					25/25/25/20/8		32/32/25/20/8	
Maximum operating frequency for DC-3		op. c./h	300					
Electrical endurance for DC-3		op. c.	100.000					
Rated operational current for DC-5 (L/R ≤ 7.5 ms): 1 pole ... 24 V DC/48 V DC/60 V DC/110 V DC/ 220 V DC 2 poles in series ... 24 V DC/48 V DC/60 V DC/110 V DC/ 220 V DC 3 poles in series ... 24 V DC/48 V DC/60 V DC/110 V DC/ 220 V DC 4 poles in series ... 24 V DC/48 V DC/60 V DC/110 V DC/ 220 V DC	I _e	A	18/6/3/0.5/0.1		15/5/3/0.5/0.1		18/6/3/0.5/0.1	
			32/16/10/4/0.4		25/15/10/4/0.4		32/16/10/4/0.4	
					25/25/20/12/2		32/28/20/12/2	
					25/25/25/15/5		32/32/25/15/5	
Maximum operating frequency for DC-5		op. c./h	300					
Electrical endurance for DC-5		op. c.	100.000					
Terminal capacity: rigid (solid and stranded)	S	mm ²	1 ... 10					
flexible			1 ... 6					
Length of removed wire insulation		mm	9					
Screw			M3.5					
Screw head			PZ1					
Tightening torque		Nm	1.2					
Contact reliability			≥17 V; ≥50 mA					
Minimum distance of open contacts		mm	3.6					
Power dissipation per pole		W	2.5	2.5	2.2	2.2	2.5	2.5
Overload current withstand capability: 10 s		A	72		68			
Maximum back-up fuse for short-circuit protection gL and gG: coordination type 1 coordination type 2	I _v	A	32	32	25	25	32	32
Rated insulation voltage	U _i	V	440					
Rated impulse withstand voltage	U _{imp}	kV	4					
Rated operational voltage	U _e	V	230/400					
Rated frequency	f	Hz	50/60					
Thermal current	I _{th}	A	32		25		32	
Rated operational current for AC-15: single-phase 230 V single-phase 400 V	I _e	A	6					
			4					
Maximum operating frequency for AC-15		op. c./h	600					
Electrical endurance for AC-15		op. c.	300.000		500.000			
Rated operational current for DC-13: 1 pole ... 24 V DC/48 V DC/60 V DC/110 V DC/ 220 V DC 2 poles in series ... 24 V DC/48 V DC/60 V DC/110 V DC/ 220 V DC 3 poles in series ... 24 V DC/48 V DC/60 V DC/110 V DC/ 220 V DC 4 poles in series ... 24 V DC/48 V DC/60 V DC/110 V DC/ 220 V DC	I _e	A	6/4/1/0.3/0.05					
			6/6/4/1/0.1					
			6/6/6/3/1					
			6/6/6/4/2					

TECHNICAL DATA

AUXILIARY CIRCUIT	Type	Symbol	Unit	IKA232 IKA232-R IKA232-T	IKD232 IKD232-R IKD232-T	IKA25 IKA25-R IKA25-T	IKD25 IKD25-R IKD25-T	IKA432 IKA432-R IKA432-T	IKD432 IKD432-R IKD432-T
	Maximum operating frequency for DC-13		op. c./h	300					
	Electrical endurance for DC-13		op. c.	200.000					
	Terminal capacity: rigid (solid and stranded) flexible	S	mm ²	1 ... 10 1 ... 6					
	Length of removed wire insulation		mm	9					
	Screw			M3.5					
	Screw head		mm	PZ1					
	Tightening torque			1.2					
	COIL	Range of control voltage for switch-on	U _c	%	85 ... 110				
Range of control voltage for drop out		U _c	%	AC: 75 ... 20 / DC: 75 ... 10 (where is applicable)					
Kind of voltage				AC	AC/DC	AC	AC/DC	AC	AC/DC
Standard control voltages		U _c	V	12, 24, 48, 120, 230		12, 24, 48 120, 230, 400	12, 24, 48 120, 230	12, 24, 48, 120, 230, 400	12, 24, 48, 120, 230
Frequency of AC control voltage		f	Hz	50/60	40 ... 500	50/60	40 ... 500	50/60	40 ... 500
Control mode				remote control with U _c / manual control only for types with -R and -T					
Impulse duration of control voltage: minimum maximum				permanent permanent					
Minimum duration between two impulses of control voltage			ms	AC: 150 / DC: 500 (where is applicable)					
Surge immunity withstand voltage 1,2/50 μs acc. to standard IEC/EN 61000-4-5			kV	2					
Coil consumption: switch-on operation			VA/W	12/10 2.8/1.2	2.1/2.1 2.1/2.1	33/25 5.5/1.6	2.6/2.6 ¹⁾ 2.6/2.6 ¹⁾	33/25 5.5/1.6	2.6/2.6 ¹⁾ 2.6/2.6 ¹⁾
Delays: make brake			ms	15 ... 25 10 ... 30	15 ... 45 20 ... 50	10 ... 30 10 ... 30	15 ... 45 20 ... 70	10 ... 30 10 ... 30	15 ... 45 20 ... 70
Terminal capacity: rigid (solid and stranded) flexible			mm ²	1 ... 2.5 1 ... 2.5					
Length of removed wire insulation			mm	7					
Screw				M3					
Screw head				PZ1					
Tightening torque			Nm	0.6					
SAFETY	MTTF - Mean time to failure MTTF = 1/λ = B10/(0.1 n _{op})		h	AC-1: 3.750 AC-3: 7.500		AC-1: 5.000 AC-3: 12.500		AC-1: 3.750 AC-3: 16.666	
	MTTF _d - Mean time to failure dangerous MTTF _d = 1/λ _d = B10 _d /(0.1 n _{op})		h	AC-1: 5.000 AC-3: 10.000		AC-1: 6.666 AC-3: 16.666		AC-1: 5.000 AC-3: 112.500	
	B10 - Number of operating cycles until 10 % of devices fail		op. c.	AC-1: 112.500 for NO AC-3: 225.000		AC-1: 150.000 AC-3: 375.000		AC-1: 112.500 AC-3: 375.000	
	B10 _d - Number of operating cycles until 10 % of device dangerous B10 _d = B10/ratio of dangerous failures		op. c.	AC-1: 150.000 for NO AC-3: 300.000		AC-1: 200.000 AC-3: 500.000		AC-1: 150.000 AC-3: 500.000	
	λ - Failure rate λ = (0.1 n _{op})/B10		1/h	AC-1: 0.000266 for NO AC-3: 0.000133		AC-1: 0.0002 AC-3: 0.00008		AC-1: 0.000266 AC-3: 0.00008	
	λ _d - Failure rate dangerous λ _d = (0.1 n _{op})/B10 _d		1/h	AC-1: 0.0002 for NO AC-3: 0.0001		AC-1: 0.00015 AC-3: 0.00006		AC-1: 0.0002 AC-3: 0.00006	
	Ratio of dangerous failures		%	75					
	n _{op} - Operating cycles (operating cycles/h)		op. c./h	300					

¹⁾ Coil consumption for version -04 is 3.8 VA/3.8 W

Installation Contactors

up to 63 A



TECHNICAL DATA

GENERAL	Type	Symbol	Unit	IKA40	IK40	IKA63	IK63
	Standards			IEC/EN 61095, IEC/EN 60947-4-1, IEC/EN 60947-5-1			
	Approvals			CE, CB, NF, EAC			
	Module width			3			
	Number of poles			4			
	Degree of protection			IP20 (IP40 when installed in installation box - distribution board)			
	Pollution degree			3			
	Climatic conditions			95 % relative humidity			
	Ambient temperature (open)		°C	-15 ... +55 ³⁾			
	Storage temperature		°C	-30... +80			
	Maximum altitude		m	2000			
	U _i and U _e is reduced for 1.2 % and I _e for 0.4 % for every additional 100 m						
	Number of contactors or switches side-by-side:						
	≤40 °C			no limitation	max. 3	no limitation	max. 3
	(40 ... 55) °C			no limitation	max. 2	no limitation	max. 2
Noise level (operation)		dB	30	20	30	20	
Vibration resistance according to IEC/EN 60068-2-6	a	g	switched off: 2 (Z and X axis) / switched on: 3 (Z axis) and 1 (X axis)				
Shock resistance according to IEC/EN 6068-2-27	a	g	switched off: 10 (Z and X axis) / switched on: 15 (Z axis) and 2 (X axis)				
Maximum operating frequency with no load		op. c./h	3.000				
Mechanical endurance		op. c.	3.000.000	10.000.000	3.000.000	10.000.000	
Weight		g	350	420	350	420	
MAIN CIRCUIT	Contact reliability			≥17 V; ≥50 mA			
	Minimum distance of open contacts		mm	3.6			
	Power dissipation per pole		W	4	4	8	8
	Overload current withstand capability: 10 s		A	176		240	
	Maximum back-up fuse for short-circuit protection gL and gG: coordination type 1	I _v	A	63	63	80	80
	coordination type 2			40	40	63	63
	Rated insulation voltage	U _i	V	440			
	Rated impulse withstand voltage	U _{imp}	kV	6			
	Rated operational voltage	U _e	V	400			
	Rated frequency	f	Hz	50/60			
	Thermal current	I _{th}	A	40		63	
	Rated operational current for AC-1, AC-7a and AC-21	I _e	A	40		63 ¹⁾	
	Operational power for AC-1, AC-7a and AC-21: single-phase 230 V	P _e	kW	8.7		13.3 ²⁾	
	three-phase 230 V			16		24 ²⁾	
	three-phase 400 V			26		40 ²⁾	
	Maximum operating frequency for AC-1, AC-7a and AC-21		op. c./h	600			
	Electrical endurance for AC-1, AC-7a and AC-21		op. c.	100.000			
	Rated operational current for AC-2	I _e	A	25		32	
	Operational power for AC-2: single-phase 230 V	P _e	kW	3.7		4.8	
	three-phase 230 V			6.5		8.3	
	three-phase 400 V			11.2		14.4	
	Maximum operating frequency for AC-2		op. c./h	120			
	Electrical endurance for AC-2		op. c.	50.000			
	Rated operational current for AC-22	I _e	A	40		63	
	Operational power for AC-22: single-phase 230 V	P _e	kW	7.4		11.6	
	three-phase 230 V			12.7		20.1	
	three-phase 400 V			22.2		34.9	
Maximum operating frequency for AC-22		op. c./h	300				
Electrical endurance for AC-22		op. c.	50.000				
Rated operational current for AC-3, AC-7b and AC-23	I _e	A	22		30		
Operational power for AC-3, AC-7b and AC-23: single-phase 230 V	P _e	kW	3.7		5		
three-phase 230 V			5.5		8.5		
three-phase 400 V			11		15		
Maximum operating frequency for AC-3, AC-7b and AC-23		op. c./h	600				
Electrical endurance for AC-3, AC-7b and AC-23		op. c.	150.000				

¹⁾ I_e (AC-1) for IK63-04 is 50 A

²⁾ Rated power (AC-1) for IK63-04:
single-phase 230 V = 10.9 kW
three-phase 230 V = 18.9 kW
three-phase 400 V = 32.9 kW

³⁾) Ambient temperature (open) -25...+55 °C for version with 4NO contacts

TECHNICAL DATA

MAIN CIRCUIT	Type	Symbol	Unit	IKA40	IK40	IKA63	IK63
	Rated operational current for AC-5a (at 230 V)	I _e	A	20		32	
	Maximum operating frequency for AC-5a		op. c./h	600			
	Electrical endurance for AC-5a		op. c.	100.000			
	Rated operational current for AC-5b (at 230 V)	I _e	A	17.6		22	
	Maximum operating frequency for AC-5b		op. c./h	600			
	Electrical endurance for AC-5b		op. c.	100.000			
	Rated operational current for AC-6a (at 230 V)	I _e	A	10.8		17.2	
	Maximum operating frequency for AC-6a		op. c./h	600			
	Electrical endurance for AC-6a		op. c.	100.000			
	Switching of capacitors AC-6b and AC-7c (at 230 V)	C	µF	220		330	
	Maximum operating frequency for AC-6b and AC-7c		op. c./h	600			
	Electrical endurance for AC-6b and AC-7c		op. c.	100.000			
	Rated operational current for DC-1 (L/R ≤ 1 ms): 1 pole ... 24 V DC/48 V DC/60 V DC/110 V DC/ 220 V DC 2 poles in series ... 24 V DC/48 V DC/60 V DC/110 V DC/ 220 V DC 3 poles in series ... 24 V DC/48 V DC/60 V DC/110 V DC/ 220 V DC 4 poles in series ... 24 V DC/48 V DC/60 V DC/110 V DC/ 220 V DC	I _e	A	40/25/18/4/1.2		63/26/20/4/1.2	
	40/38/32/10/8			63/42/34/10/8			
	40/40/40/30/20			63/63/60/35/30			
	40/40/40/40/40			63/63/63/63/63			
	Maximum operating frequency for DC-1		op. c./h	300			
	Electrical endurance for DC-1		op. c.	100.000			
	Rated operational current for DC-3 (L/R ≤ 2 ms): 1 pole ... 24 V DC/48 V DC/60 V DC/110 V DC/ 220 V DC 2 poles in series ... 24 V DC/48 V DC/60 V DC/110 V DC/ 220 V DC 3 poles in series ... 24 V DC/48 V DC/60 V DC/110 V DC/ 220 V DC 4 poles in series ... 24 V DC/48 V DC/60 V DC/110 V DC/ 220 V DC	I _e	A	22/10/5/1.5/0.3		25/11/5/1.5/0.3	
	40/20/16/5/1			45/22/18/5/1			
	40/40/32/15/4			63/45/35/18/5			
	40/40/40/40/10			63/63/63/63/10			
	Maximum operating frequency for DC-3		op. c./h	300			
	Electrical endurance for DC-3		op. c.	100.000			
	Rated operational current for DC-5 (L/R ≤ 7.5 ms): 1 pole ... 24 V DC/48 V DC/60 V DC/110 V DC/ 220 V DC 2 poles in series ... 24 V DC/48 V DC/60 V DC/110 V DC/ 220 V DC 3 poles in series ... 24 V DC/48 V DC/60 V DC/110 V DC/ 220 V DC 4 poles in series ... 24 V DC/48 V DC/60 V DC/110 V DC/ 220 V DC	I _e	A	20/8/4/1/0.2		25/10/5/1/0.2	
	40/18/14/5/0.8			45/20/15/5/0.8			
	40/40/28/12/3			63/44/30/15/4			
	40/40/40/35/8			63/63/60/45/10			
	Maximum operating frequency for DC-5		op. c./h	300			
	Electrical endurance for DC-5		op. c.	100.000			
	Terminal capacity: rigid (solid and stranded) flexible	S	mm ²	1.5 ... 25			
				1.5 ... 16			
	Length of removed wire insulation		mm	10			
	Screw			M5			
	Screw head			PZ2			
Tightening torque		Nm	3.5				
Contact reliability			≥17 V; ≥50 mA				
Minimum distance of open contacts		mm	3.6				
Power dissipation per pole		W	4	4	8	8	
Overload current withstand capability: 10 s		A	176		240		
Maximum back-up fuse for short-circuit protection gL and gG: coordination type 1 coordination type 2	I _v	A	63	63	80	80	
			40	40	63	63	
Rated insulation voltage	U _i	V	440				
Rated impulse withstand voltage	U _{imp}	kV	4				
Rated operational voltage	U _e	V	230/400				
Rated frequency	f	Hz	50/60				
Thermal current	I _{th}	A	40		63		
Rated operational current for AC-15: single-phase 230 V single-phase 400 V	I _e	A	6				
			4				
Maximum operating frequency for AC-15		op. c./h	1.200				
Electrical endurance for AC-15		op. c.	150.000				
Rated operational current for DC-13: 1 pole ... 24 V DC/48 V DC/60 V DC/110 V DC/ 220 V DC 2 poles in series ... 24 V DC/48 V DC/60 V DC/110 V DC/ 220 V DC 3 poles in series ... 24 V DC/48 V DC/60 V DC/110 V DC/ 220 V DC 4 poles in series ... 24 V DC/48 V DC/60 V DC/110 V DC/ 220 V DC	I _e	A	6/4/1/0.3/0.05				
			6/6/4/1/0.1				
			6/6/6/3/1				
			6/6/6/4/2				

Installation Contactors

up to 63 A



TECHNICAL DATA

	Type	Symbol	Unit	IKA40	IK40	IKA63	IK63
AUXILIARY CIRCUIT	Maximum operating frequency for DC-13		op. c./h	300			
	Electrical endurance for DC-13		op. c.	200.000			
	Terminal capacity:	S	mm ²	1.5 ... 25			
	rigid (solid and stranded)			1.5 ... 16			
	flexible			10			
	Length of removed wire insulation		mm	M5			
	Screw			PZ2			
	Screw head		mm	3.5			
COIL	Tightening torque			85 ... 110			
	Range of control voltage for switch-on	U _c	%	AC: 75 ... 20 / DC: 75 ... 10 (where is applicable)			
	Range of control voltage for drop out	U _c	%				
	Kind of voltage			AC	AC/DC	AC	AC/DC
	Standard control voltages	U _c	V	12, 24, 48, 120, 230, 400	12, 24, 48, 120, 230	12, 24, 48, 120, 230, 400	12, 24, 48, 120, 230
	Frequency of AC control voltage	f	Hz	50/60	40 ... 500	50/60	40 ... 500
	Control mode			remote control with U _c / manual control only for types with -R			
	Impulse duration of control voltage:			permanent			
	minimum			permanent			
	maximum			AC: 150 / DC: 500 (where is applicable)			
	Minimum duration between two impulses of control voltage		ms	2			
	Surge immunity withstand voltage 1.2/50 µs acc. to standard IEC/EN 61000-4-5		kV				
	Coil consumption:						
	switch-on		VA/W	15.4/6	5/5 ¹⁾	15.4/6	5/5 ¹⁾
	operation			7.7/3	5/5 ¹⁾	7.7/3	5/5 ¹⁾
	Delays:						
	make		ms	10 ... 20	15 ... 20	10 ... 20	15 ... 20
	break			10 ... 15	35 ... 45	10 ... 15	35 ... 45
	Terminal capacity:						
	rigid (solid and stranded)		mm ²	1 ... 2.5			
	flexible			1 ... 2.5			
SAFETY	Length of removed wire insulation		mm	8			
	Screw			M3			
	Screw head			PZ1			
	Tightening torque		Nm	0.6			
	MTTF - Mean time to failure			AC-1: 2.500			
	MTTF = 1/λ = B10/(0.1 n _{op})		h	AC-3: 3.750			
	MTTF _d - Mean time to failure dangerous			AC-1: 3.333			
	MTTF _d = 1/λ _d = B10 _d /(0.1 n _{op})		h	AC-3: 5.000			
	B10 - Number of operating cycles until 10 % of devices fail		op. c.	AC-1: 75.000			
				AC-3: 112.500			
	B10 _d - Number of operating cycles until 10 % of device dangerous		op. c.	AC-1: 100.000			
	B10 _d = B10/ratio of dangerous failures			AC-3: 150.000			
	λ - Failure rate			AC-1: 0.0004			
	λ = (0.1 n _{op})/B10		1/h	AC-3: 0.000266			
	λ _d - Failure rate dangerous			AC-1: 0.0003			
	λ _d = (0.1 n _{op})/B10 _d		1/h	AC-3: 0.0002			
	Ratio of dangerous failures		%	75			
	n _{op} - Operating cycles (operating cycles/h)		op. c./h	300			

¹⁾ Coil consumption for version -22 and -04 is 6.1 VA/6.1 W

TECHNICAL DATA

GENERAL	Type	Symbol	Unit	IKA220	IKD220	IKA425	IKD425
	Standards			UL 60947-4-1A, C22.2 No. 60947-4-1A-07, IEC/EN 61095, IEC/EN 60947-4-1			
	Approvals			CE, UL, CSA			
	Module width			1		2	
	Number of poles			2		4	
	Degree of protection			IP20 (IP40 when installed in installation box - distribution board)			
	Pollution degree			3			
	Ambient temperature (closed)			5 °F ... 104 °F / -5 °C ... +40 °C ⁵⁾			
	Storage temperature			-22 °F ... 176 °F / -30 °C ... +80 °C			
	Maximum altitude		m	2000			
	U _i and U _e is reduced for 1.2 % and I _e for 0.4 % for every additional 100 m						
	Number of contactors or switches side-by-side: ≤40 °C			no limitation			
	(40 ... 55) °C						
	Noise level (operation)		dB	30	20	30	20
	Vibration resistance according to IEC/EN 60068-2-6	a	g	switched off: 2 (Z and X axis) / switched on: 3 (Z axis) and 1 (X axis)			
	Shock resistance according to IEC/EN 6068-2-27	a	g	switched off: 10 (Z and X axis) / switched on: 15 (Z axis) and 2 (X axis)			
Maximum operating frequency with no load		op. c./h	3.000				
Mechanical endurance		op. c.	3.000.000	10.000.000	3.000.000	10.000.000	
Weight		g	130	130	230	250	
MAIN CIRCUIT	Contact reliability			≥17 V; ≥50 mA			
	Minimum distance of open contacts			0.118 in / 3.6 mm			
	Power dissipation per pole		W	1.7	1.7	2	2
	Overload current withstand capability: 10 s		A	72		68	
	Maximum back-up fuse for short-circuit protection gL and gG: coordination type 1	I _v	A			25	25
	coordination type 2			20	20		
	Maximum back-up fuse for short-circuit protection KS acc. to UL and CSA	I _v	A	20	20	25	25
	Rated insulation voltage	U _i	V	440			
	Rated impulse withstand voltage	U _{imp}	kV	4			
	Rated operational voltage	U _e	V	440 ^{1) 2)} 240 ³⁾		400/480 ⁴⁾	
	Rated frequency	f	Hz	50/60			
	Thermal current	I _{th}	A	20		25	
	Rated operational current for AC-1, AC-7a and AC-21	I _e	A	20		20	
	Operational power for AC-1, AC-7a and AC-21: single-phase 230 V	P _e	kW	4		5.4	
	three-phase 230 V					9	
	three-phase 400 V					16	
	Maximum operating frequency for AC-1, AC-7a and AC-21		op. c./h	600			
	Electrical endurance for AC-1, AC-7a and AC-21		op. c.	200.000			
	Rated operational current for AC-2	I _e	A	12		14	
	Operational power for AC-2: single-phase 230 V	P _e	kW	1.8		2	
	three-phase 230 V					3.6	
	three-phase 400 V					6	
	Maximum operating frequency for AC-2		op. c./h	120			
	Electrical endurance for AC-2		op. c.	100.000			
	Rated operational current for AC-22	I _e	A	20		25	
	Operational power for AC-22: single-phase 230 V	P _e	kW	3.7		4.6	
	three-phase 230 V					8	
	three-phase 400 V					13.8	
	Maximum operating frequency for AC-22		op. c./h	300			
	Electrical endurance for AC-22		op. c.	50.000			
	Rated operational current for AC-3, AC-7b and AC-23	I _e	A	NO: 9 / NC: 6		8.5	
	Operational power for AC-3, AC-7b and AC-23: single-phase 230 V	P _e	kW	NO: 1.3 / NC: 0.75		1.3	
three-phase 230 V					2.2		
three-phase 400 V					4		
Maximum operating frequency for AC-3, AC-7b and AC-23		op. c./h	600				
Electrical endurance for AC-3, AC-7b and AC-23		op. c.	300.000		500.000		

¹⁾ Rated operational voltage between two line (phase) conductors

²⁾ Rated operational voltage for versions of contacts -10 and -01 is 230 V

³⁾ Rated voltage 240 V valid in acc. to UL and CSA

⁴⁾ Rated voltage 480 V valid in acc. to UL and CSA

⁵⁾ Ambient temperature (open) -13 ... 104 °F / -25 ... +40 °C for version with 2NO and 4NO contacts

Installation Contactors UL/CSA

up to 25 A



TECHNICAL DATA

Type	Symbol	Unit	IKA220	IKD220	IKA425	IKD425
Rated motor power acc. to standards UL and CSA:	P _e	HP	1/3	1/3	1/3	1/3
single-phase 120 V			3/4	3/4	3/4	3/4
single-phase 208 V			1	1	1	1
single-phase 240 V					1	1
three-phase 120 V					2	2
three-phase 208 V					3	3
three-phase 240 V					5	5
three-phase 460 V						
Maximum operating frequency for motors acc. to UL and CSA		op. c./h	360			
Electrical endurance for motors according to UL and CSA		op. c.	300.000		500.000	
General use according to standards UL and CSA:	I _e	A	20	20		
single-phase 240 V					25	25
three-phase 480 V						
Maximum operating frequency for general use acc. to UL and CSA		op. c./h	360			
Electrical endurance for general use acc. to UL and CSA		op. c.	200.000			
Switching of discharge lamps acc. to standards UL and CSA:	I _e	A	20	20		
single-phase 240 V - standard ballast					25	25
three-phase 480 V - standard ballast						
Maximum operating frequency for discharge lamps acc. to UL and CSA		op. c./h	360			
Electrical endurance for discharge lamps acc. to UL and CSA		op. c.	100.000			
Rated operational current for AC-5a (at 230 V)	I _e	A	8.8		11.2	
Maximum operating frequency for AC-5a		op. c./h	600			
Electrical endurance for AC-5a		op. c.	100.000			
Rated operational current for AC-5b (at 230 V)	I _e	A	8.8		9.7	
Maximum operating frequency for AC-5b		op. c./h	600			
Electrical endurance for AC-5b		op. c.	100.000			
Rated operational current for AC-6a (at 230 V)	I _e	A	4		4.8	
Maximum operating frequency for AC-6a		op. c./h	600			
Electrical endurance for AC-6a		op. c.	100.000			
Switching of capacitors AC-6b and AC-7c (at 230 V)	C	µF	30		36	
Maximum operating frequency for AC-6b and AC-7c		op. c./h	600			
Electrical endurance for AC-6b and AC-7c		op. c.	100.000			
Rated operational current for DC-1 (L/R ≤ 1 ms):	I _e	A	20/15/10/6/0.6		25/20/15/6/0.6	
1 pole ... 24 V DC/48 V DC/60 V DC/110 V DC/ 220 V DC			25/18/15/10/6		25/25/20/10/6	
2 poles in series ... 24 V DC/48 V DC/60 V DC/110 V DC/ 220 V DC					25/25/25/20/15	
3 poles in series ... 24 V DC/48 V DC/60 V DC/110 V DC/ 220 V DC					25/25/25/20/15	
4 poles in series ... 24 V DC/48 V DC/60 V DC/110 V DC/ 220 V DC						
Maximum operating frequency for DC-1		op. c./h	300			
Electrical endurance for DC-1		op. c.	100.000			
Rated operational current for DC-3 (L/R ≤ 2 ms):	I _e	A	10/5/2/1/0.1		15/8/4/1.3/0.2	
1 pole ... 24 V DC/48 V DC/60 V DC/110 V DC/ 220 V DC			20/10/8/4/0.4		25/10/8/4/0.4	
2 poles in series ... 24 V DC/48 V DC/60 V DC/110 V DC/ 220 V DC					25/25/25/15/3	
3 poles in series ... 24 V DC/48 V DC/60 V DC/110 V DC/ 220 V DC					25/25/25/20/8	
4 poles in series ... 24 V DC/48 V DC/60 V DC/110 V DC/ 220 V DC						
Maximum operating frequency for DC-3		op. c./h	300			
Electrical endurance for DC-3		op. c.	100.000			
Rated operational current for DC-5 (L/R ≤ 7.5 ms):	I _e	A	10/4/1/0.3/0.06		15/5/3/0.5/0.1	
1 pole ... 24 V DC/48 V DC/60 V DC/110 V DC/ 220 V DC			20/8/6/2/0.2		25/15/10/4/0.4	
2 poles in series ... 24 V DC/48 V DC/60 V DC/110 V DC/ 220 V DC					25/25/20/12/2	
3 poles in series ... 24 V DC/48 V DC/60 V DC/110 V DC/ 220 V DC					25/25/25/15/5	
4 poles in series ... 24 V DC/48 V DC/60 V DC/110 V DC/ 220 V DC						
Maximum operating frequency for DC-5		op. c./h	300			
Electrical endurance for DC-5		op. c.	100.000			
Terminal capacity:	S		16 ... 10 AWG / 1 ... 10 mm ²			
rigid (solid and stranded)			16 ... 8 AWG / 1 ... 6 mm ²			
flexible			0.354 in / 9 mm			
Length of removed wire insulation			M3.5			
Screw			PZ1			
Screw head			10.62 lb-in / 1.2 Nm			
Tightening torque			≥17 V; ≥50 mA			
Contact reliability			0.118 in / 3.6 mm			
Minimum distance of open contacts						
Power dissipation per pole		W	1.7		2.2	
Overload current withstand capability:						
10 s			72		68	
Maximum back-up fuse for short-circuit protection gL and gG:	I _v	A				
coordination type 1					25	
coordination type 2			20			

TECHNICAL DATA

AUXILIARY CIRCUIT	Type	Symbol	Unit	IKA220	IKD220	IKA425	IKD425	
	Maximum back-up fuse for short-circuit protection K5 acc. to UL and CSA	U_i	V	20	20	25	25	
	Rated insulation voltage	U_i	V	440				
	Rated impulse withstand voltage	U_{imp}	kV	4				
	Rated operational voltage	U_e	V	230/400				
	Rated frequency	f	Hz	50/60				
	Thermal current	I_{th}	A	20		25		
	Rated operational current for AC-15: single-phase 230 V single-phase 400 V	I_e	A	6 4				
	Maximum operating frequency for AC-15		op. c./h	600				
	Electrical endurance for AC-15		op. c.	300.000		500.000		
	Switching of auxiliary loads according to standard UL and CSA			B300, P300				
	Maximum operating frequency for auxiliary loads according to UL and CSA		op. c./h	360				
	Electrical endurance for auxiliary loads according to UL and CSA		op. c.	100.000				
	Rated operational current for DC-13: 1 pole ... 24 V DC/48 V DC/60 V DC/110 V DC/ 220 V DC 2 poles in series ... 24 V DC/48 V DC/60 V DC/110 V DC/ 220 V DC 3 poles in series ... 24 V DC/48 V DC/60 V DC/110 V DC/ 220 V DC 4 poles in series ... 24 V DC/48 V DC/60 V DC/110 V DC/ 220 V DC	I_e	A	6/4/1/0.3/0.05 6/6/4/1/0.1 6/6/6/3/1 6/6/6/4/2				
	Maximum operating frequency for DC-13		op. c./h	300				
	Electrical endurance for DC-13		op. c.	200.000				
	Terminal capacity: rigid (solid and stranded) flexible	S		16...10 AWG / 1...10 mm ² 16... 8 AWG / 1...6 mm ²				
	Length of removed wire insulation			0.354 in / 9 mm				
	Screw			M3.5				
	Screw head			PZ1				
	Tightening torque			10.62 lb-in / 1.2 Nm				
	COIL	Range of control voltage for switch-on	U_c	%	85 ... 110			
		Range of control voltage for drop out	U_c	%	AC: 75 ... 20 / DC: 75 ... 10 (where is applicable)			
		Kind of voltage			AC	AC/DC	AC	AC/DC
Standard control voltages		U_c	V	12, 24, 48, 110, 120, 127, 208, 230, 240				
Frequency of AC control voltage		f	Hz	50/60				
Control mode				remote control with U_c				
Impulse duration of control voltage: minimum maximum				permanent permanent				
Minimum duration between two impulses of control voltage			ms	AC: 150 / DC: 500 (where is applicable)				
Surge immunity withstand voltage 1.2/50 μs acc. to standard IEC/EN 61000-4-5			kV	2				
Coil consumption: switch-on operation			VA/W	12/10 2.8/1.2	2.1/2.1 2.1/2.1	33/25 5.5/1.6	2.6/2.6 ¹⁾ 2.6/2.6 ¹⁾	
Delays: make brake			ms	15 ... 25 10 ... 30	15 ... 45 20 ... 50	10 ... 30 10 ... 30	15 ... 45 20 ... 70	
Terminal capacity: rigid (solid and stranded) flexible				16 ... 14 AWG / 1 ... 2.5 mm ² 16 ... 14 AWG / 1 ... 2.5 mm ²				
Length of removed wire insulation				0.276 in / 7 mm				
Screw				M3				
Screw head				PZ1				
Tightening torque				5.31 lb-in / 0.6 Nm				
SAFETY		MTTF - Mean time to failure MTTF = 1/λ = B10/(0.1 n _{op})		h	General Use: 4.166 Motor: 6.250 Motor: 10.416			
		MTTF _d - Mean time to failure dangerous MTTF _d = 1/λ _d = B10 _d /(0.1 n _{op})		h	General Use: 5.555 Motor: 8.333 Motor: 13.888			
		B10 - Number of operating cycles until 10 % of devices fail		op. c.	General Use: 150.000 Motor: 225.000 Motor: 375.000			
		B10 _d - Number of operating cycles until 10 % of device dangerous B10 _d = B10/ratio of dangerous failures		op. c.	General Use: 200.000 Motor: 300.000 Motor: 500.000			
		λ - Failure rate λ = (0.1 n _{op})/B10		1/h	General Use: 0.00024 Motor: 0.00016 Motor: 0.000096			
		λ _d - Failure rate dangerous λ _d = (0.1 n _{op})/B10 _d		1/h	General Use: 0.00018 Motor: 0.00012 Motor: 0.000072			
	Ratio of dangerous failures		%	75				
	n _{op} - Operating cycles (operating cycles/h)		op. c./h	360				

¹⁾ Coil consumption for contact version -04 is 3.8 VA / 3.8 W

Installation Contactors UL/CSA

up to 63 A



TECHNICAL DATA

GENERAL	Type	Symbol	Unit	IKA440	IKD440	IKA463	IKD463
	Standards			UL 60947-4-1A, C22.2 No. 60947-4-1A-07, IEC/EN 61095, IEC/EN 60947-4-1			
	Approvals			CE, UL, CSA			
	Module width			3			
	Number of poles			4			
	Degree of protection			IP20 (IP40 when installed in installation box - distribution board)			
	Pollution degree			3			
	Ambient temperature (open)			1) -22 °F ... 176 °F / -30 °C ... +80 °C			2)
	Storage temperature			-22 °F ... 176 °F / -30 °C ... +80 °C			
	Maximum altitude		m	2000			
	U _i and U _e is reduced for 1.2 % and I _e for 0.4 % for every additional 100 m						
	Number of contactors or switches side-by-side:			no limit	max. 3	no limit	max. 3
	≤40 °C						
	(40 ... 55) °C						
	Noise level (operation)		dB	30	20	30	20
	Vibration resistance according to IEC/EN 60068-2-6	a	g	switched off: 2 (Z and X axis) / switched on: 3 (Z axis) and 1 (X axis)			
Shock resistance according to IEC/EN 6068-2-27	a	g	switched off: 10 (Z and X axis) / switched on: 15 (Z axis) and 2 (X axis)				
Maximum operating frequency with no load		op. c./h	3.000				
Mechanical endurance		op. c.	3.000.000	10.000.000	3.000.000	10.000.000	
Weight		g	350	420	350	420	
MAIN CIRCUIT	Contact reliability			≥17 V; ≥50 mA			
	Minimum distance of open contacts			0.118 in / 3.6 mm			
	Power dissipation per pole		W	4	4	8	8
	Overload current withstand capability: 10 s		A	176		240	
	Maximum back-up fuse for short-circuit protection gL and gG: coordination type 1	I _v	A	63	63	80	80
	coordination type 2			40	40	63	63
	Maximum back-up fuse for short-circuit protection KS acc. to UL and CSA	I _v	A	60	60	70	70
	Rated insulation voltage	U _i	V	440			
	Rated impulse withstand voltage	U _{imp}	kV	4			
	Rated operational voltage	U _e	V	400/480 ³⁾			
	Rated frequency	f	Hz	50/60			
	Thermal current	I _{th}	A	40		63	
	Rated operational current for AC-1, AC-7a and AC-21	I _e	A	40		63	
	Operational power for AC-1, AC-7a and AC-21: single-phase 230 V	P _e	kW	8.7		13.3	
	three-phase 230 V			16		24	
	three-phase 400 V			26		40	
	Maximum operating frequency for AC-1, AC-7a and AC-21		op. c./h	600			
	Electrical endurance for AC-1, AC-7a and AC-21		op. c.	100.000			
	Rated operational current for AC-2	I _e	A	25		32	
	Operational power for AC-2: single-phase 230 V	P _e	kW	3.7		4.8	
	three-phase 230 V			6.5		8.3	
	three-phase 400 V			11.2		14.4	
	Maximum operating frequency for AC-2		op. c./h	120			
	Electrical endurance for AC-2		op. c.	50.000			
	Rated operational current for AC-22	I _e	A	40		63	
	Operational power for AC-22: single-phase 230 V	P _e	kW	7.4		11.6	
	three-phase 230 V			12.7		20.1	
	three-phase 400 V			22.2		34.9	
	Maximum operating frequency for AC-22		op. c./h	300			
	Electrical endurance for AC-22		op. c.	50.000			
	Rated operational current for AC-3, AC-7b and AC-23	I _e	A	22		30	
	Operational power for AC-3, AC-7b and AC-23: single-phase 230 V	P _e	kW	3.7		5	
	three-phase 230 V			5.5		8.5	
	three-phase 400 V			11		15	
Maximum operating frequency for AC-3, AC-7b and AC-23		op. c./h	600				
Electrical endurance for AC-3, AC-7b and AC-23		op. c.	150.000				

¹⁾ Surrounding air temperature for 4NO contacts version -13 °F...104 °F / -25 °C ... 40 °C, for others contacts version 5 °F ... 104 °F / -15 °C ... +40 °C

²⁾ Surrounding air temperature for 4NO contacts version -13 °F...95 °F / -25 °C ... 35 °C, for others contacts version 5 °F ... 95 °F / -15 °C ... +35 °C

³⁾ Rated voltage 480 V valid only for UL and CSA

TECHNICAL DATA

Type	Symbol	Unit	IKA440	IKD440	IKA463	IKD463
Rated motor power acc. to standards UL and CSA:	P _e	HP				
single-phase 120 V			1	1	2	2
single-phase 208 V			2	2	3	3
single-phase 240 V			3	3	5	5
three-phase 120 V			3	3	5	5
three-phase 208 V			7 1/2	7 1/2	10	10
three-phase 240 V			7 1/2	7 1/2	10	10
three-phase 460 V			15	15	20	20
Maximum operating frequency for motors acc. to UL and CSA		op. c./h	360			
Electrical endurance for motors according to UL and CSA		op. c.	150.000			
General use according to standards UL and CSA:	I _e	A				
single-phase 240 V						
three-phase 480 V			40	40	63	63
Maximum operating frequency for general use acc. to UL and CSA		op. c./h	360			
Electrical endurance for general use acc. to UL and CSA		op. c.	100.000			
Switching of discharge lamps acc. to standards UL and CSA:	I _e	A				
single-phase 240 V - standard ballast						
three-phase 480 V - standard ballast			30	30	40	40
Maximum operating frequency for discharge lamps acc. to UL and CSA		op. c./h	360			
Electrical endurance for discharge lamps acc. to UL and CSA		op. c.	100.000			
Rated operational current for AC-5a (at 230 V)	I _e	A	20		32	
Maximum operating frequency for AC-5a		op. c./h	600			
Electrical endurance for AC-5a		op. c.	100.000			
Rated operational current for AC-5b (at 230 V)	I _e	A	17.6		22	
Maximum operating frequency for AC-5b		op. c./h	600			
Electrical endurance for AC-5b		op. c.	100.000			
Rated operational current for AC-6a (at 230 V)	I _e	A	10.8		17.2	
Maximum operating frequency for AC-6a		op. c./h	600			
Electrical endurance for AC-6a		op. c.	100.000			
Switching of capacitors AC-6b and AC-7c (at 230 V)	C	µF	220		330	
Maximum operating frequency for AC-6b and AC-7c		op. c./h	600			
Electrical endurance for AC-6b and AC-7c		op. c.	100.000			
Rated operational current for DC-1 (L/R ≤ 1 ms):	I _e	A				
1 pole ... 24 V DC/48 V DC/60 V DC/110 V DC/ 220 V DC			40/25/18/4/1.2		63/26/20/4/1.2	
2 poles in series ... 24 V DC/48 V DC/60 V DC/110 V DC/ 220 V DC			40/38/32/10/8		63/42/34/10/8	
3 poles in series ... 24 V DC/48 V DC/60 V DC/110 V DC/ 220 V DC			40/40/40/30/20		63/63/60/35/30	
4 poles in series ... 24 V DC/48 V DC/60 V DC/110 V DC/ 220 V DC			40/40/40/40/40		63/63/63/63/63	
Maximum operating frequency for DC-1		op. c./h	300			
Electrical endurance for DC-1		op. c.	100.000			
Rated operational current for DC-3 (L/R ≤ 2 ms):	I _e	A				
1 pole ... 24 V DC/48 V DC/60 V DC/110 V DC/ 220 V DC			22/10/5/1.5/0.3		25/11/5/1.5/0.3	
2 poles in series ... 24 V DC/48 V DC/60 V DC/110 V DC/ 220 V DC			40/20/16/5/1		45/22/18/5/1	
3 poles in series ... 24 V DC/48 V DC/60 V DC/110 V DC/ 220 V DC			40/40/32/15/4		63/45/35/18/5	
4 poles in series ... 24 V DC/48 V DC/60 V DC/110 V DC/ 220 V DC			40/40/40/40/10		63/63/63/63/10	
Maximum operating frequency for DC-3		op. c./h	300			
Electrical endurance for DC-3		op. c.	100.000			
Rated operational current for DC-5 (L/R ≤ 7.5 ms):	I _e	A				
1 pole ... 24 V DC/48 V DC/60 V DC/110 V DC/ 220 V DC			20/8/4/1/0.2		25/10/5/1/0.2	
2 poles in series ... 24 V DC/48 V DC/60 V DC/110 V DC/ 220 V DC			40/18/14/5/0.8		45/20/15/5/0.8	
3 poles in series ... 24 V DC/48 V DC/60 V DC/110 V DC/ 220 V DC			40/40/28/12/3		63/44/30/15/4	
4 poles in series ... 24 V DC/48 V DC/60 V DC/110 V DC/ 220 V DC			40/40/40/35/8		63/63/60/45/10	
Maximum operating frequency for DC-5		op. c./h	300			
Electrical endurance for DC-5		op. c.	100.000			
Terminal capacity:	S					
rigid (solid and stranded)			14 ... 10 AWG / 1.5 ... 25 mm ²			
flexible			14 ... 4 AWG / 1.5 ... 16 mm ²			
Length of removed wire insulation			0.394 in / 10 mm			
Screw			M5			
Screw head			PZ2			
Tightening torque			30.98 lb-in / 3.5 Nm			
Contact reliability			≥17 V; ≥50 mA			
Minimum distance of open contacts			0.118 in / 3.6 mm			
Power dissipation per pole		W	4		8	
Overload current withstand capability:						
10 s			176		240	
Maximum back-up fuse for short-circuit protection gL and gG:	I _v	A				
coordination type 1			63	63	80	80
coordination type 2			40	40	63	63

Installation Contactors UL/CSA

up to 63 A



TECHNICAL DATA

AUXILIARY CIRCUIT	Type	Symbol	Unit	IKA440	IKD440	IKA463	IKD463	
	Maximum back-up fuse for short-circuit protection K5 acc. to UL and CSA	I _v	A	60	60	70	70	
	Rated insulation voltage	U _i	V	440				
	Rated impulse withstand voltage	U _{imp}	kV	4				
	Rated operational voltage	U _e	V	230/400				
	Rated frequency	f	Hz	50/60				
	Thermal current	I _{th}	A	40		63		
	Rated operational current for AC-15: single-phase 230 V single-phase 400 V	I _e	A	6 4				
	Maximum operating frequency for AC-15		op. c./h	1.200				
	Electrical endurance for AC-15		op. c.	150.000				
	Switching of auxiliary loads according to standard UL and CSA			B300, P300				
	Maximum operating frequency for auxiliary loads according to UL and CSA		op. c./h	360				
	Electrical endurance for auxiliary loads according to UL and CSA		op. c.	100.000				
	Rated operational current for DC-13: 1 pole ... 24 V DC/48 V DC/60 V DC/110 V DC/ 220 V DC 2 poles in series ... 24 V DC/48 V DC/60 V DC/110 V DC/ 220 V DC 3 poles in series ... 24 V DC/48 V DC/60 V DC/110 V DC/ 220 V DC 4 poles in series ... 24 V DC/48 V DC/60 V DC/110 V DC/ 220 V DC	I _e	A	6/4/1/0.3/0.05 6/6/4/1/0.1 6/6/6/3/1 6/6/6/4/2				
	Maximum operating frequency for DC-13		op. c./h	300				
	Electrical endurance for DC-13		op. c.	200.000				
	Terminal capacity: rigid (solid and stranded) flexible	S		4 ... 10 AWG / 1.5... 25 mm ² 4 ... 10 AWG / 1.5...16 mm ²				
	Length of removed wire insulation			0.394 in / 10 mm				
	Screw			M5				
	Screw head			PZ2				
	Tightening torque			30.98 lb-in / 3.5 Nm				
	COIL	Range of control voltage for switch-on	U _c	%	85 ... 110			
		Range of control voltage for drop out	U _c	%	AC: 75 ... 20 / DC: 75 ... 10 (where is applicable)			
		Kind of voltage			AC	AC/DC	AC	AC/DC
		Standard control voltages	U _c	V	12, 24, 48, 110, 120, 127, 208, 230, 240			
Frequency of AC control voltage		f	Hz	50/60				
Control mode				remote control with U _c				
Impulse duration of control voltage: minimum maximum				permanent permanent				
Minimum duration between two impulses of control voltage			ms	AC: 150 / DC: 500 (where is applicable)				
Surge immunity withstand voltage 1,2/50 μs acc. to standard IEC/EN 61000-4-5			kV	2				
Coil consumption: switch-on operation			VA/W	15.4/6 7.7/3	5/5 ¹⁾ 5/5 ¹⁾	15.4/6 7.7/3	5/5 ¹⁾ 5/5 ¹⁾	
Delays: make brake			ms	10 ... 20 10 ... 15	15 ... 20 35 ... 45	10 ... 20 10 ... 15	15 ... 20 35 ... 45	
Terminal capacity: rigid (solid and stranded) flexible				16 ... 14 AWG / 1 ... 2.5 mm ² 16 ... 14 AWG / 1 ... 2.5 mm ²				
Length of removed wire insulation				0.315 in / 8 mm				
Screw				M3				
Screw head				PZ1				
Tightening torque				5.31 lb-in / 0.6 Nm				
SAFETY		MTTF - Mean time to failure MTTF = 1/λ = B10/(0.1 n _{op})		h	General Use: 2.083 Motor: 3.125			
		MTTF _d - Mean time to failure dangerous MTTF _d = 1/λ _d = B10 _d /(0.1 n _{op})		h	General Use: 2.777 Motor: 4.166			
		B10 - Number of operating cycles until 10 % of devices fail		op. c.	General Use: 75.000 Motor: 112.500			
		B10 _d - Number of operating cycles until 10 % of device dangerous B10 _d = B10/ratio of dangerous failures		op. c.	General Use: 100.000 Motor:150.000			
	λ - Failure rate λ = (0.1 n _{op})/B10		1/h	General Use: 0.00048 Motor: 0.00032				
	λ _d - Failure rate dangerous λ _d = (0.1 n _{op})/B10 _d		1/h	General Use: 0.00036 Motor: 0.00024				
	Ratio of dangerous failures		%	75				
	n _{op} - Operating cycles (operating cycles/h)		op. c./h	360				

¹⁾ Coil consumption for -22 and -04 is 6.1 VA/6.1 W

IKN, IKN-UL – Auxiliary switch

TECHNICAL DATA

GENERAL	Type	Symbol	Unit	IKN	IKN-UL
	Standards			IEC/EN 60947-5-1	UL508, C22.2 No. 14, IEC/EN 60947-5-1
	Approvals			CE, CB, NF, EAC	CE, UL, CSA
	Module width			0.5	0.5
	Number of poles			2	2
	Degree of protection			IP20 ¹⁾	IP20 ¹⁾
	Pollution degree			3	3
	Climatic conditions			95 % relative humidity	
	Ambient temperature: open			-25 °C ... +55 °C	
	closed				-13 °F ... 104 °F / -25 °C ... +40 °C
	Storage temperature			-30 °C ... +80 °C	-22 °F ... 176 °F / -30 °C ... +80 °C
	Maximum altitude U _i and U _e is reduced for 1.2 % and I _e for 0.4 % for every additional 100 m		m	2000	2000
	Mechanical endurance		op. c.	3.000.000	3.000.000
	Weight			30 g	0.08 lb / 30 g
AUXILIARY CIRCUIT	Contact reliability			≥12 V; ≥5 mA	≥12 V; ≥5 mA
	Minimum distance of open contacts			3.6 mm	0.142 in / 3.6 mm
	Power dissipation per pole		W	0.3	0.3 (at I _{th} = 6 A)
	Maximum back-up fuse for short-circuit protection gL and gG: coordination type 2	I _v	A	6	6
	Maximum back-up fuse for short-circuit protection KS acc. to UL and CSA	I _v	A		6
	Rated insulation voltage	U _i	V	500	500
	Rated impulse withstand voltage	U _{imp}	kV	4	4
	Rated operational voltage	U _e	V	230/400	IEC: 230 / 400
					UL: C300 (120 VAC, 240 VAC)
					UL: Q300 (125 VDC, 250 VDC)
	Rated frequency	f	Hz	50/60	50/60
	Thermal current	I _{th}	A	6	IEC: 6; UL: 2.5
	Rated operational current for AC-15: single-phase 230 V single-phase 400 V	I _e	A	6	6
				4	4
	Electrical endurance for AC-15		op. c.	50.000	50.000
	Switching of auxiliary loads acc. to standard UL and CSA				C300, Q300
	Electrical endurance for auxiliary loads acc. UL and CSA		op. c.		50.000
	Rated operational current for DC-13: 1 pole ... 24 VDC / 48 VDC / 60 VDC / 110 VDC / 220 VDC 2 poles in series ... 24 VDC / 48 VDC / 60 VDC / 110 VDC / 220 VDC	I _e	A	6/4/1/0.3/0.05	6/4/1/0.3/0.05
				6/6/4/1/0.1	6/6/4/1/0.1
	Electrical endurance for DC-13		op. c.	50.000	50.000
	Switching of auxiliary loads acc. to standard UL and CSA				C300, Q300
	Electrical endurance for auxiliary loads acc. UL and CSA		op. c.		50.000
	Terminal capacity: rigid (solid and stranded) flexible	S		1 ... 2.5 mm ²	16 ... 14 AWG / 1 ... 2.5 mm ²
				1 ... 2.5 mm ²	16 ... 14 AWG / 1 ... 2.5 mm ²
	Length of removed wire insulation			7 mm	0.276 in / 7 mm
	Screw			M3	M3
Screw head			PZ1	PZ1	
Tightening torque			0.8 Nm	7.08 lb-in / 0.8 Nm	
SAFETY	MTTF - Mean time to failure MTTF = 1/λ = B10/(0.1 n _{op})		h	833	694
	MTTF _d - Mean time to failure dangerous MTTF _d = 1/λ _d = B10 _d /(0.1 n _{op})		h	1.666	1.388
	B10 - Number of operating cycles until 10 % of devices fail		op. c.	25.000	25.000
	B10 _d - Number of operating cycles until 10 % of device dangerous B10 _d = B10/ratio of dangerous failures		op. c.	50.000	50.000
	λ - Failure rate λ = (0.1 n _{op})/B10		1/h	0.0012	0.00144
	λ _d - Failure rate dangerous λ _d = (0.1 n _{op})/B10 _d		1/h	0.0006	0.00072
	Ratio of dangerous failures		%	50	50
	n _{op} - Operating cycles (operating cycles/h)		op. c./h	300	360

¹⁾ IP40 when installed in installation box - distribution boards

Installation Switches IKS-R

Installation Momentary Switches IKS-T




TECHNICAL DATA

GENERAL	Type	Symbol	Unit	IKS220-R IKS220-T	IKS225-R IKS225-T	IKS232-R IKS232-T	IKS420-R IKS42-T	IKS425-R IKS425-T	IKS432-R IKS432-T	
	Standards			IEC/EN 60947-3						
	Approvals			CE						
	Module width			2			4			
	Number of poles			2			4			
	Degree of protection			IP20 (IP40 when installed in installation box - distribution board)						
	Pollution degree			3						
	Climatic conditions			95 % relative humidity						
	Ambient temperature (open)		°C	-25 ... +55						
	Storage temperature		°C	-30... +80						
	Maximum altitude U _i and U _e is reduced for 1.2 % and I _e for 0.4 % for every additional 100 m		m	2000						
	Number of contactors or switches side-by-side: ≤40 °C (40 ... 55) °C			no limitation						
	Maximum operating frequency with no load		op. c./h	600						
	Mechanical endurance		op. c.	1.000.000						
	Weight		g	55			105			
	MAIN CIRCUIT	Contact reliability			≥17 V; ≥50 mA					
		Minimum distance of open contacts		mm	3.6					
		Power dissipation per pole		W	1.7	2	2.5	1.7	2	2.5
		Overload current withstand capability: 10 s			72			68		
Maximum back-up fuse for short-circuit protection gL and gG: coordination type 1		I _v	A	20	25	32	20	25	32	
Rated insulation voltage		U _i	V	440						
Rated impulse withstand voltage		U _{imp}	kV	4						
Rated operational voltage		U _e	V	230						
Rated frequency		f	Hz	50/60						
Thermal current		I _{th}	A	20	25	32	20	25	32	
Rated operational current for AC-1, AC-7a and AC-21		I _e	A	20	25	32	20	25	32	
Operational power for AC-1, AC-7a and AC-21: single-phase 230 V three-phase 230 V		P _e	kW	4	5.4	7	4	5.4	7	
						7	9	12		
Maximum operating frequency for AC-1, AC-7a and AC-21			op. c./h	300						
Electrical endurance for AC-1, AC-7a and AC-21			op. c.	100.000						
Rated operational current for AC-22		I _e	A	20	25	32	20	25	32	
Operational power for AC-22: single-phase 230 V three-phase 230 V		P _e	kW	3.7	4.6	5.9	3.7	4.6	5.9	
						6.2	8	10.2		
Maximum operating frequency for AC-1, AC-7a and AC-21			op. c./h	300						
Electrical endurance for AC-1, AC-7a and AC-21			op. c.	50.000						
Rated operational current for AC-5a (at 230 V)		I _e	A	8.8	11	13	8.8	11	13	
Maximum operating frequency for AC-5a			op. c./h	300						
Electrical endurance for AC-5a (at 230 V)			op. c.	100.000						
Rated operational current for AC-5b (at 230 V)		I _e	A	8.8	9.7	11	8.8	9.7	11	
Maximum operating frequency for AC-5b			op. c./h	300						
Electrical endurance for AC-5b (at 230 V)			op. c.	100.000						
Rated operational current for AC-6a (at 230 V)		I _e	A	4	4.8	6	4	4.8	6	
Maximum operating frequency for AC-6a			op. c./h	300						
Electrical endurance for AC-6a (at 230 V)			op. c.	100.000						
Switching of capacitors AC-6b and AC-7c (at 230 V)		C	µF	30	36	40	30	36	40	
Maximum operating frequency for AC-6b and AC-7c			op. c./h	300						
Electrical endurance for AC-6b and AC-7c			op. c.	100.000						
Terminal capacity: rigid (solid and stranded) flexible		S	mm²	1 ... 10 1 ... 6						
Length of removed wire insulation				9						
Screw				M3.5						
Screw head			PZ1							
Tightening torque		Nm	1.2							

Diagram 1

AC-1/230V/1-phase for IKA20, IKD20, IKA220 (UL), IKD220 (UL), IKA225, IKD225, IKA232, IKD232, IKA440 (UL), IKD440 (UL), IKA463 (UL), IKD463 (UL)
 AC-1/400V/3-phase for IK21, IKA25, IKD25, IKA425 (UL), IKD425 (UL), IKA432, IKD432, IKA40, IK40, IKA63, IK63



Installation Contactors

Electrical Endurance

Diagram 2

AC-3/400V/3-phase for IK21, IKA25, IKD25, IKA425 (UL), IKD425 (UL), IKA432, IKD432, IKA40, IKA63, IK63, IKA440 (UL), IKD440 (UL), IKA463 (UL), IKD463 (UL)






Diagram 3

AC-3/230V/1-phase for IKA20, IKD20, IKA220 (UL), IKD220 (UL), IKA225, IKD225, IKA232, IKD232



Mounting positions of accessories




Installation Contactors

Operating Position, Dimensions


Operation position

IKA20/225/232/ 25/432/ 40/ 63
IKA220/425/ 440/ 463 (UL)


180°



All installation contactors




IKD20/225/232/ 25/432
IK40/63, IKD220/425/440/463 (UL)




IKA20/225/232-R/-T
IKA25/432-R/-T


180°



IKA/D20/225/232-R/-T
IKA/D25/432-R/-T




IKD20/225/232-R/-T
IKD25/432-R/-T




NOTE: IK21 and IKS-R/-T have no limitation

Dimension (in millimeters)



IK21



IKA20, IKD20
IKA225, IKD225
IKA232, IKD232




IKA25, IKD25
IKA432, IKD432




Dimensions (in millimeters unless otherwise stated)

IK40, IK63
IKA40, IKA63



IKA20-R, IKD20-R
IKA225-R, IKD225-R
IKA232-R, IKD232-R



IKA25-R, IKD25-R
IKA432-R, IKD432-R
IKS420-R, IKS425-R, IKS432-R
IKS420-T, IKS425-T, IKS432-T



IKA20-T, IKD20-T
IKA225-T, IKD225-T
IKA232-T, IKD232-T





IKS220-R, IKS225-R
IKS232-R

IKS220-T, IKS225-T
IKS232-T



IKA220 (UL), IKA425 (UL)
IKD220 (UL), IKD425 (UL)

IKA440 (UL), IKD440 (UL)
IKA463 (UL), IKD463 (UL)




Installation Contactors


Dimensions

Dimensions (in millimeters unless otherwise stated)

IKN



IKN-UL



IKV

