



EN: This Datasheet/Document is presented by the manufacturer.

Please visit our website for pricing and availability at www.hestore.hu.



WXR3031 Set 230V

Item No: T0053502699N

3-Channel Rework Station, 420 W
(600 W)

KEY FEATURES

- + Power unit WXR 3, 3 channels with WXHAP 200 Hot air iron, WXDP 120 Desoldering iron and WXP 120 Soldering Iron

TECHNICAL DATA

Height	102mm
Length	273mm
Dimensions L x W x H	273.0 x 235.0 x 102.0mm
Capacity (l/min)	18 l/min
Equipotential Bonding Socket	Via 3.5mm pawl socket on back of device (hard-grounded)
ESD Safe	Yes
Interface	1x USB, 2x RS232, 2x Switching Output
Maximum Hot Air Flow Rate l/min (Depends on Tool)	15 l/min
Noise level (distance 1 m) dB(A)	0.7 bar
Number of Channels	3
Overcurrent Release	2 A
Power	420 W (600 W)
Temperature Accuracy °C	± 9°C
Temperature Accuracy °F	± 17°F
Temperature Accuracy for Hot Air	± 30°C, ± 54°F
Temperature Range °C	100 - 450 °C (550 °C)
Temperature Range °F	200 - 850 °F (999 °F)
Temperature Stability °C	± 2°C
Temperature Stability °F	± 4°F
Tip Type	WX
UPC	4003019435838
USB	USB interface of firmware updates, parameterization and monitoring USB interface supports all standard USB flash drive types
Weight (Catalog)	6.70 kg
Product Family	Rework, Hot Air, Desoldering Stations