



EN: This Datasheet/Document is presented by the manufacturer.

Please visit our website for pricing and availability at www.hestore.hu.

WXR3030 Set 230V

Item No: T0053501699N
3-Channel Rework Station, 420 W
(600 W)



KEY FEATURES

- + Power unit WXR 3, 3 channels with WXHAP 200 Hot air iron, WXDP 120 Desoldering iron and WXP 65 Soldering iron

TECHNICAL DATA

Height	102mm
Length	273mm
Dimensions L x W x H	273.0 x 235.0 x 102.0mm
Capacity (l/min)	18 l/min
Equipotential Bonding Socket	Via 3.5mm pawl socket on back of device (hard-grounded)
ESD Safe	Yes
Interface	1x USB, 2x RS232, 2x Switching Output
Maximum Hot Air Flow Rate l/min (Depends on Tool)	15 l/min
Noise level (distance 1 m) dB(A)	0.7 bar
Number of Channels	3
Overcurrent Release	2 A
Power	420 W (600 W)
Temperature Accuracy °C	± 9°C
Temperature Accuracy °F	± 17°F
Temperature Accuracy for Hot Air	± 30°C, ± 54°F
Temperature Range °C	100 - 450 °C (550 °C)
Temperature Range °F	200 - 850 °F (999 °F)
Temperature Stability °C	± 2°C
Temperature Stability °F	± 4°F
Tip Type	LT RTM RTW WX XHT XNT XT
USB	USB interface of firmware updates, parameterization and monitoring USB interface supports all standard USB flash drive types
Voltage	230V (50/60 Hz)
Weight (Catalog)	6.70 kg
Product Family	Rework, Hot Air, Desoldering Stations