EN: This Datasheet/Document is presented by the manufacturer.

Please visit our website for pricing and availability at www.hestore.hu.

Data sheet Product WLK DK 10



Thermal interface material / Fixing material / Mounting material>Thermal interface material>Thermally conductive adhesive

- solvent-free and thermal conductive two part adhesive
- epoxy based filled with aluminium oxide
- composition of hardener and resin (1:1) with statical mixing tube
- lockability of the container via Luer-Lock System
- good usage and working properties
- more package sizes and container types upon request
- store cool and dry



Features

thermal conductivity:	**1 W/m·K**
specific thermal resistance:	**118°C cm/W**
working life at room temperature:	**approx. 30 min**
hardening time:	**60°C approx. 4 h/25°C approx. 16 h**
volume resistance:	**$8 \cdot 10^{11}$ Ω/cm**
temperature range:	**-50°C... +145°C**
glue layer:	**Epoxid**
mixture proportion:	**1:1**
contents of delivery:	**1x 10 ml syringe / 3x mixer WLK M4**
storage conditions:	• **+25 °C** • **50 % humidity**
shelf life:	**12 months**

Fischer Elektronik GmbH & Co. KG
DEUTSCHLAND • GERMANY • ALLEMAGNE
Nottebohmstraße 28
58511 Lüdenscheid
Telefon +49 2351 435-0
Telefax +49 2351 45754
info@fischerelektronik.de
www.fischerelektronik.de