




EN: This Datasheet/Document is presented by the manufacturer.

Please visit our website for pricing and availability at www.hestore.hu.




线长依订单要求

PIN ASSIGNMENT:

	BK	RD	GR	YL
P1:	2	3	4	5
P2:	5	4	3	2
	BK	RD	GR	YL

DESIGNATION	SIZE/L	Jacket Colour
TEL-RJ11-WH/05	5000±50MM	WH
TEL-RJ11-WH/10	10000±60MM	WH
TEL-RJ11-WH/20	20000±100MM	WH
TEL-RJ11-WH/02	2000±10MM	WH
TEL-RJ11-BK/05	5000±50MM	BK
TEL-RJ11-WH/15	15000±100 MM	WH
TEL-RJ11-BK/01	1000±30 MM	BK
TEL-RJ11-BK/10	10000±50 MM	BK
TEL-RJ11-BK/07	7000±50 MM	BK
TEL-RJ11-WH/07	7000±50 MM	WH



SECTION A-A

1	Cable (0.11BC/7C+PP0.95)*4F+PVC OD:2.4*4.8±0.2MM	A/R	M						
2	Connector RJ11 6P4C FU	2	PCS						
3				TOLERANCE OTHERWISE UNLESS SPECIFIED		DRAWING:	曾洪彬	MCXH	
4						REVIEW:		CLIENT	TME
5						APPROVED:		NUMBER	
6						DATE	2014-01-07	SCALE	FREE UNIT MM
备注:				UP TO 5	±0.2				
				ABOVE 5—30	±0.3				
				ABOVE 30—50	±0.4				
				ABOVE 50	±0.5				
NO	Description	Q'TY	Units	ANGLE	±3°				