



EN: This Datasheet/Document is presented by the manufacturer.

Please visit our website for pricing and availability at www.hestore.hu.

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

TRADE NAME:

Lead & tin soft solder alloys with flux F4V12 / PRO / SW26 / RC1

OTHER NAME:

Sn60Pb40	PRO/1/1,5% (1.1.3.B)	Sn63Pb37	SW26/2,5% (1.1.2.B)
Sn60Pb40	PRO/3/2,0% (1.1.3.B)	Sn63Pb37	F4V12/3/2,0% (1.1.2.B)
Sn60Pb40	PRO/3/2,5% (1.1.3.B)	Sn63Pb37	F4V12/2,0% (1.1.2.B)
Sn60Pb40	PRO/1,5% (1.1.3.B)	Pb50Sn50	SW26/3/2,5% (1.1.2.B)
Sn60Pb40	PRO/2,0% (1.1.3.B)	Pb50Sn50	SW26/2,5% (1.1.2.B)
Sn60Pb40	RC1/3/2,5% (1.1.2.B)	Pb60Sn40	SW26/2,5% (1.1.2.B)
Sn60Pb40	RC1/2,5% (1.1.2.B)	Pb60Sn40	SW26/3/2,5% (1.1.2.B)
Sn60Pb40	SW26/3/2,0% (1.1.2.B)	Pb60Sn40	SW26/1/2,5% (1.1.2.B)
Sn60Pb40	SW26/3/2,5% (1.1.2.B)	Pb60Sn40	SW26/3/2,5% (1.1.2.B)
Sn60Pb40	SW26/2,0% (1.1.2.B)	Pb60Sn40	SW26/3/2,5% (1.1.2.B)
Sn60Pb40	SW26/2,5% (1.1.2.B)	Pb60Sn40	SW26/3/2,5% (1.1.2.B)
Sn60Pb40	SW26/3,5% (1.1.2.B)	Pb60Sn40	SW26/3/2,5% (1.1.2.B)
Sn63Pb37	PRO/1/1,0% (1.1.3.B)	Pb60Sn40	SW26/3/2,5% (1.1.2.B)
Sn63Pb37	PRO/1/1,5% (1.1.3.B)	Pb60Sn40	SW26/3/2,5% (1.1.2.B)
Sn63Pb37	PRO/1,5% (1.1.3.B)	Pb60Sn40	SW26/3/2,5% (1.1.2.B)
Sn63Pb37	SW26/1/1,0% (1.1.2.B)	Pb60Sn40	SW26/3/2,5% (1.1.2.B)
Sn63Pb37	SW26/3/2,5% (1.1.2.B)	Pb70Sn30	SW26/2,5% (1.1.2.B)
Sn63Pb37	SW26/2,2% (1.1.2.B)		

SPOIWO LUTOWNICZE Z TOPNIKIEM Sn60Pb40 SW26/3/2,5%

1.2 Relevant identified uses of the substance or mixture and uses advised against

RELEVANT IDENTIFIED USES:

Intended for industrial and professional applications. Restricted to professional users.

USES ADVISED AGAINST:

Consumer and not identified uses.

1.3 Details of the supplier of the safety data sheet

SUPPLIER:

Cynel-Unipress Sp. z o. o.

ADDRESS:

ul. Białolecka 231B, 03-253 Warszawa, Poland

TELEPHONE/FAX NUMBER:

+48 22 519 29 48/ 22 519 29 46

E-MAIL ADDRESS:

marketing@cynel.com.pl

1.4 Emergency telephone number

Emergency Phone in Poland (open: 8.00 a.m.-4.00 p.m.)

+48 22 519 29 48 or +48 22 519 29 49

Section 2: Hazards identification

2.1 Classification of the substance or mixture**CLASSIFICATION ACCORDING TO REGULATION (EC) No 1272/2008****Reproductive toxicity, Hazard Category 1A (Repr. 1 A)**

May damage fertility. May damage the unborn child (H360FD)

Reproductive toxicity, Additional category, Effects on or via lactation (Lact.)

May cause harm to breast-fed children (H362)

Specific target organ toxicity — Repeated exposure, Hazard Category 1 (STOT RE1)

Causes damage to central nervous system, blood and kidneys through prolonged or repeated exposure by inhalation or ingestion (H372)

Sensitization, Skin hazard category 1 (Skin Sens 1)

May cause an allergic skin reaction (H317)

HARMFUL EFFECTS OF HUMAN HEALTH EFFECTS:

May cause an allergic skin reaction. May damage fertility. May damage the unborn child. May cause harm to breast-fed children. Causes damage to central nervous system, blood and kidneys through prolonged or repeated exposure by inhalation or ingestion.

There is a danger of lead poisoning in its processing. Fumes and vapors of lead, separated during the processes of soldering are damaging and irritating to the respiratory system. Lead compounds such as oxides and alloys have toxic and mutagenic effects, may accumulate in the body and impair fertility.

EFFECTS OF OPERATION ON THE ENVIRONMENT:

If you use rightly, does not pose a threat to the environment.

EFFECTS OF ACTION RELATED TO PHYSICOCHEMICAL PROPERTIES:

Not applicable

2.2 Label elements**HAZARD SYMBOLS:**

Danger

RISK PHRASES:

H360FD May damage fertility. May damage the unborn child.

H362 May cause harm to breast-fed children.

H372 Causes damage to central nervous system, blood and kidneys through prolonged or repeated exposure by inhalation or ingestion.

H317 May cause an allergic skin reaction

SAFETY PHRASES:

P260 Do not breathe dust/fume.

P308 + P313 If exposed or concerned: Get medical advice/ attention.

P501 Dispose of contents/container to authorized waste collector.

OTHER INFORMATION:

Contains rosin. Contains lead. Restricted to professional users.

2.3 Other hazards

When applying or processing products containing lead and lead-based products there is a risk of lead poisoning.

The mixture does not contain substances included on the list established in accordance with Article 59(1) as having endocrine disrupting properties and substances with endocrine disrupting properties in accordance with the criteria laid down in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605.

The criteria for PBT or vPvB according to Annex XIII of Regulation REACH do not apply to inorganic substances.

Section 3: Composition/Information on ingredients

3.1 Substances

Not applicable

3.2 Mixtures:

TIN (Sn):

Range of percentages: 29,50 – 63,00%

CAS number: 7440-31-5

EC number: 231-141-8

Registration number: 01-2119486474-28-0000

Classification acc. to 1272/2008/EC: not classified

Substance with defined value of the permissible concentration in the working environment at Community level.

LEAD (Pb) MASSIVE: [PARTICLE DIAMETER ≥ 1 MM]

Range of percentages: 36,0 – 70,5 %

CAS number: 7439-92-1

EC number: 231-100-4

UN number: 082-014-00-7

Registration number: 01-2119513221-59-0056

Classification acc. to 1272/2008/EC: Lact. H362, Repr.1A H360FD, STOT RE1 H372
Substance with defined value of the permissible concentration in the working environment at Community level.

ROSIN

Range of percentages: 0 – 3,0%
CAS number: 8050-09-7
EC number: 232-475-7
Registration number: 01-2119480418-32-XXXX
Classification acc. to 1272/2008/EC: Skin Sens 1 H317

Full text of each relevant H phrase is given in section 16.

Section 4: First aid measures

4.1 Description of first aid measures

GENERAL INFORMATION:

at room temperature (outside of the dangers of a mechanical nature), calophony does not pose risk to human health and life. But in the process of soldering the main risks are: high temperature, solder fumes and vapours.

In case of health problems, immediately contact to a doctor or poison control center. Please check vital functions. If victim is unconscious, please provide adequate ventilation. Prevent the victim from cooling down.

SKIN CONTACT:

Solder alloy: In case of exposure wash the affected skin thoroughly with soap and water.
In the process of soldering: possible thermal burn. Rinse damaged skin with cold water. Apply a sterile dressing. Consult with the doctor.

EYE CONTACT:

Solder alloy: if filings get into the eyes, immediately rinse with plenty of water with the eyelids wide open, for at least 10-15 min. Consult an ophthalmologist.
In the process of soldering: In the process of soldering: splashes of molten metal can cause burns. Apply a sterile dressing. Immediately consult an ophthalmologist.

INGESTION:

Rinse mouth with water. Do not induce vomiting without medical advice. Consult a physician.
The form of the product causes that exposure is unlikely. Consume the product may be a consequence of not following basic hygiene rules, e.g. washing hands after work or exposure to high concentrations of dust and fumes in the workplace.

INHALATION:

Wire: exposure not possible.
In the process of soldering: take the affected person to fresh air and obtain medical ensure help. Symptoms of poisoning may appear after a few days.

4.2 Most important symptoms and effects, both acute and delayed

Lead is bioaccumulating in the body. Exposure to low concentrations of lead can provides increased levels of lead in the body to toxic levels. Symptoms of chronic poisoning can be similar to food poisoning.

EYE CONTACT:

may cause irritation, redness, tearing.

SKIN CONTACT:

may cause redness, burning sensation, bums (during soldering). Lead can be absorbed through the intact skin as a result of prolonged contact.

INHALATION:

irritation of respiratory tract, cough, headaches and dizziness.

Lead can cause "fever of foundry" with metallic taste in the mouth, fever, chills, cough, weakness, muscle aches, increased white blood cell count, gastrointestinal irritation with nausea, vomiting and diarrhea. After absorption into the blood, lead is toxic to the hematopoietic system, the central nervous system and the kidneys. Symptoms of lead poisoning include: general weakness, loss of weight, insomnia, hypotension, constipation, anorexia, abdominal pain, colic. Symptoms of exposure may only appear after a few days.

INGESTION:

Symptoms of lead poisoning include: general weakness, loss of weight, insomnia, hypotension, constipation, anorexia, abdominal pain, colic.

4.3 Indication of any immediate medical attention and special treatment needed

A decision regarding further medical treatment by a physician should be made after thorough examination of the injured.

Section 5: Firefighting measures

5.1 Extinguishing media

SUITABLE EXTINGUISHING MEDIA:

extinguishing powder, sand

Extinguishing with extinguishing powders or sand promotes the limitation of the release of toxic fumes of lead, lead oxides and other metals.

UNSUITABLE EXTINGUISHING MEDIA:

CO₂, foam, water jet – risk of the propagation of the flame

5.2 Special hazards arising from the substance or mixture

Non-combustible product. During the combustion at > 400° C may be create products with toxic and irritating fumes contains lead. Do not inhale combustion products – it can be dangerous to health.

5.3 Advice for firefighters

Personal protection typical in case of fire. Self-contained breathing apparatus and protective clothing should be worn.

Section 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Limit the access to the breakdown area for the outsiders, until the suitable cleaning operations are completed. Use personal protective equipment. Ensure that the consequences of failure are removed by trained personnel only. Do not inhale dust. Avoid direct contact with the product. There must be adequate ventilation. Wear a face mask if the ventilation is insufficient.

FOR NON-EMERGENCY PERSONNEL

Use protective clothing made of natural materials (cotton) or synthetic fibers, gloves made of nitrile. Use safety goggles. Do not inhale dust, smoke, vapour. Remove sources of ignition. . Ensure that the consequences of failure are removed by trained personnel only.

FOR EMERGENCY RESPONDERS

Use protective clothing made of natural materials (cotton) or synthetic fibers. Use full safety mask. Do not inhale dust, smoke, vapour. Remove sources of ignition. Mark the contamination of the area.

6.2 Environmental precautions

Prevent entry into drains, surface and ground water and soil. In case of release of large amounts of the product, notify the appropriate emergency services.

6.3 Methods and material for containment and cleaning up

Pick it up mechanically. Avoid dust formation during collection. The waste must be collected and transported in sealed container. Treat collected material like a waste or reuse it. Hand over the waste to waste management companies.

6.4 Reference to other sections

Appropriate conduct with waste product – section 13

Appropriate personal protective clothing – section 8

Section 7: Handling and storage

7.1 Precautions for safe handling

Handle in accordance with good occupational hygiene and safety practices Before break and after work wash hands carefully. Avoid contact with eyes and skin. Do not breathe fumes in the process of soldering. Ensure proper ventilation during soldering process. Do not eat, drink and smoke during the handling. Avoid creating dust in the workplace. Use as intended. Wear personal protective equipment.

7.2 Conditions for safe storage, including any incompatibilities

Keep in properly labeled original packaging. Keep in a dry and well-ventilated place. Keep away from strong acids and oxidants. Store at temp. 5-30°C. The recommended humidity level of 20-80%. Keep away from food and beverages.

7.3 Specific end use(s)

The product for manual and automatic soft soldering restricted to professional users.

Section 8: Exposure controls/personal protection

8.1 Control parameters

Follow the procedures for monitoring the concentrations of hazardous components in the air and the procedures for the control of air quality in the workplace - as long as they are available and reasonable on a given workplace - according to the relevant European Standards. Take into account the conditions at the site of exposure and appropriate measurement methodology adapted to working conditions.

THE FOLLOWING CURRENT NATIONAL OCCUPATIONAL EXPOSURE LIMIT VALUES APPLY (EUROPEAN UNION):

Specification	TLV-TWA [$\mu\text{g}/\text{m}^3$] *	TLV-STEL [mg/m^3]
Lead and its inorganic compounds	100	—
Tin and its inorganic compounds	—	—

* Measured or calculated in relation to a reference period of eight hours as a time-weighted average.

Please check also any national occupational exposure limit values in your country.

TIN

DNEL inhalation (long-term) worker 71 mg / m^3

DNEL skin (long-term) worker 10 mg / kg body weight / day

DNEL inhalation (long-term) consumer 17 mg / m^3

DNEL skin (long-term) consumer 80 mg / kg body weight / day

DNEL oral (long-term) consumer 5 mg / kg body weight / day

PNEC LEAD

	Value	Assessment factor	Remarks/Justification
PNEC freshwater sediment (mg/kg d.w.)	174	3	Based on the use of the species sensitivity distribution approach
PNEC freshwater sediment (mg/kg d.w.)	41	10	Based on AVS correction
PNEC marine sediment (mg/kg d.w.)	164	3	Based on the use of the species sensitivity distribution approach and pooling of AVS -

[In accordance with COMMISSION REGULATION (EU) 2020/878 of 18 June 2020 amending Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (Official Journal of the European Union No L.203 z 26.06.2020)]

			freshwater/marine toxicity data
PNEC aqua – freshwater (µg/L)	5,6 µg dissolved Pb/L	3	Based on the use of the SSD approach and for normalization of the toxicity data at reasonable worst case DOC of 2.6 mg/l
PNEC aqua - marine water (µg/L)	3,4 µg dissolved Pb/L	3	Based on the use of the species sensitivity distribution approach
PNEC soil (mg/kg d.w.)	147	2	Based on the use of the species sensitivity distribution approach
PNEC – oral (mg/kg food) for birds	16,9	6	-----
PNEC - oral (mg/kg paszy) for mammals	10,9	6	-----
PNEC STP (mg/L)	0,1	10	-----

DNEL LEAD FOR WORKERS

Exposure pattern	Route	Descriptors	DNEL/DMEL (appropriate unit)	Most sensitive endpoint
Long-term – systemic effects	systemic (µg/dL Pb we blood)	NOAEL = 40 µg Pb/dl blood NOAEL = 10 µg Pb/dl blood	40 µg Pb/dL blood 10 µg Pb/dL blood	Adult neurological function Developmental effect on foetus of pregnant women

DNEL LEAD FOR GENERAL POPULATION

Exposure pattern	Route	Descriptors	DNEL/DMEL (appropriate unit)	Most sensitive endpoint
Long-term – systemic effects	systemic (µg/dL Pb we blood)	NOAEL = 40 µg Pb/dl	20 µg Pb/dL	Adult neurological function
Neurological function		NOAEL = 10 µg Pb/dl	10 µg Pb/dL	Foetal development for a pregnant woman
		NOAEL = 10 µg Pb/dl	10 µg Pb/dL	IQ development in individual child
		NOAEL = 5 µg Pb/dl	5 µg Pb/dL	IQ development in a large number of children

8.2 Exposure controls

APPROPRIATE ENGINEERING CONTROLS

Ensure adequate general and local ventilation. In case of insufficient ventilation use respiratory protection. When handling do not eat, drink, take medicine and smoke. Before break and after work carefully wash hands. Avoid dusting. Avoid contact with skin, eyes and inhalation of dust, fumes and vapors produced during processing of the product.

Employer is obliged to ensure equipment adequate to activities carried out, with quality demands, cleaning and maintenance.

INDIVIDUAL PROTECTION MEASURES, SUCH AS PERSONAL PROTECTIVE EQUIPMENT

Respiratory protection

In the event of exceedances of limit values use respiratory protection with filter type P1 or depending on the concentration exceeded (P2, P3)

If you work in closed spaces or where there is a risk of an uncontrolled expansion use insulating respiratory protective equipment.

Skin, hand and body protection

Use protective clothing made of natural materials (cotton) or synthetic fibers, gloves made of nitrile or latex (thickness $0,4 \pm 0,05$ mm, breakthrough time > 60 min)

Eye protection

Use safety goggles that protect against splatter during soldering.

Handle in accordance with good industrial hygiene and safety procedures. Do not allow the crossing of the environment, the work place concentration limits for hazardous constituents.

After work, remove soiled clothing. Wash hands and face thoroughly after handling product, before eating, smoking and at the end of the working period. Do not eat, drink or smoke when working.

ENVIRONMENTAL EXPOSURE CONTROLS

Prevent entry into sewage collection system and watercourses.

Section 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state	solid
Colour	gray
Odour	odorless
Melting point/freezing point	
Pb50Sn50	183 / 215 °C
Pb60Sn40	183 / 238 °C
Sn63Pb37	183 °C
Sn60Pb40	183 / 190 °C
Pb70Sn30	183 / 257 °C
Boiling point or initial boiling point and boiling range	the temperature cannot be determined for the mixture, the boiling point for the component with the lowest boiling point: rosin > 200 °C
Flammability	not data
Lower and upper explosion limit	does not apply to solids
Flash point	does not apply to solids
Auto-ignition temperature	does not apply to solids
Decomposition temperature	> 300 ° decomposition temperature of rosin
pH	not applicable, the mixture is insoluble in water
Kinematic viscosity	does not apply to solids

Solubility	insoluble in water
Partition coefficient n-octanol/water (log value)	not applicable the mixture
Vapour pressure	not applicable
Density and/or relative density	
Pb50Sn50	8,87 g/cm ³
Pb60Sn40	9,28 g/cm ³
Pb70Sn30	9,72 g/cm ³
Sn63Pb37	8,40 g/cm ³
Sn60Pb40	8,50 g/cm ³
Relative vapour density	does not apply to solids
Particle characteristics	

diameter / [mm]	> 1,00	≤ 1,00 ; 2,50 >	≤ 2,50 ; 3,00 >	< 3,00 ; 6,00 >
tolerance / [mm]	±0,05	±0,10	±0,15	±0,30

9.2 Other safety information

No relevant physical and chemical parameters for safe use of the mixture

Section 10: Stability and reactivity

10.1 Reactivity

Under normal conditions of storage and use, hazardous decomposition products not be reactivity

10.2 Chemical stability

The product is stable under normal conditions.

10.3 Possibility of hazardous reactions

In contact with incompatible materials reacts violently with emission of heat.

10.4 Conditions to avoid

Extreme temperature and humidity.

10.5 Incompatible materials

Strong oxidizing agents, bases and acids (nitric acid, hot sulfuric acid, hydrogen sulfide), halogens, ammonium nitrate, chlorine trifluoride, hydrogen peroxide, sodium azide, zirconium, disodium acetylene, oxidants, concentrated nitric acid, picric acid and derivatives thereof

10.6 Hazardous decomposition products

None under normal conditions of use and storage.

Section 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

TOXICITY OF MIXTURE

Based on available data, the classification criteria are not met.

TOXICITY OF COMPOUNDS:

Tin

LD50 (oral, rat) > 2 000 mg/kg

LD50 (skin, rat) > 2 000 mg/kg

LC50 (inhalation, rat) > 4,75 mg/l/4h

In the form of dust or fumes is irritating. May cause shortness of breath, fever, general weakness, sweating, remitting without treatment (so-called smoke-induced fever metals). Dusts may cause mechanical irritation of the conjunctiva with tearing, pain, congestion.

Rosin

LD50 (oral, rat) 2800 mg/kg

LD50 (skin, rat) > 2 000 mg/kg

Lead

TCL₀ (inhalation, man) 0,01 mg/m³

TDL₀ (oral, rat) 790-1140 mg/kg

Lead compounds damage the peripheral and central nervous system and cause anemia, mainly due to inhibition of synthesis of hemoglobin red blood cells. Lead accumulates in the body, mainly in the bones, as well as in the kidney and other tissues. Acute symptoms of poisoning may occur after a few days of exposure to high concentrations of dust or fumes in excess of the airborne limit values. Symptoms of exposure include abdominal pain, diarrhea followed by constipation, loss of appetite, metallic taste in the mouth, nausea, vomiting, fatigue, insomnia, muscle weakness, joint pain, irritability, headache, dizziness, increased blood pressure. Anemia, kidney, liver, female gonads and central nervous system damage may occur. Lead compounds cause severe irritation and hypersensitivity of respiratory tract, shortness of breath, short breath and asthma symptoms. There is a danger of cumulative effects.

Reproductive toxicity:

Lead penetrates the placental barrier. Animal studies have shown teratogenic effects. As a result of excessive exposure to lead the pregnant women have neurological disorders in children.

The adverse effects of lead on reproduction have been demonstrated in studies in experimental animals as well as in humans, men and women. At the battery factory workers, with a mean lead exposure of 8.5 years, compared to the control group, increased frequency of pathological changes in semen.

ACUTE TOXICITY

based on available data, the classification criteria are not met

SKIN CORROSION/IRRITATION

based on available data, the classification criteria are not met

SERIOUS EYE DAMAGE/IRRITATION

based on available data, the classification criteria are not met

RESPIRATORY OR SKIN SENSITISATION

may cause an allergic skin reaction

GERM CELL MUTAGENICITY

based on available data, the classification criteria are not met

Evidence for the genotoxic effects of highly soluble inorganic lead compounds is contradictory and numerous studies have both positive and negative effects.

CARCINOGENICITY

based on available data, the classification criteria are not met

There is evidence that non-monatomic lead compounds may be carcinogenic and have been classified by IARC as possibly carcinogenic to humans (Group 2A). It is believed, however, that this classification does not apply to lead in a massive form, taking into account the very low bioavailability of metallic lead, and carcinogenicity studies on lead metal powder were negative. Epidemiological studies of workers exposed to inorganic lead compounds have shown a limited relationship with stomach cancer. IARC recognized that lead metal is probably carcinogenic to humans (Group 2B)

REPRODUCTIVE TOXICITY

May damage fertility. May damage the unborn child. May cause harm to breast-fed children.

Exposure to high concentrations of lead

and inorganic lead compounds leading to systemic absorption may cause undesirable effects of fertility in men and women, including adverse effects on sperm quality. The prenatal exposure to an inorganic lead compound is also associated with adverse effects on the development of the unborn child.

STOT-SINGLE EXPOSURE

based on available data, the classification criteria are not met

STOT-REPEATED EXPOSURE

Causes damage to central nervous system, blood and kidneys through prolonged or repeated exposure by inhalation or ingestion. Lead is a cumulative poison and can be absorbed by the lead cation, it is unlikely that inhalation and consumption of lead in the form of a mass of alloy.

ASPIRATION HAZARD

based on available data, the classification criteria are not met

HEALTH EFFECTS OF LOCAL EXPOSURE

Skin contact:

may cause redness, dry skin, burning sensation, burns (during soldering)

Eye contact:

may cause irritation, redness, tearing. Contamination of eyes results in lachrymation, pain, redness of conjunctivas with a risk of damage to cornea.

Ingestion:

may cause stomach disorders (nausea, vomiting, abdominal pain)

Inhalation:

may cause cough, headaches and dizziness

People with asthmatic, chronic respiratory diseases and pregnant women should not work with the product.

11.2 Information on other hazards

The mixture does not cause adverse health effects due to endocrine disrupting properties.

Section 12: Ecological information

12.1 Toxicity

No specific toxicity test results for the mixture

Toxicity of component:

Lead:

Lead compounds such as salts and oxides are toxic to aquatic organisms. The permissible lead concentration in wastewater for the heating industry is 0.1 mg / dm³; for other types of sewage 0.5 mg / dm³. The permissible lead level in the atmospheric air is 0.5 µg / m³, averaged for the calendar year.

Lead is a relatively corrosion-resistant metal that is chemically not very reactive. However, the reaction products of lead in the environment, especially soluble lead salts, are assessed as very toxic to aquatic organisms and drinking water supplies. Do not allow discharges of solutions containing lead or its compounds to surface water, groundwater, soil and sewage system.

Rosin:

Ecotoxicity to fish:

LC50 60.3 mg / l / 96h (Danio rerio, static method, OECD 203)

LL100 ≤ 10 mg / l / 24h (Danio rerio, semi-static method, OECD 203)

LL100 ≤ 10 mg / l / 96h (Danio rerio, semi-static method, OECD 203)

LL50 ≤ 10 mg / l / 96h (Danio rerio, semi-static method, OECD 203)

NOELR > = 1 mg / l / 96h (Danio rerio, semi-static method, OECD 203)

NOELR > = 1000 mg / l / 96h (Pimephales promelas, static method OECD 203)

LL50 > 1000 mg / l / 96h (Pimephales promelas, static method, OECD 203)

Ecotoxicity to aquatic invertebrates:

EL50 911 mg / l / 48h (Daphnia magna, OECD 202)

NOELR 750 mg / l / 48h (Daphnia magna, OECD 202)

Ecotoxicity to algae and aquatic plants:

NOELR > = 1000 mg / l / 72h (Pseudokirchnerella subcapitata, OECD 201, based on growth rate)

NOELR > = 1000 mg / l / 72h (Pseudokirchnerella subcapitata, OECD 201, based on biomass)

EL50 > 1000 mg / l / 72h (Pseudokirchnerella subcapitata, OECD 201, based on growth rate)

EL50 > 1000 mg / l / 72h (Pseudokirchnerella subcapitata, OECD 201, based on biomass)

Tin:

Short-term toxicity, fish 96 h

LC50 > 12.4 µg / L (NOEC 12.4 µg / L) Pimephales promelas (total amount of tin in solutions containing tin) - OECD 203.

Long-term toxicity, aquatic invertebrates 7 days:

LC50 (mortality) > 3200 µg / L,

EC50

(reproductive) 1303 µg / L (total amount of tin in solutions containing tin) - Daphnia magna - EPA 1002.0.

Toxicity to algae

EC50 (72 h):> 19.2 µg / L (total amount of tin in solutions containing tin) - Pseudokirchnerella subcapitata - OECD 201.

12.2 Persistence and degradability

Not biodegradable.

Rosin

Easily biodegradable in water

12.3 Bioaccumulative potential

Risk of accumulation of heavy metals in aquatic organisms.

Rosin BCF: 56,23

Tin has a low bioaccumulation capacity

12.4 Mobility in soil

Poorly mobile in soil and aquatic environment. Heavier than water, sinks to the bottom and remains here

Tin: Log Kd: 2.1 - 4.3L/kg

12.5 Results of PBT and vPvB assessment

Does not apply to inorganic substances

12.6. Endocrine disrupting properties

The mixture does not contain substances with endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605.

12.7. Other adverse effects

This product has no influence on the global warming or the ozone layer depletion.

Section 13: Disposal considerations

13.1 Waste treatment methods

The one introducing hazardous agents in packages is obliged to organize the collection system and ensure recycling including the recycling of hazardous agents packaging. The one introducing hazardous agents performs above duties on their own or by agreement with local government.

SPECIAL PRECAUTIONS:

Dispose of this material safely.

DISPOSAL METHODS FOR THE PRODUCT:

Do not dispose of the product together with domestic waste, do not release to sewage system. Do not allow contamination of groundwater and surface water. Recommended way of disposing of waste: recycling.

DISPOSAL METHODS FOR USED PACKAGING:

Contaminated packaging (after a thorough emptying) and unused product to pass to the designated recipient of waste.

16 03 03* inorganic waste containing dangerous substances

15 01 01 paper and cardboard packaging

15 01 02 plastic packaging

15 01 10* packaging containing residues of or contaminated by dangerous substances

Section 14: Transport information

14.1 UN number or ID number

Not applicable, product is not classified as hazardous in transportation.

14.2 UN proper shipping name

Not applicable.

14.3 Transport hazard class(es)

Not applicable.

14.4 Packing group

Not applicable.

14.5 Environmental hazards

Not classified as dangerous for the environment.

14.6 Special precautions for user

Not necessary.

14.7 Maritime transport in bulk according to IMO instruments

Not applicable.

Section 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

1. REGULATION (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC.

2. REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006 with later changes (adaptation to technical and scientific progress 1-20 ATP)

3. Commission Regulation (EC) No 790/2009 of 10 August 2009 amending, for the purposes of its adaptation to technical and scientific progress, Regulation (EC) No 1272/2008 of the European Parliament and of the Council on classification, labelling and packaging of substances and mixtures
4. Commission Regulation (EU) 2020/878 of 18 June 2020 amending Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH)
5. Directive 2008/98/EC of the European Parliament and of the Council of 19 November 2008 on waste and repealing certain Directives
6. European Parliament and Council Directive 94/62/EC of 20 December 1994 on packaging and packaging waste
7. European Agreement concerning the International Carriage of Dangerous Goods by Road (ADR), concluded in Geneva on 30 September 1957 (Dz. U. Nr 110, poz. 641).
8. European Commission Employment, Social Affairs & Inclusion Health and Safety at work – The Scientific Committee on Occupational Exposure Limits (SCOEL)

15.2 Chemical Safety Assessment

Chemical safety assessment of the mixture has not been performed.

Section 16: Other information

TRAININGS

Before commencing working with the product, the user should learn the Health & Safety regulations regarding handling chemicals, and in particular undergo proper workplace training.

EXPLANATION OF ABBREVIATIONS AND ACRONYMS

PEL	Permissible Exposure Limit
PBT	Persistent, Bioaccumulative and Toxic substance
vPvB	very Persistent, very Bioaccumulative substance
DNEL	Derived No Effect Level
PNEC	Predicted No Effect Concentration
LD50	lethal dose is an indication of the lethal toxicity of a given substance or type of radiation.
LC50	lethal concentration
CAS	unique numerical identifier assigned by Chemical Abstracts Service
WE	unique seven-digit identifier that was assigned to substances for regulatory purposes within the European Union by the European Commission
UN	The four-digit identification number of the material in the UN hazardous materials
NDS/MAK	The highest acceptable concentration
NDSch	The highest permissible instantaneous concentration
NDSP	Concentration value of toxic chemical or dust
BCF	bio-concentration factor
Repr. 1 A	Reproductive toxicity, Hazard Category 1A
H360FD	May damage fertility. May damage the unborn child.

[In accordance with COMMISSION REGULATION (EU) 2020/878 of 18 June 2020 amending Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (Official Journal of the European Union No L.203 z 26.06.2020)]

Lact.	Reproductive toxicity, Additional category, Effects on or via lactation
H362	May cause harm to breast-fed children
Skin Sens	Sensitization, Skin hazard category 1
H317	May cause an allergic skin reaction
STOT RE1	Specific target organ toxicity — Repeated exposure, Hazard Category 1
H372	Causes damage to central nervous system, blood and kidneys through prolonged or repeated exposure by inhalation or ingestion

Lead is subject to restrictions resulting from Annex XVII to REACH, pos. 30. Lead is on the candidate list of substances of very high concern (SVHCs) - date of entry 27/06/2018

The information above is based on a current available data concerning the product, but also on the experience and knowledge of the producer in this field. It is neither a quality description of the product nor a guarantee of particular features. It is to be treated as aid to safety in transport, storage and usage of the product. That does not free the user from the responsibility for improper usage of the information above and also of improper compliance with the legal norms in the field.

Other data Classification of the substances based on the information from ECHA. Classification of mixture was prepared based on the data concerning the contents of dangerous components using calculation method based on the Regulation (EC) No 1272/2008 (CLP).

The information contained in the SDS is to describe the product only in terms of safety requirements. The user is the one responsible for creating conditions for the safe use of the product, and assumes the responsibility for the consequences resulting from improper use of this product.

card points update: 8.1, 15.1