**EN:** This Datasheet/Document is presented by the manufacturer.

Please visit our website for pricing and availability at www.hestore.hu.

# UT673A/UT675A NEW
## Battery Testers

**UT673A/UT675A battery testers can be used to analyze the battery health of automobile batteries, suitable for battery capacities from 3 to 250Ah. These CE certified testers can rapidly and accurately detect common battery faults. UT675A also includes USB communication and built-in printer for report generation.**

- 12V cranking lead acid battery test
- 12/24V charging or cranking system test
- Displays battery capacity, voltage, resistance and life
- Four-terminal Kelvin test
- 10 types of battery standards
- Language option (Chinese/English)
- Test without battery disassembly
- LED color indication (UT673A)
- Printing of test reports (UT675A)
- USB data transfer (UT675A)

| Specifications | Range | UT673A | UT675A |
|---|---|---|---|
| **Certificates** | **CE, FCC, UKCA** | | |
| 12V battery test | 7~16V DC | √ | √ |
| 12V/24V cranking system test | 7~30V DC | √ | √ |
| 12V/24V charging system test | 7~30V DC | √ | √ |
| Battery type | Lead acid battery, AGM flat plate battery, AGM spiral battery, GEL battery, EFB battery | | |
| Battery capacity | 3~250Ah | √ | √ |
| Battery standards and range | CCA: 40~2000; BCI: 40~2000; CA: 40~2000; MCA: 40~2000; JIS: 26A17~245H52; DIN: 40~1400; IEC: 40~1400; EN: 40~2000; SAE: 40~2000; AH: 3~250AH | | |
| USB communication | | | √ |
| Printing function | | | √ |

| Features |
|---|
| Over voltage protection |
| Reverse connection protection |
| A prompt of poor contact |
| Battery status display |
| Battery life display |
| Battery capacity display |
| Battery internal resistance display |

| Characteristics | |
|---|---|
| Standard accessories | UT673A: English manual; UT675A: English manual, USB cable, printing paper 3 rolls, carrying bag |
| Power | None, powered by external source |
| Display | 128 x 64 black and white lattice |
| Product size | UT673A: 76 x 22 x 142mm; UT675A: 95 x 47 x 183mm |
| Product net weight | UT673A: 264g; UT675A: 413g |
| Standard individual packing | UT673A: Blister; UT675A: Gift box, carrying bag |
| Standard quantity per carton | UT673A: 30pcs; UT675A: 10pcs |
| Standard carton measurement | UT673A: 650 x 380 x 350mm; UT675A: 590 x 470 x 260mm |
| Standard carton gross weight | UT673A: 13.6kg; UT675A: 9.3kg |



UT673A



UT675A