EN: This Datasheet/Document is presented by the manufacturer.

Please visit our website for pricing and availability at www.hestore.hu.

ANSMANN ENERGY GMBH – Industriestraße 10 – D–97959 Assamstadt GERMANY
Tel. +49 (0) 6294 / 4204 – 0 – Fax +49 (0) 6294 / 4204 – 44 / 43 – E–mail: info@ansmann.de

ALCS 2–24 A – Plug–in charger for lead acid batteries 2–24V



Plug–in charger for lead acid batteries 2–24 V from 2–24 Ah. 3 year warranty.

Plug–in charger for maintenance free lead acid batteries 2–24 V from 2–24 Ah. Adjusts automatically to the voltage of the lead acid battery to be charged. The corresponding LED displays the voltage of the battery. With IU–characteristic curve. Overcharging protection and trickle charge. Protection against short–circuit and reverse–connect . Includes crocodile clips to contact the rechargeable lead acid battery. The unit is suitable for stand–by as well as parallel operation of lead acid/sealed lead acid batteries.

Art.–Nr.: 9564006

Dimensions: 106 x 58 x 51

Weight: 520 g

nom. voltage	*final voltage*	*charg. current*	*charg. time*
2 V	2,3 V	900 mA	40min/500mAh
6 V	6,9 V	700 mA	50min/500mAh
12 V	13,8 V	600 mA	60min/500mAh
24 V	27,6 V	300 mA	120min/500mAh

ANSMANN ENERGY GMBH – Industriestraße 10 – D–97959 Assamstadt GERMANY
Tel. +49 (0) 6294 / 4204 – 0 – Fax +49 (0) 6294 / 4204 – 44 / 43 – e–Mail: info@ansmann.de

ALCS 2–24 A – Plug–in charger for lead acid batteries 2–24V

