



EN: This Datasheet is presented by the manufacturer.

Please visit our website for pricing and availability at www.hestore.hu.

UT10A

Modern Pocket-Size Digital Multimeters



UL/cUL Pending

Registered Design No.: 0412182.2M002

SPECIFICATIONS

Basic Functions	Range	Best Accuracy
DC Voltage	400mV/4V/40V/300V	$\pm (0.8\%+1)$
AC Voltage	4V/40V/400V/300V	$\pm (1.2\%+3)$
Resistance	400 Ω /4k Ω /40k Ω /400k Ω /4M Ω /40M Ω	$\pm (1\%+2)$
Capacitance	4nF/40nF/400nF/4 μ F/40 μ F/200 μ F	$\pm (4\%+3)$
Frequency	10Hz/100kHz	$\pm (0.5\%+3)$
Special Functions		
Auto Ranging	✓	
Duty Cycle	0.1%~99.9%	
Diode	✓	
Continuity Buzzer	✓	
Relative Mode	✓	
Data Hold	✓	
Full Icon Display	✓	
Sleep Mode	✓	
Low Battery Display	✓	
Input Impedance for DC Voltage Measurement	10M Ω	
Max. Display	3999	

GENERAL CHARACTERISTICS

Power	3V Button Battery (CR2032)
LCD Size	43 x 22 mm
Product Colour	Red and Grey
Product Net Weight	62g
Product Size	58 x 108 x 12mm
Standard Accessories	Test Lead, Battery, English Manual, Vinyl Holder
Standard Individual Packing	Blister
Standard Quantity Per Carton	90 pcs
Standard Carton Measurement	Around 545 x 305 x 425mm (0.071CBM Per Standard Carton)
Standard Carton Gross Weight	Around 11.25kg