



EN: This Datasheet/Document is presented by the manufacturer.

Please visit our website for pricing and availability at www.hestore.hu.


GT Series

SAMXON®

+105°C, High Ripple Current(高紋波), Long Life Assurance(長壽命), Low Impedance(低阻抗品)

FEATURES


- 1. Low impedance for high frequency
- 2. Long life:4000~10000 hours at 105°C



SPECIFICATIONS

Item	Performance Characteristics								
Operating Temperature Range	-40 to +105°C								
Rated Working Voltage Range	6.3 to 100V								
Nominal Capacitance Range	15 to 18000μF								
Capacitance Tolerance	±20% (120Hz, +20°C)								
Leakage Current	I≤0.01CV or 3(μA) (after 2 minutes,whichever is greater) I=Leakage Current(μA) C=Nominal Capacitance(μF) V=Rated Voltage(V)								
Dissipation Factor tan δ (120Hz, +20°C)	Working Voltage (V)	6.3	10	16	25	35	50	63	100
	tan δ (max.)	0.22	0.19	0.16	0.14	0.12	0.10	0.09	0.08
	For capacitance value>1000 μF,add 0.02 per another 1000 μF								
Low Temperature Characteristics	Impedance ratio max. at 120Hz								
	Rated Voltage(V)	6.3	10	16	25	35	50	63	100
	Z-25°C / Z+20°C	4	3	2	2	2	2	2	2
	Z-40°C / Z+20°C	8	6	4	3	3	3	3	3
High Temperature Loading	Test conditions				Post test requirements at +20°C				
	Duration :	φD	5 ~ 6.3	8~10	12.5 ~	Leakage current : ≤ Initial specified value			
		6.3~10WV	4000h	6000h	8000h	Cap. change : within ±25% of initial measured value			
		16~100WV	5000h	7000h	10000h	tan δ : ≤ 200% of initial specified value			
	Ambient temp. : +105°C								
	Applied voltage : Rated DC working voltage with max. ripple current								
Shelf Life	Test conditions				Post test requirements at +20°C				
	Duration : 1000 hours				Same limits for high temperature loading				
	Ambient temp. : +105°C								
	Applied voltage : (None)								
Others	JIS C - 5101 (IEC 60384)								

CASE SIZE TABLE



φD	6.3	8(L<20) 8(L≥20)	10	12.5	16~18	
F	2.5	3.5	5.0	5.0	7.5	
φd	0.5		0.6		0.8	
α	(L<20) 1.5		(L≥20) 2.0			
β	(D<20) 0.5		(D≥20) 1.0			

RIPPLE CURRENT MULTIPLIER

Temperature Coefficient						Frequency Coefficient						
Temperature(°C)	~ 55	60	70	85	105	Cap(μF)	Freq.(Hz)	50	120	300	1K	10K ~
Factor	2.23	2.17	2.00	1.75	1.00	6.3 ~ 33		0.45	0.55	0.70	0.90	1.00
						39 ~ 330		0.60	0.70	0.85	0.95	1.00
						390 ~ 1000		0.65	0.75	0.90	0.98	1.00
						1200 ~ 18000		0.75	0.80	0.95	1.00	1.00

GT Series

SAMXON®

+105°C, High Ripple Current(高紋波), Long Life Assurance(長壽命), Low Impedance(低阻抗品)

DIMENSIONS										
Voltage (Code)		6.3V (0J)			10V (1A)			16V (1C)		
Cap.(μF)	Code	Case Size	Impedance	Ripple Current	Case Size	Impedance	Ripple Current	Case Size	Impedance	Ripple Current
120	127							6.3 x 11	0.220	340
150	157									
220	227				6.3 x 11	0.220	340			
330	337	6.3 x 11	0.220	340				8 x 12	0.130	640
470	477				8 x 12	0.130	640	8 x 16	0.087	840
								10 x 12.5	0.080	865
680	687	8 x 12	0.130	640	8 x 16	0.087	840	8 x 20	0.069	1050
					10 x 12.5	0.080	865	10 x 16	0.060	1210
820	827	10 x 12.5	0.080	865						
1000	108	8 x 16	0.087	840	8 x 20	0.069	1050	10 x 20	0.046	1400
					10 x 16	0.060	1210			
1200	128	8 x 20	0.069	1050	10 x 20	0.046	1400	10 x 25	0.042	1650
		10 x 16	0.060	1210						
1500	158	10 x 20	0.046	1400	10 x 25	0.042	1650	10 x 30	0.031	1910
								12.5 x 20	0.035	1900
2200	228	10 x 25	0.042	1650	10 x 30	0.031	1910	12.5 x 25	0.027	2230
					12.5 x 20	0.035	1900			
2700	278	10 x 30	0.031	1910				12.5 x 30	0.024	2650
								16 x 20	0.027	2530
3300	338	12.5 x 20	0.035	1900	12.5 x 25	0.027	2230	12.5 x 35	0.020	2880
					12.5 x 30	0.024	2650	12.5 x 40	0.017	3350
3900	398	12.5 x 25	0.027	2230	16 x 20	0.027	2530	16 x 25	0.021	2930
								16 x 20	0.026	2860
4700	478	12.5 x 30	0.024	2650	12.5 x 35	0.020	2880	16 x 30	0.017	3450
								18 x 25	0.019	3140
5600	568	12.5 x 35	0.020	2880	12.5 x 40	0.017	3350	16 x 35	0.015	3610
		16 x 20	0.027	2530	16 x 25	0.021	2930	18 x 30	0.015	4170
					18 x 20	0.026	2860			
6800	688	12.5 x 40	0.017	3350	16 x 30	0.017	3450	16 x 40	0.013	4080
		16 x 25	0.021	2930	18 x 25	0.019	3140			
		18 x 20	0.026	2860						
8200	828	16 x 30	0.017	3450	16 x 35	0.015	3610	18 x 35	0.014	4220
					18 x 30	0.015	4170			
10000	109	16 x 35	0.015	3610	16 x 40	0.013	4080	18 x 40	0.012	4280
		18 x 25	0.019	3140	18 x 35	0.014	4220			
12000	129	16 x 40	0.013	4080	18 x 40	0.012	4280			
		18 x 30	0.015	4170						
15000	159	18 x 35	0.014	4220						
18000	189	18 x 40	0.012	4280						

Maximum Allowable Ripple Current (mA rms) at 105°C 100KHz

Maximum Impedance (Ω) at 20°C 100KHz

Case Size φD x L(mm)

GT

Miniature Aluminum Electrolytic Capacitors

GT Series

SAMXON®

+105°C, High Ripple Current(高紋波), Long Life Assurance(長壽命), Low Impedance(低阻抗品)

DIMENSIONS

Voltage (Code)		25V (1E)			35V (1V)			50V (1H)		
Cap.(μF)	Code	Case Size	Impedance	Ripple Current	Case Size	Impedance	Ripple Current	Case Size	Impedance	Ripple Current
56	566				6.3 x 11	0.220	340	6.3 x 11	0.300	295
100	107	6.3 x 11	0.220	340				8 x 12	0.170	555
120	127							8 x 15	0.120	730
150	157				8 x 12	0.130	640	10 x 12.5	0.120	760
220	227	8 x 12	0.130	640	8 x 16	0.087	840	10 x 16	0.084	1050
					10 x 12.5	0.080	865			
330	337	8 x 16	0.087	840	10 x 16	0.060	1210	10 x 25	0.055	1440
		10 x 12.5	0.080	865						
470	477	8 x 20	0.069	1050	10 x 20	0.046	1400	10 x 30	0.043	1690
		10 x 16	0.060	1210				12.5 x 20	0.045	1660
560	567				10 x 25	0.042	1650	12.5 x 25	0.034	1950
680	687	10 x 20	0.046	1400	10 x 30	0.031	1910	12.5 x 30	0.030	2310
					12.5 x 20	0.035	1900			
820	827	10 x 25	0.042	1650				12.5 x 35	0.025	2510
								16 x 20	0.034	2210
1000	108	10 x 30	0.031	1910	12.5 x 25	0.027	2230	12.5 x 40	0.021	2920
		12.5 x 20	0.035	1900				16 x 25	0.025	2555
								18 x 20	0.036	2490
1200	128				12.5 x 30	0.024	2650	16 x 30	0.022	3010
					16 x 20	0.027	2530	18 x 25	0.026	2740
1500	158	12.5 x 25	0.027	2230	12.5 x 35	0.020	2880	16 x 35	0.019	3150
1800	188	12.5 x 30	0.024	2650	12.5 x 40	0.017	3350	16 x 40	0.016	3710
		16 x 20	0.027	2530	16 x 25	0.021	2930	18 x 30	0.021	3635
					18 x 20	0.026	2860			
2200	228	12.5 x 35	0.020	2880	16 x 30	0.017	3450	18 x 35	0.017	3680
		18 x 20	0.026	2860	18 x 25	0.019	3140			
2700	278	12.5 x 40	0.017	3350	16 x 35	0.015	3610	18 x 40	0.014	3800
		16 x 25	0.021	2930	18 x 30	0.015	4170			
3300	338	16 x 30	0.017	3450	16 x 40	0.013	4080			
		18 x 25	0.019	3140	18 x 35	0.014	4220			
3900	398	16 x 35	0.015	3610	18 x 40	0.012	4280			
		18 x 30	0.015	4170						
4700	478	16 x 40	0.013	4080						
		18 x 35	0.014	4220						
5600	568	18 x 40	0.012	4280						

Maximum Allowable Ripple Current (mA rms) at 105°C 100KHz
Maximum Impedance (Ω) at 20°C 100KHz

Case Size φD x L(mm)

GT Series

SAMXON®

+105°C, High Ripple Current(高紋波), Long Life Assurance(長壽命), Low Impedance(低阻抗品)

DIMENSIONS									
Voltage (Code)		63V (1J)			100V (2A)				
Cap.(μF)	Code	Case Size	Impedance	Ripple Current	Case Size	Impedance	Ripple Current		
15	156				6.3 x 11	1.200	115		
27	276				8 x 12	0.630	232		
33	336	6.3 x 11	1.200	115					
39	396				8 x 16	0.450	300		
47	476				10 x 12.5	0.430	288		
56	566	8 x 12	0.630	232	8 x 20	0.330	362		
68	686				10 x 16	0.310	357		
82	826	8 x 16	0.450	300	10 x 20	0.210	466		
		10 x 12.5	0.430	288					
100	107				10 x 25	0.200	531		
120	127	8 x 20	0.330	362	10 x 30	0.150	663		
		10 x 16	0.310	357	12.5 x 20	0.160	690		
180	187	10 x 20	0.210	466	12.5 x 25	0.120	784		
220	227	10 x 25	0.200	531	12.5 x 30	0.100	905		
					16 x 20	0.091	1040		
270	277	10 x 30	0.150	663	12.5 x 35	0.083	1050		
		12.5 x 20	0.160	690	16 x 25	0.073	1250		
330	337	12.5 x 25	0.120	784	12.5 x 40	0.071	1180		
					18 x 20	0.080	1240		
390	397				16 x 30	0.054	1570		
					18 x 25	0.057	1490		
470	477	12.5 x 30	0.100	905	16 x 35	0.045	1790		
		16 x 20	0.091	1040	18 x 30	0.047	1630		
560	567	12.5 x 35	0.083	1050	16 x 40	0.040	2020		
		16 x 25	0.073	1250					
680	687	12.5 x 40	0.071	1180	18 x 35	0.040	1790		
		18 x 20	0.080	1240					
820	827	16 x 30	0.054	1570	18 x 40	0.360	2330		
		18 x 25	0.057	1490					
1000	108	16 x 35	0.045	1790					
		18 x 30	0.047	1630					
1200	128	16 x 40	0.040	2020					
		18 x 35	0.040	1790					
1500	158	18 x 40	0.036	2330					

Maximum Allowable Ripple Current (mA rms) at 105°C 100KHz

Maximum Impedance (Ω) at 20°C 100KHz

Case Size φD x L(mm)

GT

Miniature Aluminum Electrolytic Capacitors