EN: This Datasheet/Document is presented by the manufacturer.

Please visit our website for pricing and availability at www.hestore.hu.

LUCKY LIGHT

LL-304BC2E-B4-1AC


DATA SHEET

QC: ENG: Prepared By:

Features

- High intensity
- Standard T-1 diameter type package
- Small viewing angle
- General purpose leads
- Reliable and rugged

Package Dimension:



Part NO.	Lens Color	Source Color
LL-304BC2E-B4-1AC	Water Clear	Super Bright Blue

Notes:

1. All dimensions are in millimeters (inches).
2. Tolerance is ±0.25(.010")mm unless otherwise noted.
3. Protruded resin under flange is 1.0mm(.04") max
4. Lead spacing is measured where the leads emerge from the package.
5. Specifications are subject to change without notice
6. Caution in ESD:
   Siatic Electricity and surge damages the LED. lt is recommend to use a wrist band or anti-electrostatic glove when handling the LED.All devices, equipment and machinery must be properly grounded.

Absolute Maximum Ratings at Ta=25℃

Parameter	MAX.	Unit
Power Dissipation	100	mW
Peak Forward Current (1/10 Duty Cycle, 0.1ms Pulse Width)	100	mA
Continuous Forward Current	35	mA
Derating Linear From 50℃	0.4	mA/℃
Reverse Voltage	5	V
Operating Temperature Range	-40℃ to +80℃	
Storage Temperature Range	-40℃ to +80℃	
Lead Soldering Temperature [4mm(.157") From Body]	260℃ for 5 Seconds	

Electrical Optical Characteristics at Ta=25℃

Parameter	Symbol	Min.	Typ.	Max.	Unit	Test Condition
Luminous Intensity	Iv	1000	1500	---	mcd	I_F=20mA (Note 1)
Viewing Angle	$2\theta_{1/2}$	---	20	---	Deg	(Note 2)
Peak Emission Wavelength	λ p	463	468	473	nm	I_F=20mA
Dominant Wavelength	λ d	460	470	480	nm	I_F=20mA (Note 3)
Spectral Line Half-Width	$\triangle\lambda$	---	25	---	nm	I_F=20mA
Forward Voltage	V_F	2.8	3.6	4.0	V	I_F=20mA
Reverse Current	I_R	---	---	100	μA	V_R=5V

Note:

1. Luminous intensity is measured with a light sensor and filter combination that approximates the CIE eye-response curve.
2. $\theta_{1/2}$ is the off-axis angle at which the luminous intensity is half the axial luminous intensity.
3. The dominant wavelength(λ d) is derived from the CIE chromaticity diagram and represents the single wavelength which defines the color of the device.

Typical Electrical / Optical Characteristics Curves
(25℃ Ambient Temperature Unless Otherwise Noted)

