



EN: This Datasheet/Document is presented by the manufacturer.

Please visit our website for pricing and availability at www.hestore.hu.

Features:

·Protections: Short circuit/Overload/Over Voltage/Over

Temperature

·IP protection standard: IP67

·Efficiency: 75%

·100% full load burn-in test

·Storage temperature: -40-80°C

·Operating temperature: -25-45°C

·Certificate: CE, ROHS



SPECIFICATION: ZLV-15-12		
Input Voltage (VAC)		90-250VAC
Input Current		0.13Amax@220VAC
Input Frequency (Hz)		47 to 63 Hz
Output Voltage (VDC)		12VDC±0.5V
The sum output current(A)		1.25A
Max output Power (W)		15W
Short Circuit Protection		Auto recovery
Overload Protection		20% exceed is allowing
Over-voltage Protection		≤255V
Thermal Protection		≤80°C
Temperature rising		≤28°C
CE	CE Safety Standard	Compliance to EN61347-1:2001 / EN61347-2-11.2001
	EMI conduction & radiation	Compliance to EN55015,EN61547
	Harmonic Current	Compliance to EN61000-3-2,-3
Others	Dimension/Weight	160*30*20MM/210g
	Packing/Carton Size	50pcs/carton / 34*24*18.5cm
	Cable	0.75sq.mm. VDE wire 200mm
	Housing Material	Aluminum