



EN: This Datasheet/Document is presented by the manufacturer.

Please visit our website for pricing and availability at www.hestore.hu.

Specification of Piezo Buzzer

Customer	
Customer P/O	
Bestar Model Name	BPT1412XH7.5
Product No.	040200
Issue No.	BS/TEP01.011A
Issue Date	01/10/16

Approval:

- 1.Ordering Information
- 2.Technical Terms
- 3.Drawing
- 4.Reliability Test
- 5.Appearance
- 6.Packing



BESTAR ELECTRONICS INDUSTRY CO.,LTD
TianAn Industry Park4/F,Site B ChangZhou New District
Tel:86-519-5103228
Fax:86-519-5131010
Http:www.be-star.com
E-Mail:bestarco@pub.cz.jsinfo.net

BPT1412XH7.5

1.Ordering Information

BPT1412XH7.5

BPT: Bestar Piezo Transducer

14 : Buzzer Size - diameter=14mm

12: Rated voltage 12v X: With built-in circuit


H7.5:Height 7.5



2.Technical Terms

ITEM	UNIT	SPECIFICATIONS
Rated Voltage	VDC	12
Operation Voltage	VDC	3-16
a)Rated Current	mA	max7
a)Sound Output at 10cm	dB	min80
a)Resonant Frequency	Hz	4000 ± 500
Operating Temperature	°C	-20...+70
Storage Temperature	°C	-30...+80
Weight	g	1
a)Value Applying Rated Voltage (DC)		

★.Standard Output Measurement Setup



DIS.		DATE		Page:1 of 4
CHEC.		DATE		3rd angle projection
APPR.		DATE		
BESTAR ELECTRONICS INDUSTRY CO.,LTD TianAn Industry Park 4/F,Site B ChangZhou New District E-Mail:bestarco@ pub.cz.jsinfo.net Http:www.be-star.com				

BPT1412XH7.5


Piezo Buzzer

DRG NO
BS/TEP01.011A

BPT1412XH7.5

3. Drawing

Tolerance: ± 0.2



DIS.		DATE		Page:2 of 4	BPT1412XH7.5
CHEC.		DATE		3rd angle projection	Piezo Buzzer
APPR.		DATE			DRG NO BS/TEP01.011A



BESTAR ELECTRONICS INDUSTRY CO., LTD
TianAn Industry Park 4/F, Site B ChangZhou New District
E-Mail: bestarco@pub.cz.jsinfo.net Http: www.be-star.com

BPT1412XH7.5

4. Reliability test

4.1 high temperature test

Temperature +80° C
Duration 96hrs

4.2 low temperature test


Temperature -30° C
Duration 96hrs

4.3 life test in normal temperature

Power supply rated voltage
Duration 1000hrs


4.4 temperature cycle test

Cycles 5



4.5 Humidity cycle test

Cycles 5



all these tests above should be measured after leaving normal temperature for 2hrs.

4.6 Drop test

Height 70cm
(to 10mm thickness woodenboard)
Direction 3

4.7 Solderability

Temperature $245 \pm 5^{\circ} \text{C}$
Duration $3 \pm 0.5 \text{sec}$

4.8 Solder Heat Resistance

Temperature $260 \pm 5^{\circ} \text{C}$
Duration 20sec

Notice: All specification must be satisfied in this condition.



DIS.		DATE		Page:3 of 4	BPT1412XH7.5
CHEC.		DATE		3rd angle projection	Piezo Buzzer
APPR.		DATE			DRG NO BS/TEP01.011A
 BESTAR ELECTRONICS INDUSTRY CO.,LTD TianAn Industry Park 4/F,Site B ChangZhou New District E-Mail:bestarco@ pub.cz.jsinfo.net Http:www.be-star.com					

BPT1412XH7.5

5. Appearance

Appearance : without any obstacle to normal operation : damages, cracks, rusts and distortions,ect.

6. Packing



- 1)100pcs/tray
- 2)30tray/carton
- 3)3000 pcs/carton in total
- 4)carton size 50x27x26cm

DIS.		DATE		Page:4 of 4 3rd angle projection
CHEC.		DATE		
APPR.		DATE		



BESTAR ELECTRONICS INDUSTRY CO.,LTD
TianAn Industry Park 4/F,Site B ChangZhou New District
E-Mail:bestarco@ pub.cz.jsinfo.net Http:www.be-star.com

BPT1412XH7.5

Piezo Buzzer

**DRG NO
BS/TEP01.011A**