

EN: This Datasheet is presented by the manufacturer.

Please visit our website for pricing and availability at www.hestore.hu.

## PRODUCT DATASHEET

# NiMH Battery Charger (CHEUF)

### **European Region**

Download Instructions (multilingual)

Page 01 | Page 02

### **INNOVATIVE**

- Unique and modern design
- Charges AA, AAA, C, D and 9V NiMH rechargeable batteries.



## SMART

- LCD panel indicating charging status
- · LED indicator for 9V





**Universal Charger** 

### POWERFUL

3-5 hour charging time



### **Before Using Your Charger:**

Please read all instructions and cautionary markings on the battery charger, batteries, and device.

### **Product Detail:**

Designation: Universal Charger - European Region

Color: Black and Silver

Charging Current: 2 or 4 "AA-C-D" 650mA

2 or 4 "AAA" 400mA 1 or 2 "9V" 17mA

Trickle Charge: "AA-C-D" 50mA

"AAA" 25mA

Charging Times: (estimated)

\*AA 2650 mAh AAA 1000 mAh

Battery	Capacity	Estimated
(NiMH)	(mAh)	(time)
AA	2500-2650	4.5-5.0 hrs
AA	1700-2400	3.0-4.5 hrs
AAA	850-1000	2.5-3.0 hrs
C/D	2500	4.5 hrs
9V	175	12.5 hrs

Shutoff Mechanism: Delta V Detection and Timer Control

Delta V Detection 5mV per cell for "AA-AAA-C-D" Max Timer Control 2 or 4 "AA-C-D" 5 hours

2 or 4 "AA" 3.5 hours

Charger Input: DC 12V, 600mA

**AC Adapter I nput:** 100-240V AC 50/60Hz 190mA

AC Adapter Output: DC 12V, 600mA Weight (charger): 322 grams

**Dimensions (mm):** 65 x 180 x 130 (H x L x W)

Safety Features: Delta V Charging Cut Off

Short Circuit and Reverse Polarity Protection

Safety Timer to Prevent Over Charge

**Bad Battery Detection** 

**NOTE:** Batteries must be charged in pairs with the exception of "9V" batteries that can be charged individually

### **Important Notice**

This datasheet contains information specific to products manufactured at the time of its publication.

© Energizer

Contents herein do not constitute a warranty.