HESTORE.HU
elektronikai alkatrész áruház

EN: This Datasheet is presented by the manufacturer.

Please visit our website for pricing and availability at www.hestore.hu.

170 Series Digital Multimeters

FLUKE®



Fluke 179



Fluke 177



Fluke 175

Lifetime Warranty!

CAT III 1000V
CAT IV 600V

On all inputs

LISTED UL · CSA · TÜV PRODUCT SERVICE GS · VDE · True RMS

Versatile meters for field service or bench repair

These meters have the features needed to find most electrical, electro-mechanical and heating and ventilation problems. They are simple to use and have significant improvements over Fluke's original 70 Series like, True-RMS, more measurement functions, conformance to the latest safety standards, and a much larger display that's easier to view.

Features

	175	177	179
True-RMS measurements	AC	AC	AC
Digital display counts, updates 4 times per second	6000	6000	6000
Display backlight		●	●
Analog bargraph / segments, updates 40 times per second	33-segments	33-segments	33-segments
Auto and Manual ranging	●	●	●
Display Hold and AutoHOLD®	●	●	●
Min-Max-Average recording mode with Min/Max Alert	●	●	●
Temperature readings (bead thermocouple probe included)			●
Smoothing mode allows filtering of rapidly changing inputs	●	●	●
Audible continuity and diode test	●	●	●
Test lead alert	●	●	●
Unsafe voltage alert warns for voltages above 30V	●	●	●
Low battery indication	●	●	●
Ergonomic case with integrated holster	●	●	●
Easy battery exchange without opening the complete case	●	●	●
Selectable sleep mode preserves battery life	●	●	●

Specifications

(Check the Fluke web for detailed specifications)

Functions	Maximum	Max. resolution	175	177	179
Voltage DC	1000V	0.1mV	±(0.15%+2)	±(0.09%+2)	±(0.09%+2)
Voltage AC	1000V	0.1mV	±(1.0%+3)	±(1.0%+3)	±(1.0%+3)
Current DC	10A	0.01mA	±(1.0%+3)	±(1.0%+3)	±(1.0%+3)
Current AC	10A	0.01mA	±(1.5%+3)	±(1.5%+3)	±(1.5%+3)
Resistance	50MΩ	0.1Ω	±(0.9%+1)	±(0.9%+1)	±(0.9%+1)
Capacitance	10000µF	1nF	±(1.2%+2)	±(1.2%+2)	±(1.2%+2)
Frequency	100kHz	0.01Hz	±(0.1%+1)	±(0.1%+1)	±(0.1%+1)
Temperature	-40°C/+400°C	0.1°C			±(1.0%+10)

Accuracies are best accuracies for each function

Battery Life: Alkaline, 200 hrs typical
Size (HxWxD): 190 mm x 85 mm x 45 mm
Weight: 0.42 kg
Lifetime Warranty

Recommended Accessories



i400



C90



TLK-220



SV225



i410-i1010

Included Accessories

Test leads with 4 mm lantern tips and protective cap, installed 9V battery and users manual. The 179 also includes the 80BK temperature probe.

Ordering Information

Fluke 175	True RMS Multimeter
Fluke 177	True RMS Multimeter
Fluke 179	True RMS Multimeter
Fluke 179/EDA Kit	Electronics Combo Kit
Fluke 179/MAG Kit	Industrial Combo Kit

10342-eng rev. 06