EN: This Datasheet/Document is presented by the manufacturer.

Please visit our website for pricing and availability at www.hestore.hu.

MJL21193, MJL21194

Preferred Device

Silicon Power Transistors

The MJL21193 and MJL21194 utilize Perforated Emitter technology and are specifically designed for high power audio output, disk head positioners and linear applications.

Features

- Total Harmonic Distortion Characterized
- High DC Current Gain –

$$h_{FE} = 25 \text{ Min } @ I_C = 8 \text{ Adc}$$

- Excellent Gain Linearity
- High SOA: 2.25 A, 80 V, 1 Second
- Pb−Free Packages are Available*

ON Semiconductor®

http://onsemi.com

16 AMPERE COMPLEMENTARY SILICON POWER TRANSISTORS 250 VOLTS, 200 WATTS

MAXIMUM RATINGS

Rating	Symbol	Value	Unit
Collector−Emitter Voltage	V_{CEO}	250	Vdc
Collector−Base Voltage	V_{CBO}	400	Vdc
Emitter−Base Voltage	V_{EBO}	5	Vdc
Collector−Emitter Voltage − 1.5 V	V_{CEX}	400	Vdc
Collector Current − Continuous Peak (Note 1)	I_C	16 30	Adc
Base Current − Continuous	I_B	5	Adc
Total Power Dissipation @ T_C = 25°C Derate above 25°C	P_D	200 1.43	W W/°C
Operating and Storage Junction Temperature Range	T_J, T_{stg}	−65 to +150	°C

THERMAL CHARACTERISTICS


Characteristic	Symbol	Max	Unit
Thermal Resistance, Junction−to−Case	$R_{\theta JC}$	0.7	°C/W

Stresses exceeding Maximum Ratings may damage the device. Maximum Ratings are stress ratings only. Functional operation above the Recommended Operating Conditions is not implied. Extended exposure to stresses above the Recommended Operating Conditions may affect device reliability.


1. Pulse Test: Pulse Width = 300 μs, Duty Cycle ≤2%

*For additional information on our Pb−Free strategy and soldering details, please download the ON Semiconductor Soldering and Mounting Techniques Reference Manual, SOLDERRM/D.

MARKING DIAGRAM



TO−3PBL (TO−264) CASE 340G



x = 3 or 4
A = Assembly Location
YY = Year
WW = Work Week
G = Pb−Free Package

ORDERING INFORMATION

Device	Package	Shipping†
MJL21193	TO−264	25 Units / Rail
MJL21193G	TO−264 (Pb−Free)	25 Units / Rail
MJL21194	TO−264	25 Units / Rail
MJL21194G	TO−264 (Pb−Free)	25 Units / Rail

†For information on tape and reel specifications, including part orientation and tape sizes, please refer to our Tape and Reel Packaging Specifications Brochure, BRD8011/D.

Preferred devices are recommended choices for future use and best overall value.

© Semiconductor Components Industries, LLC, 2007

ELECTRICAL CHARACTERISTICS (T_C = 25°C unless otherwise noted)

Characteristic	Symbol	Min	Typ	Max	Unit
OFF CHARACTERISTICS					
Collector−Emitter Sustaining Voltage (I_C = 100 mAdc, I_B = 0)	$V_{CEO(sus)}$	250	–	–	Vdc
Collector Cutoff Current (V_{CE} = 200 Vdc, I_B = 0)	I_{CEO}	–	–	100	μAdc
Emitter Cutoff Current (V_{CE} = 5 Vdc, I_C = 0)	I_{EBO}	–	–	100	μAdc
Collector Cutoff Current (V_{CE} = 250 Vdc, $V_{BE(off)}$ = 1.5 Vdc)	I_{CEX}	–	–	100	μAdc
SECOND BREAKDOWN					
Second Breakdown Collector Current with Base Forward Biased	$I_{S/b}$				Adc
(V_{CE} = 50 Vdc, t = 1 s (non−repetitive)		4.0	–	–	
(V_{CE} = 80 Vdc, t = 1 s (non−repetitive)		2.25	–	–	
ON CHARACTERISTICS					
DC Current Gain	h_{FE}				
(I_C = 8 Adc, V_{CE} = 5 Vdc)		25	–	75	
(I_C = 16 Adc, I_B = 5 Adc)		8	–	–	
Base−Emitter On Voltage (I_C = 8 Adc, V_{CE} = 5 Vdc)	$V_{BE(on)}$	–	–	2.2	Vdc
Collector−Emitter Saturation Voltage	$V_{CE(sat)}$				Vdc
(I_C = 8 Adc, I_B = 0.8 Adc)		–	–	1.4	
(I_C = 16 Adc, I_B = 3.2 Adc)		–	–	4	
DYNAMIC CHARACTERISTICS					
Total Harmonic Distortion at the Output	T_{HD}				%
V_{RMS} = 28.3 V, f = 1 kHz, P_{LOAD} = 100 W_{RMS} h_{FE} unmatched		–	0.8	–	
(Matched pair h_{FE} = 50 @ 5 A/5 V) h_{FE} matched		–	0.08	–	
Current Gain Bandwidth Product (I_C = 1 Adc, V_{CE} = 10 Vdc, f_{test} = 1 MHz)	f_T	4	–	–	MHz
Output Capacitance (V_{CB} = 10 Vdc, I_E = 0, f_{test} = 1 MHz)	C_{ob}	–	–	500	pF

PNP MJL21193




Figure 1. Typical Current Gain Bandwidth Product

NPN MJL21194




Figure 2. Typical Current Gain Bandwidth Product

TYPICAL CHARACTERISTICS

PNP MJL21193




Figure 3. DC Current Gain, V_{CE} = 20 V

NPN MJL21194




Figure 4. DC Current Gain, V_{CE} = 20 V

PNP MJL21193




Figure 5. DC Current Gain, V_{CE} = 5 V

NPN MJL21194




Figure 6. DC Current Gain, V_{CE} = 5 V

PNP MJL21193




Figure 7. Typical Output Characteristics

NPN MJL21194




Figure 8. Typical Output Characteristics

TYPICAL CHARACTERISTICS

PNP MJL21193




Figure 9. Typical Saturation Voltages

NPN MJL21194




Figure 10. Typical Saturation Voltages

PNP MJL21193




Figure 11. Typical Base−Emitter Voltage

NPN MJL21194




Figure 12. Typical Base−Emitter Voltage




Figure 13. Active Region Safe Operating Area

There are two limitations on the power handling ability of a transistor; average junction temperature and secondary breakdown. Safe operating area curves indicate $I_C - V_{CE}$ limits of the transistor that must be observed for reliable operation; i.e., the transistor must not be subjected to greater dissipation than the curves indicate.

The data of Figure 13 is based on $T_{J(pk)}$ = 150°C; T_C is variable depending on conditions. At high case temperatures, thermal limitations will reduce the power than can be handled to values less than the limitations imposed by second breakdown.




Figure 14. MJL21193 Typical Capacitance




Figure 15. MJL21194 Typical Capacitance




Figure 16. Typical Total Harmonic Distortion





Figure 17. Total Harmonic Distortion Test Circuit

PACKAGE DIMENSIONS

TO−3BPL (TO−264)
CASE 340G−02
ISSUE J



NOTES:
1. DIMENSIONING AND TOLERANCING PER ANSI Y14.5M, 1982.
2. CONTROLLING DIMENSION: MILLIMETER.

	MILLIMETERS		INCHES	
DIM	MIN	MAX	MIN	MAX
A	28.0	29.0	1.102	1.142
B	19.3	20.3	0.760	0.800
C	4.7	5.3	0.185	0.209
D	0.93	1.48	0.037	0.058
E	1.9	2.1	0.075	0.083
F	2.2	2.4	0.087	0.102
G	5.45 BSC		0.215 BSC	
H	2.6	3.0	0.102	0.118
J	0.43	0.78	0.017	0.031
K	17.6	18.8	0.693	0.740
L	11.2 REF		0.411 REF	
N	4.35 REF		0.172 REF	
P	2.2	2.6	0.087	0.102
Q	3.1	3.5	0.122	0.137
R	2.25 REF		0.089 REF	
U	6.3 REF		0.248 REF	
W	2.8	3.2	0.110	0.125

ON Semiconductor and ON are registered trademarks of Semiconductor Components Industries, LLC (SCILLC). SCILLC reserves the right to make changes without further notice to any products herein. SCILLC makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does SCILLC assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. “Typical” parameters which may be provided in SCILLC data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including “Typicals” must be validated for each customer application by customer’s technical experts. SCILLC does not convey any license under its patent rights nor the rights of others. SCILLC products are not designed, intended, or authorized for use as components in systems intended for surgical implant into the body, or other applications intended to support or sustain life, or for any other application in which the failure of the SCILLC product could create a situation where personal injury or death may occur. Should Buyer purchase or use SCILLC products for any such unintended or unauthorized application, Buyer shall indemnify and hold SCILLC and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that SCILLC was negligent regarding the design or manufacture of the part. SCILLC is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

PUBLICATION ORDERING INFORMATION

LITERATURE FULFILLMENT:
Literature Distribution Center for ON Semiconductor
P.O. Box 5163, Denver, Colorado 80217 USA
Phone: 303−675−2175 or 800−344−3860 Toll Free USA/Canada
Fax: 303−675−2176 or 800−344−3867 Toll Free USA/Canada
Email: orderlit@onsemi.com

N. American Technical Support: 800−282−9855 Toll Free USA/Canada
Europe, Middle East and Africa Technical Support:
Phone: 421 33 790 2910
Japan Customer Focus Center
Phone: 81−3−5773−3850

ON Semiconductor Website: **www.onsemi.com**

Order Literature: http://www.onsemi.com/orderlit

For additional information, please contact your local Sales Representative