



EN: This Datasheet/Document is presented by the manufacturer.

Please visit our website for pricing and availability at www.hestore.hu.

REV.	DESCRIPTION	DRAWN	CHECKED	APPROVED
A	NEW RELEASE	YCH 09/04/08'	~	

NOTES:

- MATERIAL
 - INSULATOR:THERMOPLASTIC(UL 94V-0).
 - CONTACT MATERIAL:COPPER ALLOY.
- SPECIFICATION
 - CURRENT RATING:1.0 Amp.
 - INSULATION RESISTANCE:1000MΩ Min.
 - DIELECTRIC WITHSTANDING:300VAC.
 - CONTACT RESISTANCE:20mΩ Max.
 - OPERATING TEMPERATURE:-40°C TO+105°C.

3. PART NUMBER: DS1031-16

4. PRODUCT NUMBER CODE:





DS1031-16 - X X X X

HOUSING COLOR
B:BLACK

CONTACT PLATING
8: FULL GOLD FLASH
6: FULL TIN

MOUNTING TYPE
V: STRAIGHT TYPE

No.OF CONTACTS
10 20 26 30 34
40 50 60 68 70
80 90 100



RECOMMEND PCB LAYOUT(TOLERANCE=±0.05)

GENERAL TOLERANCE		ANGLE TOLERANCE		PROJECTION	UNIT	TITLE	1.27*2.54mm BOX HEADER PITCH	
X.	±0.60	X.	±5°	mm				
.X	±0.38	.X	±3°					
.XX	±0.25	.XX	±2°					
DRAWING TYPE		CUSTOMER		SHEET SIZE	A4	SERIES	DS1031-16 SERIES	
SCALE	1:1	SHEET	1 OF 1					
DRAWING NO.	C-DS1031-16-XXXX							



晨翔电子有限公司
CONNFLY CONNFLY ELECTRONIC CO. LTD

Tel:86-574-63508787

Fax:86-574-63510817

E-mail:sale@zhenqin.com.cn

Http://www.connfly.com