



EN: This Datasheet/Document is presented by the manufacturer.

Please visit our website for pricing and availability at www.hestore.hu.

FUSIBILE TIPO
FUSE LINK

5 x 20 mm

MONTAGGIO
MOUNTING

PANNELLO
PANEL



Corrente nominale Rated Current	A	10 Pending
Tensione nominale Rated Voltage	VAC	250
Potenza dissipabile Rated Power Acceptance	W	2,5
Corpo isolante Housing	—	PBT - UL 94 V0
Temperatura ambiente ammissibile Admissible ambient air temperature	°C	-30 °C to 85 °C
Protezione contro le scosse elettriche Shocksafe category	PC	PC2
Grado di protezione Degree of protection	IP	IP40
Resistenza di contatto Contact Resistance	mΩ	< 5

 EN 60127-6	Corrente Nominale Rated Current	A	10 Pending
	Tensione nominale Rated Voltage	VAC	250
	Potenza dissipabile Rated Power Acceptance	W	2,5
 UL 512 + C22.2 no. 39	Corrente Nominale Rated Current	A	10
	Tensione nominale Rated Voltage	VAC	250
	Potenza dissipabile Rated Power Acceptance	W	—

Colore standard Standard colour	—	nero - black
Altri colori Other colours	—	A richiesta - On demand
Accessori Accessories	Pag	
Altri dati Other information	Pag	sezione B/ A2- section B/ A2

