



HESTORE.HU



elektronikai alkatrész áruház

EN: This Datasheet is presented by the manufacturer.



Please visit our website for pricing and availability at www.hestore.hu.

Rev	AWO #	Description	Date	Appr
-		RELEASED	4/5/05	

APPROVED: _____
 DATE: _____ TITLE: _____



PCB LAYOUT



SPECIFICATIONS:

- Material: Insulator: Hi-Temp Thermoplastic, rated UL 94V-0
- Insulator color: Black
- Contacts: Brass
- Plating: Gold flash over Nickel underplate overall
- Electrical: Operating voltage: 250 VAC max
- Current rating: 3 Amps max
- Contact resistance: 20 mohms max
- Insulation resistance: 5,000 Mohms min @ 500 VDC
- Dielectric withstanding voltage: 1,000 VAC for 1 minute
- Temperature Rating: Operating temperature: -40°C to +105°C
- Environmental: Lead free, RoHS compliant

Positions: 02 thru 40
 A = .100 [2.54] x No. of Positions
 B = .100 [2.54] x No. of Spaces

ADAM TECH

909 Rahway Avenue, Union, NJ 07083
 Phone: 908-687-5000 Fax: 908-687-5710

.100 [2.54] SINGLE ROW PIN HEADER
 SURFACE MOUNT, TYPE B

UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE IN INCHES [MM]		TITLE	
TOLERANCES: EXCEPT AS NOTED		.100 [2.54] SINGLE ROW PIN HEADER	
INCHES		SURFACE MOUNT, TYPE B	
.X ± .10	ØXX ± .10	SIZE	PART NO.
.XX ± .020	ØXXX ± .015	X	PH1-XX-UA-SMT-B
.XXX ± .015	ØXXXX ± .010	REF:	S00039T
APPROVALS	DATE	SCALE:	NTS
DRAWN	SS	4/5/05	
CHECKED			
APPROVED			
REV.		SHEET 1 OF 1	

